

Overview

HP ZBook Power G10 A Mobile Workstation PC




1. Webcam LED (Optional)
2. Internal Microphones (2)
3. Webcam
4. IR Camera (Optional)
5. Camera Shutter
6. IR Camera LEDs (Optional)
7. Glass Clickpad
8. Power Button Key
9. LED Indicator

Right

10. Power connector
11. USB Type-C® with Thunderbolt™ 4
12. USB 3.2 Gen 1
13. USB 3.2 Gen 1
14. Audio Combo Jack
15. Touch Fingerprint Sensor (Select models)
16. Speakers


Overview



Left

1. Nano Security Lock Slot (Lock sold separately)
2. RJ-45
3. SuperSpeed USB Type-A 5Gbps signaling rate (Charging)
4. HDMI 2.1 Port (Cable not included)
5. Smart Card Reader (optional)

Overview



Bottom

1. Fan Venting

Overview

At A Glance

- Premium ultraslim design with precision-crafted all-metal chassis for a premium look and feel
- Latest AMD® Ryzen PRO 7000 HS series processors and AMD® Ryzen 7000 HS series processors
- Preinstalled with Windows 11 versions or FreeDOS
- 5MP camera (with 88 degree Field of View) with HP Auto Frame allows you to move around without losing viewers' attention during video calls
- New DDR5 5600 memory and PCI Gen4 SSDs provide fast access to your work
- Choice of displays:
 - 39.6 cm (15.6") diagonal, FHD (1920 x 1080), narrow bezel, anti-glare, Touch on Panel (TOP), 250nits, 45% NTSC
 - 39.6 cm (15.6") diagonal, FHD (1920 x 1080), narrow bezel, anti-glare, 250 nits, 45% NTSC
 - 39.6 cm (15.6") diagonal, FHD (1920 x 1080), narrow bezel, anti-glare, Low Blue Light, 400nits, Low-Power, 100% sRGB
 - 39.6 cm (15.6") diagonal, QHD (2560 x 1440), narrow bezel, anti-glare, Low Blue Light, 300 nits, 100% sRGB
- Premium keyboard layout to include easy use of discrete PgUp/Dn, End, and Home keys
- Integrated AMD Radeon Graphics w/ Pro Graphics driver or Optional NVIDIA RTX A1000/2000/4050 ada pro graphics for improved performance for heavier graphics workloads.
- HP Wolf Security for Business creates a hardware-enforced, always-on, resilient defense.9
- Larger Clickpad surface for easier, more intuitive input
- Undergoes MIL-STD 810H 19 tests
- Supports fast charging (50% in 30 minutes) with no impact on battery recharge cycles
- Designed to support all HP docking options

NOTE: See important legal disclosures for all listed specs in their respective features sections.

Features

OPERATING SYSTEM

Preinstalled OS	Windows 11 Pro ² Windows 11 Pro Education ² Windows 11 Home - HP recommends Windows 11 Pro for business ² Windows 11 Home Single Language - HP recommends Windows 11 Pro for business ² Windows 11 Pro (Windows 11 Enterprise or Windows 10 Enterprise available with a Volume Licensing Agreement) ² Windows 11 Pro (preinstalled with Windows 10 Pro Downgrade) ^{2,3} FreeDOS
------------------------	---

² Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

³This system is preinstalled with Windows 10 Pro software and also comes with a license for Windows 11 Pro software and provision for recovery software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.

NOTE: Your product does not support Windows 8 or Windows 7. In accordance with Microsoft's support policy, HP does not support the Windows® 8 or Windows 7 operating system on products configured with Intel® and AMD® 7th generation and forward processors or provide any Windows® 8 or Windows 7 drivers on <http://www.support.hp.com>. A full list of HP products and the Windows 10 versions tested is available on the HP support website. <https://support.hp.com/us-en/document/c05195282>

PROCESSOR

AMD Ryzen™ 5 7640HS (with Radeon NAVI 3 Graphics 4.3 GHz base clock, up to 5.0 GHz max boost clock, 16 MB L3 cache, 6 cores, 12 threads)^{1,2,4}

AMD Ryzen™ 5 PRO 7640HS (4.3 GHz base clock, up to 5.0 GHz max boost clock, 16 MB L3 cache, 6 cores, 12 threads)^{1,2,4}

AMD Ryzen™ 7 7840HS (with Radeon NAVI 3 Graphics 3.8 GHz base clock, up to 5.1 GHz max boost clock, 16 MB L3 cache, 8 cores, 16 threads)^{1,2,4}

AMD Ryzen™ 7 PRO 7840HS (3.8 GHz base clock, up to 5.1 GHz max boost clock, 16 MB L3 cache, 8 cores, 16 threads)^{1,2,4}

AMD Ryzen™ 9 7940HS (with Radeon NAVI 3 Graphics 4.0 GHz base clock, up to 5.2 GHz max boost clock, 16 MB L3 cache, 8 cores, 16 threads)^{1,2,4}

AMD Ryzen™ 9 PRO 7940HS (with Radeon NAVI 3 Graphics 4.0 GHz base clock, up to 5.2 GHz max boost clock, 16 MB L3 cache, 8 cores, 16 threads)^{1,2,4}

¹ Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. AMD's numbering, branding and/or naming is not a measurement of higher performance.

² Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

⁴ In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

Features

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated

AMD Radeon™ Graphics^{3, 4, 5}.

Discrete

NVIDIA RTX A1000 (6 GB)^{2,3,4,5}

NVIDIA RTX 2000 Ada (8GB)^{2,3,4,5}

NVIDIA GeForce RTX 4050^{1,2,3,4,5}

Supports

Support HD decode, DX12, HDMI 2.1, HDCP 2.3

¹ Only available for China.

² Both UMA & Discrete configurations support 4 independent displays when on the HP Thunderbolt Dock G2 (120W) (sold separately) - Max. resolution = 2.5K @60Hz (DP1) & 2.5K @60Hz (DP2) & FHD (VGA) OR 4K @60Hz (one DP Port) & 4K @60Hz (Type-C output port using a Type C-to-DP adapter).

³ Support HD decode, DX12, HDMI 2.0b, HDCP 2.3 via DP up to 4K @ 60Hz and via HDMI up to 4096x2304 @ 60Hz

⁴ HDMI cable Sold Separately

⁵ Shared video memory (UMA) uses part of the total system memory for video performance. System memory dedicated to video performance is not available for other use by other programs.

DISPLAY

Non-touch

- 39.6 cm (15.6") diagonal, FHD (1920 x 1080), narrow bezel, anti-glare, 250 nits, 45% NTSC
- 39.6 cm (15.6") diagonal, FHD (1920 x 1080), narrow bezel, anti-glare, Low Blue Light, 400nits, Low-Power, 100% sRGB
- 39.6 cm (15.6") diagonal, QHD (2560 x 1440), narrow bezel, anti-glare, Low Blue Light, 300 nits, 100% sRGB

Touch

- 39.6 cm (15.6") diagonal, FHD (1920 x 1080), narrow bezel, anti-glare, Touch on Panel (TOP), 250nits, 45% NTSC

Displays support

Supports up to 4 displays through the HP Thunderbolt 280W G4 Dock

¹HD content required to view HD images.

²Sold separately or as an optional feature.

³Resolutions are dependent upon monitor capability, and resolution and color depth settings.

⁴Actual brightness will be lower with touchscreen.

Features

DOCKING

Docking station model #1	HP Thunderbolt™ 280W G4 Dock
Total number of supported displays (incl.the notebook) display)	4
Max.resolutions supported	Quad 4K @60Hz Dual 8K single cable@30 for Thunderbolt™ hosts or USB-C® hosts DisplayPort™ 1.4 with DSC in high res mode
Dock Connectors	2xDisplayPort™, 1xVGA, 1xThunderbolt™, 1xUSB-C® alt-mode
Technical limitations	<p>Thunderbolt™ Hosts: Maximum of (4) displays with maximum resolution of 5K@ 30Hz running Thunderbolt™ host. Max resolution possible is dual 8K displays @ 60Hz running Thunderbolt™ host or running a non-Thunderbolt™ host in High Resolution mode @30Hz</p> <p>Non-Thunderbolt™ hosts: The highest resolution for dual displays running a non-Thunderbolt™ host in multi-function mode is (1) 5K dual cable (using both DisplayPort™ ports) +(1) 4K on USB-C® DisplayPort™ port Non-Thunderbolt™ hosts support (3) displays with a max resolution of: (2) 5K single cable + (1) 4K UHD @ 60 Hz in high resolution mode. In multi-function mode the maximum resolution for (3) displays is (2) 5K single cable @ 30Hz + (1) 4K UHD @ 30Hz.</p>

Features

STORAGE AND DRIVES*

Max Storage

8TB through two m.2 NVMe drivers

(Up to 2) m.2 storage (NVMe PCIe Gen4 SSDs)

Primary M.2 Storage

2 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

1 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

4 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

512 GB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

512 GB PCIe® Gen4x4 NVMe™ SED TLC OPAL2

512 GB PCIe® NVMe™ Value M.2 SSD

Secondary M.2 Storage

2 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

1 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

4 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

512 GB PCIe® Gen4x4 NVMe™ M.2 SSD TLC

512 GB PCIe® Gen4x4 NVMe™ SED TLC OPAL2

* For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 35GB of disk is reserved for system recovery software.

DRIVE CONTROLLERS

M.2 Storage Bay (PCIe NVMe)

RAID:

PCIe® Gen4 x4 lanes NVMe™ Solid State Drive

RAID 0/1 is supported (and available from factory)

MEMORY

Maximum Memory

64GB DDR5-4800

Memory

64GB DDR5-5600 (2x32GB)

32GB DDR5-5600 (2x16GB)

32GB DDR5-5600 (1x32GB)

16GB DDR5-5600 (2x8GB)

16GB DDR5-5600 (1x16GB)

8GB DDR5-5600 (1x8GB)

Memory Slots

2 SODIMM

DDR5 SODIMMS, system runs at 5600

Supports Dual Channel Memory

¹ Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

Features

NETWORKING/COMMUNICATIONS

Ethernet

RTK GBE Ethernet Controller (Non-DASH QFN32) RTL8111HSH-CG

RTK GBE Ethernet Controller RTL8111FPH-CG LAN CHIP

WLAN¹

Mediatek RZ616 Wi-Fi 6E Bluetooth® 5.3 AIM-T WLAN wireless card

Realtek 8852CE Wi-Fi 6E Bluetooth® 5.3 WLAN wireless card

¹ Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

Near Field Communication (NFC) module

No Near Field Communication (NFC) module

NFC Mirage WNC XRAV-1

Miracast

Native Miracast Support

NOTE: Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

AUDIO/MULTIMEDIA

Audio

2 Integrated stereo speakers

Discrete Amplifiers

Integrated dual array microphone

Speaker Power

2W/4ohm Per speaker

Camera^{1,2}

HD camera

5 MP+IR camera

Sensors

Hall effect Sensor

HP Sure Platform

Motion AI LSM6DSL

Thermal Sensor

HP Tamper Lock³

¹ HD content required to view HD images.

² Windows Hello face authentication utilizes a camera specially configured for near infrared (IR) imaging to authenticate and unlock Windows devices as well as unlock your Microsoft Passport.

³ HP Tamper Lock must be enabled by the customer or your administrator.

Features

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard*

HP Premium Keyboard, spill resistant, Backlit keyboard and DuraKeys

HP Premium Keyboard, spill resistant, Non-Backlit keyboard and DuraKeys

Pointing Devices

Clickpad with multi-touch gesture support, taps enabled as default

Microsoft Precision Touchpad Default Gestures Support

Function Keys

ESC: system information

F1 - Display Switching

F2 - Blank

F3 - Brightness Down

F4 - Brightness Up

F5 - Audio Mute

F6 - Volume Down

F7 - Volume Up

F8 - Mic Mute

F9 - Blank or Backlit Toggle

F10 - Insert

F11 - Airplane Mode

F12 - HP Command Center

home

end

Power Button (with LED)

delete

Hidden Keys

Fn+R - Break

Fn+S - Sys Rq

Fn+C - Scroll Lock

*Backlit keyboard is an optional feature.

SOFTWARE AND SECURITY

Software

HP PC Hardware Diagnostics Windows

Touchpoint Customizer for Commercial

myHP

HP Smart Support²⁴

HP Connection Optimizer¹⁰

HP Mac Address Manager

HP Hotkey Support

HP Support Assistant¹

HP Notifications

HP Privacy Settings

HP Power Manager³

Buy Microsoft Office (Microsoft Office sold separately and requires Internet access for activation.)

HP Performance Advisor⁵

Manageability Features

HP Connect for Microsoft Endpoint Manager²⁶

HP Image Assistant Gen5 (download)

HP Manageability Integration Kit (download)¹²

Features

HP Client Management Script Library (download)
HP Patch Assistant (download)²⁷
HP Driver Packs (download)
HP Cloud Recovery ²⁸
HP Client Catalog (download)

Security Management

HP Wolf Security of Business ²⁹ includes:

HP Sure Click ³⁰
HP Sure Sense¹⁹
HP Sure Run Gen5³¹
HP Sure Recover Gen5¹⁴
HP Sure Start Gen7¹⁶
HP Tamper Lock⁴
HP Sure Admin²³
HP Client Security Manager Gen7¹⁸

BIOS

HP BIOSphere Gen6⁶
HP Secure Erase¹⁷
Absolute Persistence Module⁷
HP DriveLock & Automatic DriveLock
BIOS Update via Network
HP Wake on WLAN
HP Fingerprint Sensor³²
Secured-Core PC Enable²⁰
TPM 2.0 Embedded Security Chip (Common Criteria EAL4+ Certified) (FIPS 140-2 Level 2 Certified)

For more information on HP Client Security Software Suite, refer to <http://www.hp.com/go/clientsecurity>.

¹ HP Support Assistant - Requires Windows and Internet Access.

³HP Power Manager requires Windows 10 and higher and can be downloaded from the Microsoft Store.

⁴HP Tamper Lock must be enabled by the customer or your administrator.

⁵ HP Performance Advisor is ready and waiting to help you get the most out of your HP Workstation from day one—and every day after. Learn more or download at: <https://www.hp.com/us-en/workstations/performanceadvisor.html>

⁶ HP BIOSphere Gen6 is available on select HP Pro, Elite and ZBook PCs. See product specifications for details. Features may vary depending on the platform and configurations.

⁷ Absolute Persistence Module: Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.

¹⁰ HP Connection Optimizer requires Windows 10 and beyond version.

¹² HP Manageability Integration Kit can be downloaded from <http://www.hp.com/go/clientmanagement>.

¹⁴ HP Sure Recover Gen5 with Embedded Reimaging is an optional feature which requires Windows 10 and higher must be configured at purchase. You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Network based recovery using Wi-Fi is only available on PCs with Intel Wi-Fi Module

¹⁵ HP Sure Recover with Embedded Reimaging Gen3 is an optional feature which must be configured at purchase with a base unit that has the On System Recovery (OSR) module . See product specifications for availability You must back up important files, data, photos, videos, etc. before use to avoid loss of data. HP Sure Recover with Embedded Reimaging (Gen1) does not support platforms with Intel® Optane™.

¹⁶ HP Sure Start Gen7 is available on select HP PCs and requires Windows 10 and higher

¹⁷ HP Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.

¹⁸ HP Client Security Manager Gen7 requires Windows and is available on select HP Pro, Elite and ZBook PCs. See product specifications for details.

¹⁹ HP Sure Sense is available on select HP PCs with Windows 10 Pro, Windows 10 Enterprise, Windows 11 Pro, or Windows 11 Enterprise OS.

Features

- ²⁰ Secured-core PC requires an Intel® vPro® or AMD Ryzen™ Pro processor. Requires 8 GB or more system memory. Secured-core PC functionality can be enabled from the factory.
- ²³ HP Sure Admin requires Windows 10, HP BIOS, HP Manageability Integration Kit from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.
- ²⁴ HP Smart Support requires HP TechPulse to be installed. For more information about how to enable or to download HP Smart Support, please visit <http://www.hp.com/smart-support>.
- ²⁶ HP Connect for Microsoft Endpoint Manager is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.
- ²⁷ HP Patch Assistant available on select HP PCs with the HP Manageability Kit that are managed through Microsoft System Center Configuration Manager. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>.
- ²⁸ HP Cloud Recovery is available for Z by HP, HP Elite and Pro desktops and laptops PCs with Intel® or AMD processors and requires an open, wired network connection. **NOTE:** You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Detail please refer to: <https://support.hp.com/us-en/document/c05115630>.
- ²⁹ HP Wolf Security for Business requires Windows 10 or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features and OS requirement.
- ³⁰ HP Sure Click requires Windows 10 Pro or higher or Enterprise. See https://bit.ly/2PrLT6A_SureClick for complete details.
- ³¹ HP Sure Run Gen5 is available on select HP PCs and requires Windows 10 and higher.
- ³² HP Fingerprint Reader is an optional feature that requires Windows 10 IoT and must be configured at purchase.

Features

POWER

Power Supply

HP Smart 120 W External AC power adapter³

HP Smart 150 W External AC power adapter⁴

Battery

HP Long Life 6-cell, 83 Wh Li-ion Polymer

Power Cord

3-wire plug - 1m

Battery life

Up to 19 hours 30 minutes (UMA SKU)

14 hours 30min (discrete GFX SKU)

¹ MobileMark18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.

² Battery is internal and not replaceable by customer. Serviceable by warranty.

³ Only available with UMA graphics

⁴ Only available with discrete graphic options

⁵ Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

ENVIRONMENTAL

ENERGY STAR[®] certified

EPEAT[®] registered where applicable. EPEAT[®] registration varies by country. See www.epeat.net for registration status by country.

EPEAT[®] Gold¹

TCO 8.0 Certified

RCTA DO-160G

Medical EMC: IEC 60601-1-2:2014 EN60601-1-2: 2015

SEPA

GS Mark

Eyesafe Certification - Worldwide

Sustainable Impact Specifications

Recycled Aluminum and Magnesium, 75% PCR w/30% ITE plastics

¹ Based on US EPEAT[®] registration according to IEEE 1680.1-2018 EPEAT[®]. Status varies by country. Visit www.epeat.net for more information.

Features

WEIGHTS & DIMENSIONS

Dimensions (w x d x h)

35.94 x 23.39 x 2.29 cm

14.15 x 9.21 x 0.9 in

Weights*

Starting at 1.96 kg (4.32 lb)

*Weight will vary by configuration. Does not include power adapter.

PORTS/SLOTS

1 Thunderbolt™ 4 with USB4 Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)

3 Super Speed USB Type-A 5Gbps signaling rate (1 charging)

1 HDMI 2.1

1 Headphone/microphone combo jack

1 Nano Security Lock Slot (Lock sold separately)

1 Smartcard reader (Optional)

*SuperSpeed USB 20Gbps is not available with Thunderbolt™ 4.

*HDMI cable sold separately.

COMPATIBILITY

HP Wired USB-A Stereo Headset	428K6AA
HP Renew Business 17.3 Laptop Backpack	3E2U5AA
HP Universal USB-C Multiport Hub	50H55AA
HP Multi-Device 635 Black Wireless Mouse	1D0K2AA
HP 975 USB+Bluetooth® Dual-Mode Wireless Keyboard	3Z726AA

SERVICE AND SUPPORT

1-year warranty and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for HP Long Life batteries which will follow the one or three year warranty of the platform. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.

¹HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)	Nominal Operating Voltage	19.5V
--	----------------------------------	-------

Features

	System in idle mode + max panel brightness	8.09W
	Integrated graphics	Yes
	Discrete Graphics	Yes
	Max Operating Power	<150W
Temperature	Operating	32° to 95° F (0° to 35° C)
	Non-operating	-4° to 140° F (-20° to 60° C)
Relative Humidity	Operating	10% to 90%, non-condensing
	Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
Shock	Operating	40G, 2ms
	Non-operating	240G, 2ms
Random Vibration	Operating	1.043 grms
	Non-operating	3.5 grms
Maximum Altitude (unpressurized)	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Temperature Derating with Altitude	Operating	1.8°F / 1000 ft (1°C / 304.8 m)
Planned Industry Standard Certifications	Regulatory Model Number	HSN-Q37C
	CSA/UL 62368-1	Yes
	CSA	Yes
	FCC/ICES/CISPR/VCCI	Yes
	ENERGY STAR®	Select models ¹
	EPEAT Gold	EPEAT Gold in United States ²
	TCO	Yes
	China CCC/SRRC	Yes
	Korea KCC/KC/KES	Yes
	Taiwan BSMI/NCC	Yes
	CE MARKING	Yes
	EAEU compliance	Yes
	CITC	Yes
	WW RoHS	Yes
	EAEU compliance	Yes
	Saudi Arabian Compliance	Yes
	Ukraine NSoC/TEC	Yes
	Low Blue Light	Yes

¹Configurations of the HP ZBook Power G10 A Mobile Workstation PC that are ENERGY STAR® qualified are identified as HP ZBook Power G10 A Mobile Workstation PC ENERGY STAR on HP websites and on <http://www.energystar.gov>.

²Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit www.epeat.net for more information.

Technical Specifications – Displays

DISPLAYS

Panel LCD 15.6 inch FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR bent Touch on Panel NWBZ	Outline Dimensions (W x H)	350.96 x 205.74 mm (max)		
	Active Area	344.16 x 193.59 mm (typ.)		
	Weight	380 g (max)		
	Diagonal Size	15.6 inch		
	Thickness	3.2 mm / 5.2 mm (max)		
	Interface	eDP 1.2		
	Surface Treatment	Anti-Glare On-cell		
	Touch enabled	Yes		
	Contrast Ratio	600:1 (typ)		
	Refresh Rate	60 Hz		
	Brightness	250 nits (typ)		
	Pixel Resolution	Pitch	1920 x 1080 (FHD)	
		Format	RGB Stripe	
	Backlight	LED		
	Color Gamut Coverage	NTSC 45%		
	Color Depth	6		
	Viewing Angle	UWVA 85/85/85/85		
Low Blue Light	No			
Power Consumption (W, EBL@ 150nits max/ 200nits max)	2.54 (Max) / 3.12 (Max)			

*All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

15.6 in FHD (1920 x 1080) Anti-Glare UWVA Low Blue Light sRGB NB2X 400 eDP 1.4+PSR2 Low-Power 100 bent LCD Panel	Outline Dimensions (W x H)	349.460 x 204.790 (max)		
	Active Area	344.160 x 193.590 mm (typ)		
	Weight	310 g (max)		
	Diagonal Size	15.6 (inch)		
	Thickness	2.6 mm / 4.8 mm (max)		
	Interface	eDP1.4		
	Surface Treatment	Anti-Glare		
	Touch enabled	No		
	Contrast Ratio	1200:1 (typ)		
	Refresh Rate	60 Hz		
	Brightness	400 nits (typ)		
	Pixel Resolution	Pitch	1920 x 1080 (FHD)	
		Format	RGB Stripe	
	Backlight	WLED		
	Color Gamut Coverage	sRGB 100%		
	Color Depth	8		
	Viewing Angle	UWVA 89/89/89/89		
Low Blue Light	Yes			
Power Consumption (W,	1.27 (max) / 1.5 (max)			

Technical Specifications – Displays

EBL@ 150nits max/ 200nits max)

*All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

15.6 inch FHD (1920x1080) Anti-Glare WLED UWVA 45percent cg 250nits eDP 1.2 w/o PSR bent NWBZ

Outline Dimensions (W x H)	350.960 x 205.540 (max)	
Active Area	344.160 x 193.590 mm (typ)	
Weight	370 g (max)	
Diagonal Size	15.6	
Thickness	3.0 mm / 5.0 mm (max)	
Interface	eDP 1.2	
Surface Treatment	Anti-Glare	
Touch enabled	No	
Contrast Ratio	600:1 (typ)	
Refresh Rate	60 Hz	
Brightness	250 nits (typ)	
Pixel Resolution	Pitch	1920 x 1080 (FHD)
	Format	RGB Stripe
Backlight	LED	
Color Gamut Coverage	NTSC 45%	
Color Depth	6 (Hi FRC w/ condition to enable)	
Viewing Angle	UWVA 85/85/85/85	
Low Blue Light	No	
Power Consumption (W, EBL@ 150nits max/ 200nits max)	2.62 (Max) / 3.27 (Max)	

*All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

15.6 in QHD (2560 x 1440) Anti-Glare UWVA Low Blue Light sRGB NWBZ 300 eDP 1.4+PSR2 100 120Hz bent LCD Panel

Outline Dimensions (W x H)	350.960 x 205.550 (max)	
Active Area	344.2176 x 193.6224 mm	
Weight	300 g (max)	
Diagonal Size	15.6	
Thickness	2.6mm /4.6 mm (Max)	
Interface	eDP 1.4	
Surface Treatment	Anti-Glare	
Touch Enabled	No	
Contrast Ratio	1000:1 (typ)	
Refresh Rate	120 Hz	
Brightness	300 nits (typ)	
Pixel Resolution	Pitch	2560x1440 (QHD)
	Format	RGB Stripe

Technical Specifications – Displays

Backlight	WLED
Color Gamut Coverage	sRGB 100%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	Yes
Power Consumption (W, EBL@ 150nits max/ 200nits max)	3.41 (max) / 4.06 (max)

*All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Technical Specifications – Storage

STORAGE AND DRIVES

SSD 512GB 2280 PCIe-4x4 NVMe Three Layer Cell	Form Factor	M.2 2280		
	Capacity	512GB		
	NAND Type	TLC		
	Height	0.09 in (2.3 mm)		
	Width	0.87 in (22 mm)		
	Weight	0.02 lb (10 g)		
	Interface	PCIe NVMe Gen4X4		
	Performance	Minimum Sequential Read	Minimum Sequential Write	
		6400 MB/s ±10%	3500 MB/s ±10%	
	Logical Blocks	1,000,215,215		
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]		
Features	Pyrite 2.0; TRIM; L1.2			
	NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 35 GB (for Windows 10) is reserved for system recovery software.			
SSD 1TB 2280 PCIe-4x4 NVMe Three Layer Cell	Form Factor	M.2 2280		
	Capacity	1TB		
	NAND Type	TLC		
	Height	0.09 in (2.3 mm)		
	Width	0.87 in (22 mm)		
	Weight	0.02 lb (10 g)		
	Interface	PCIe NVMe Gen4X4		
	Performance	Minimum Sequential Read	Minimum Sequential Write	
		6400 MB/s ±10%	5000 MB/s ±10%	
	Logical Blocks	2,000,409,264		
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]		
Features	Pyrite 2.0; TRIM; L1.2			
	NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 35 GB (for Windows 10) is reserved for system recovery software.			
SSD 2TB 2280 PCIe-4x4 NVMe Three Layer Cell	Form Factor	M.2 2280		
	Capacity	2TB		
	NAND Type	TLC		
	Height	0.09 in (2.3 mm)		
	Width	0.87 in (22 mm)		
	Weight	0.02 lb (10 g)		
	Interface	PCIe NVMe Gen4X4		
	Performance	Minimum Sequential Read	Minimum Sequential Write	
		6400 MB/s ±10%	5000 MB/s ±10%	
	Logical Blocks	4,000,797,360		
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]		
Features	Pyrite 2.0; TRIM; L1.2			
	NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 35 GB (for Windows 10) is reserved for system recovery software.			

Technical Specifications – Storage

512GB PCIe-4x4 2280 NVME Self Encrypted OPAL2 Three Layer Cell Solid State Drive	Form Factor	M.2 2280		
	Capacity	512GB		
	NAND Type	Opal2 TLC		
	Height	0.09 in (2.3 mm)		
	Width	0.87 in (22 mm)		
	Weight	0.02 lb (10 g)		
	Interface	PCIe NVMe Gen4X4		
	Performance	Minimum Sequential Read	Minimum Sequential Write	
		6400 MB/s ±10%	3500 MB/s ±10%	
	Logical Blocks	1,000,215,215		
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]		
Features	TCG Opal 2.0; TRIM; L1.2			
	NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 35 GB (for Windows 10) is reserved for system recovery software.			
4TB PCIe-4x4 2280 NVMe Three Layer Cell double-sided M.2 Solid State Drive	Form Factor	M.2 2280		
	Capacity	4TB		
	NAND Type	TLC		
	Height	0.09 in (2.3 mm)		
	Width	0.87 in (22 mm)		
	Weight	15g		
	Interface	PCIe NVMe Gen4X4		
	Performance	Minimum Sequential Read	Minimum Sequential Write	
		6400 MB/s ±10%	5000 MB/s ±10%	
	Logical Blocks	8,001,594,720		
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]		
Features	Pyrite 2.0; TRIM; L1.2			
	NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 35 GB (for Windows 10) is reserved for system recovery software.			
SSD 512GB 2280 PCIe NVMe Value	Form Factor	M.2 2280		
	Capacity	512GB		
	NAND Type	TLC		
	Height	0.09 in (2.3 mm)		
	Width	0.87 in (22 mm)		
	Weight	0.02 lb (10 g)		
	Interface	PCIe NVMe		
	Performance	Minimum Sequential Read	Minimum Sequential Write	
		2200 MB/s ±10%	1000 MB/s ±10%	
	Logical Blocks	1000215216		
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]		
Features	Pyrite 2.0; TRIM; L1.2			
	NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 35 GB (for Windows 10) is reserved for			

Technical Specifications – Storage

[system recovery software.](#)

Technical Specifications – Networking

NETWORKING/COMMUNICATION

Realtek RTL8852CE	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11i IEEE 802.11k
802.11ax 2x2 Wi-Fi 6E + Bluetooth® 5.3 (802.11ax 2x2, supporting gigabit data rate) wireless card [1]		Wi-Fi certified
	Interoperability	802.11b/g/n/ax
	Frequency Band	• 2.402 – 2.482 GHz 802.11a/n/ac/ax • 5.15 – 5.25 GHz • 5.25 – 5.35 GHz • 5.47 – 5.725 GHz • 5.825 – 5.850 GHz
	Data Rates	• 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac: MCS0 ~ MCS9, (20MHz, 40MHz, ,80MHz & 160MHz) • 802.11ax: MCS0 ~ MCS11, (20MHz, 40MHz, ,80MHz & 160MHz)
	Modulation	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
	Security¹	• IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • WPA3 (personal) certification • IEEE 802.11i • WAPI • EAP
	Network Architecture	Ad-hoc (Peer to Peer)
	Models	Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power²	• 802.11b : +17dBm minimum • 802.11g : +16dBm minimum • 802.11a : +17dBm minimum • 802.11n HT20(2.4GHz) : +14dBm minimum • 802.11n HT40(2.4GHz) : +13dBm minimum • 802.11n HT20(5GHz) : +14dBm minimum • 802.11n HT40(5GHz) : +13dBm minimum • 802.11ac VHT80(5GHz) : +10dBm minimum • 802.11ac VHT160(5GHz) : +10dBm minimum

Technical Specifications – Networking

	<ul style="list-style-type: none"> • 802.11ax HE40(2.4GHz) : +12dBm minimum • 802.11ax HE80(5GHz) : +10dBm minimum • 802.11ax HE160(5GHz) : +10dBm minimum • 802.11ax HE80(6GHz) : +10dBm minimum • 802.11ax HE160(6GHz) : +10dBm minimum
Power Consumption	<ul style="list-style-type: none"> • Transmit mode :2.5 W • Receive mode :2 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode :50 mW (WLAN unassociated) • Connected Standby/Modern Standby: 10mW • Radio disabled: 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity³	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -84dBm maximum 802.11a/g, 6Mbps : -86dBm maximum 802.11a/g, 54Mbps : -72dBm maximum 802.11n, MCS07 : -67dBm maximum 802.11n, MCS15 : -64dBm maximum 802.11ac, MCS0(VHT80) : -84dBm maximum 802.11ac, MCS9(VHT80) : -59dBm maximum 802.11ac, MCS9(VHT160) : -58.5dBm maximum •802.11ax, MCS11(HE40): -57dBm maximum •802.11ax, MCS11(HE80): -54dBm maximum •802.11ax, MCS11(HE160): -53.5dBm maximum
Antenna Type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230 : 2.8g 2. Type 126: 1.3g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
Humidity	Operating 10% to 60% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating Non-operating 0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)
LED Activity	N/A
HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Technology	
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps,

Technical Specifications – Networking

	voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth Software Supported	Microsoft Windows Bluetooth Software
Link Topology	
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.407
Power Management	ETS 300 328
Certifications	Low Voltage Directive CE Mark
Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) BT5.2 ESR9/10 Compliance LE Advertisement Extensions Channel Selection Algo Limited High Duty Cycle Non-Connectable Advertising 2Mbps LE LE Long Range Windows BT profiles support BT5.3 Periodic Advertisement interval Encryption key size control enhancements

*Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, and Windows 11 to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

[2] Check latest software/driver release for updates on supported security features.

[3] The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

[4] Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Technical Specifications – Networking

Mediatek RZ616 Wi-Fi 6E Wireless LAN Standards + Bluetooth® 5.3 (802.11ax 2x2, supporting gigabit data rate) wireless card [1]

	<ul style="list-style-type: none">IEEE 802.11aIEEE 802.11bIEEE 802.11gIEEE 802.11nIEEE 802.11acIEEE 802.11axIEEE 802.11dIEEE 802.11eIEEE 802.11hIEEE 802.11iIEEE 802.11jIEEE 802.11kIEEE 802.11mcIEEE 802.11rIEEE 802.11vIEEE 802.11w
Interoperability	Wi-Fi certified
Frequency Band	802.11b/g/n/ax <ul style="list-style-type: none">• 2.402 – 2.482 GHz
	802.11a/n/ac/ax <ul style="list-style-type: none">• 5.15 – 5.25 GHz• 5.25 – 5.35 GHz• 5.47 – 5.725 GHz• 5.825 – 5.850 GHz• 5.925 – 7.125 GHz
Data Rates	<ul style="list-style-type: none">• 802.11b: 1, 2, 5.5, 11 Mbps• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)• 802.11ac: MCS0 ~ MCS9, (20MHz, 40MHz, ,80MHz & 160MHz)• 802.11ax: MCS0 ~ MCS11, (20MHz, 40MHz, ,80MHz & 160MHz)
Modulation	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
Security¹	<ul style="list-style-type: none">• IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only• AES-CCMP: 128 bit in hardware• 802.1x authentication• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.• WPA2 certification• WPA3 (personal) certification• IEEE 802.11i• WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	2.4GHz (MIMO, typical): <ul style="list-style-type: none">• 802.11b : +18dBm• 802.11g : +16.5dBm• 802.11n/ac/ax (HT20/VHT20/HE20) : +16dBm• 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm 5GHz (MIMO, typical):

Technical Specifications – Networking

	<ul style="list-style-type: none"> • 802.11a : +13dBm • 802.11n/ac/ax (HT20/VHT20/HE20) : +13.5dBm • 802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm • 802.11ac/ax (VHT80/HE80) : +11.5dBm • 802.11ax HE160 : +11.5dBm 				
	<p>6GHz LPI mode (MIMO, typical)::</p> <ul style="list-style-type: none"> • 802.11a : 0dBm • 802.11ax HE20 : +1dBm • 802.11ax HE40 : +4dBm • 802.11ax HE80 : +7dBm • 802.11ax HE160 : +7.5dBm 				
Power Consumption	<ul style="list-style-type: none"> • Transmit mode :2.5 W • Receive mode :2 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode :50 mW (WLAN unassociated) • Connected Standby/Modern Standby: 10mW • Radio disabled: 8 mW 				
Power Management	<p>ACPI and PCI Express compliant power management 802.11 compliant power saving mode</p>				
Receiver Sensitivity³	<p>2.4GHz (SISO):</p> <ul style="list-style-type: none"> • 802.11b, 11Mbps : -82dBm maximum • 802.11g, 54Mbps : -71dBm maximum • 802.11n, MCS7 : -64dBm maximum • 802.11ac, MCS9 : -52dBm maximum • 802.11ax, MCS11(HT40): -49dBm maximum <p>5GHz (SISO):</p> <ul style="list-style-type: none"> • 802.11a, 54Mbps : -71dBm maximum • 802.11n, MCS07 : -64dBm maximum • 802.11ac, MCS9 : -52dBm maximum • 802.11ax, MCS11(HE80/HE160): -46dBm maximum <p>6GHz (SISO):</p> <ul style="list-style-type: none"> • 802.11a, 54Mbps : -71dBm maximum • 802.11n, MCS7 : -64dBm maximum • 802.11ac, MCS9 : -52dBm maximum • 802.11ax, MCS11(HE160): -46dBm maximum 				
Antenna Type	<p>High efficiency antenna with spatial diversity, mounted in the display enclosure</p> <p>Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications</p>				
Form Factor	<p>PCI-Express M.2 MiniCard</p>				
Dimensions	<p>1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm</p>				
Weight	<p>1. Type 2230 : 2.8g 2. Type 126: 1.3g</p>				
Operating Voltage	<p>3.3v +/- 9%</p>				
Temperature	<table border="0"> <tbody> <tr> <td>Operating</td> <td>14° to 158° F (-10° to 70° C)</td> </tr> <tr> <td>Non-operating</td> <td>-40° to 176° F (-40° to 80° C)</td> </tr> </tbody> </table>	Operating	14° to 158° F (-10° to 70° C)	Non-operating	-40° to 176° F (-40° to 80° C)
Operating	14° to 158° F (-10° to 70° C)				
Non-operating	-40° to 176° F (-40° to 80° C)				
Humidity	<table border="0"> <tbody> <tr> <td>Operating</td> <td>10% to 60% (non-condensing)</td> </tr> <tr> <td>Non-operating</td> <td>5% to 95% (non-condensing)</td> </tr> </tbody> </table>	Operating	10% to 60% (non-condensing)	Non-operating	5% to 95% (non-condensing)
Operating	10% to 60% (non-condensing)				
Non-operating	5% to 95% (non-condensing)				
Altitude	<table border="0"> <tbody> <tr> <td>Operating Non-operating</td> <td>0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)</td> </tr> </tbody> </table>	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)		
Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)				

Technical Specifications – Networking

LED Activity	N/A
HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Technology	
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class 1.5 Bluetooth device with a maximum transmit power of + 14 dBm and 10 dBm for BR and EDR, respectively.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth Software Supported	
Link Topology	Microsoft Windows Bluetooth Software
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.407
Power Management Certifications	
Bluetooth Profiles Supported	ETS 300 328 Low Voltage Directive CE Mark BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) BT5.2 ESR9/10 Compliance LE Advertisement Extensions Channel Selection Algo Limited High Duty Cycle Non-Connectable Advertising 2Mbps LE LE Long Range Windows BT profiles support

Technical Specifications – Networking

BT5.3
 Periodic Advertisement interval
 Encryption key size control enhancements

*Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, and Windows 11 to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 6E is supported.

[2] Check latest software/driver release for updates on supported security features.

[3] The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

[4] Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

NFC Mirage module (NXP NPC300 I2C 10mmx17mm)

Dimensions (L x W x H)	Module 25 mm by 10 mm by 2.0 mm
Chipset	NPC300
System interface	I2C
NFC RF standards	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
NFC Forum Support	Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2
Reader (PCD-VCD) Mode	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K MIFARE DESFire FeliCa Jewel and Topaz cards
Card Emulation (PICC-VICC) Mode	ISO/IEC 14443 A ISO/IEC 14443 B and B' MIFARE FeliCa
Frequency	13.56 MHz
NFC Modes Supported	Reader/Writer, Peer-to-Peer
Raw RF Data Rates	106, 212, 424, 848 kbps
Operating temperature	0°C to 70°C
Storage temperature	-20°C to 125°C
Humidity	10-90% operating 5-95% non-operating
Supply Operating voltage	4.35 to 5.25 Volts
I/O Voltage	1.8V or 3.3V
Power Consumption	Booster enable, VBAT= 3.3V,

Technical Specifications – Networking

VCC_BOOST = 5V)	Polling	7.3 mA
Mode Power	Detected Test	Total 283.8 mA
Consumption,	Tag Type 1	Net Module 236.8 mA
Typical	Detected Test	Total 288.8 mA
	Tag Type 2	Net Module 241.8 mA
	Detected Test	Total 287.7 mA
	Tag Type 3	Net Module 240.7 mA
	Detected Test	Total 282.3 mA
	Tag Type 4	Net Module 235.3 mA

Antenna Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.

Realtek RTL8111FPH 10/100/1000 Integrated NIC

Connector	RJ-45
System Interface	PCIe + SMBus
Data rates supported	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
IEEE Compliance	IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet)
Performance	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling Jumbo Frame 9K
Power consumption	Cable Disconnection: 25mW 100Mbps Full Run: 450mW 1000bp Full Run: 1000mW WoL Enable(S3/S4/S5): 50mW WoL Disable(S3/S4/S5): 25mW
Power Management	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
Management Interface	Auto MDI/MDIX Crossover cable detection Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite
IT Manageability	Virtual Cable Doctor for Ethernet cable status
Security & Manageability	Support DASH 1.2 compliant

Realtek RTL8111HSH 10/100/1000 Integrated NIC

Connector	RJ-45
System Interface	PCIe + SMBus
Data rates supported	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14)

Technical Specifications – Networking

	100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30)
	1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40)
	Auto-Negotiation (Automatic Speed Selection)
	Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
	IEEE 802.1p QoS (Quality of Service) Support
	IEEE 802.1q VLAN support
	IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)
IEEE Compliance	IEEE 802.3az EEE (Energy Efficient Ethernet)
	TCP/IP/UDP Checksum Offload (configurable)
	Protocol Offload (ARP & NS)
	Large send offload and Giant send offload
	Receiving Side Scaling
Performance	Jumbo Frame 9K
	Cable Disconnection: 25mW
	100Mbps Full Run: 450mW
	1000bp Full Run: 1000mW
Power consumption	WoL Enable(S3/S4/S5): 50mW
	WoL Disable(S3/S4/S5): 25mW
Power Management	ACPI compliant – multiple power modes
	Situation-sensitive features reduce power consumption
Management Interface	Advanced link down power saving for reducing link down power consumption
	Auto MDI/MDIX Crossover cable detection
	Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)
	PXE 2.1 Remote Boot
	Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))
IT Manageability	Comprehensive diagnostic and configuration software suite
	Virtual Cable Doctor for Ethernet cable status

AUDIO

HD Stereo Codec	Realtek ALC3247
Audio I/O Ports	Headset : CTIA only and Headphone-out
Internal Speaker Amplifier	Realtek Class-D
Multi-streaming Capable	Playback multi-streaming can be enabled in the audio control panel to allow independent audio. Following MSFT Behaviour
Sampling	DAC:48kHz ADC:48kHz
Wavetable Syntheses	
Analog Audio	Support 3.5mm Headset : CTIA only and Headphone-out
# of Channels on Line-Out	
Internal Speaker	Yes

FINGERPRINT READER

Sensor vendor	ELAN 80SW
Sensor type	Capacitive
DPI resolution	508 DPI

Technical Specifications – Networking

Scan area	80x80 pixels
False Rejection Rate	<3%
False Acceptance Rate	< 0.001%
Mobile Voltage Operation	2.7~3.6V
Operating Temperature	-20°C - +80°C
Current Consumption Image	35mA peak
Low Latency Wait For Finger	300uA
Capture Rate	Capture Rate: 50 frame/sec
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	508 dpi / 4x4mm sensor area

POWER

AC Adapter 150 Watt Smart PFC Slim Barrel 4.5mm Right Angle	Dimensions	5.43 x 2.59 x 0.39 in (13.8x6.6x2.2cm)	
	Weight	0.716 lb (325 g) max (Not including power cord. Power cord varies by country.)	
	Input	Input Efficiency	88% at 115 Vac and 89% at 230Vac
		Input frequency range	47 ~ 63 Hz
		Input AC current	Max. 2.7 A at 90 Vac
	Output	Output power	150W
		DC output	19.5V
		Hold-up time	100% load 5ms at 115 Vac input
		Output current limit	<16.0A
		Connector	C6
	Environmental Design	DC Plug	4.5mm Barrel Type
		Operating temperature	32° to 95° F (0° to 35° C)
		Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
		Altitude	0 to 16,400 ft (0 to 5000m)
		Humidity	20% to 95
Storage Humidity		10% to 95%	
EMI and Safety Certifications	<p>*CE Mark - full compliance with LVD and EMC directives</p> <p>*Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1</p> <p>*Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC), NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC</p>		

AC Adapter 120 Watt Smart PFC Slim Barrel	Dimensions	5.433 x 2.697 x 1.0 in (13.8x6.85x2.54cm)
	Weight	0.88 lb (400 g) max (Not including power cord. Power cord varies by

Technical Specifications – Networking

4.5mm Right Angle

		country.)	
Input	Input Efficiency	88% at 115 Vac and 89% at 230Vac	
	Input frequency range	47 ~ 63 Hz	
	Input AC current	Max. 1.7 A at 90 Vac	
Output	Output power	120W	
	DC output	19.5V	
	Hold-up time	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input	
	Output current limit	<18.0A	
Connector		C6	
	DC Plug	4.5mm Barrel Type	
Environmental Design	Operating temperature	32° to 95° F (0° to 35° C)	
	Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)	
	Altitude	0 to 16,400 ft (0 to 5000m)	
	Humidity	20% to 95	
	Storage Humidity	10% to 95%	
EMI and Safety Certifications	<p>*CE Mark - full compliance with LVD and EMC directives *Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1 *Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC), NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC</p>		

Technical Specifications – Power

Battery 6 Cell WHr 83 Long Life -PL Fast Charge	Dimensions (H x W x L)	7.78 x 316.1 x 70.2mm (0.306 x 12.44 x 2.763 inch)
	Weight	0.31kg (0.683lb)
	Cells/Type	6cell Lithium-Ion Polymer cell / 685257
	Energy	Voltage 11.58V Amp-hour capacity 7.170Ah Watt-hour capacity 83Wh
	Temperature	Operating (Charging) 32° to 113° F (0° to 45° C) Operating (Discharging) 14° to 122° F (-10° to 60° C)
	Fuel Gauge LED	NA
	Warranty	Refer to http://www.hp.com/support/batterywarranty/ for battery warranty information.
	Optional Travel Battery Available	N/A

*Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year or 3-year limited warranty as the platform.

Technical Specifications – Environmental

ENVIRONMENTAL DATA

Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- US Federal Energy Management Program (FEMP)
- EPEAT[®] Gold registered in the United States. See <http://www.epeat.net> for registration status in your country.
- TCO Certified
- China Energy Conservation Program (CECP)
- China State Environmental Protection Administration (SEPA)
- Taiwan Green Mark
- Korea Eco-label
- Japan PC Green label*

Sustainable Impact Specifications

- Product Carbon Footprint (hp.com)
- Ocean-bound plastic in Speaker
- 14.3% post-consumer recycled plastic
- 50% recycled metal
- Low halogen
- Outside Box and corrugated cushions are 100% sustainably sourced and recyclable
- Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable
- Bulk packaging available

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a “Typically Configured Notebook”.

Energy Consumption (in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
Normal Operation (Short idle)	7.38 W	7.29 W	7.17 W
Normal Operation (Long idle)	N/A	N/A	N/A
Sleep	3.62 W	3.74 W	3.55 W
Off	0.36 W	0.40 W	0.36 W

NOTE:

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

Heat Dissipation*

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
Normal Operation (Short idle)	25 BTU/hr	25 BTU/hr	25 BTU/hr
Normal Operation (Long idle)	N/A	N/A	N/A
Sleep	12 BTU/hr	13 BTU/hr	12 BTU/hr

Technical Specifications – Environmental

Off 1 BTU/hr 1 BTU/hr 1 BTU/hr

***NOTE:** Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)

Sound Power
(L_{Wad} , bels)

Sound Pressure
(L_{pAm} , decibels)

Typically Configured – Idle
Fixed Disk – Random writes
Optical Drive – Sequential
reads

2.6
2.7
3.5

13.
13.6
25.6

Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the

Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product is 94.3% recycle-able when properly disposed of at end of life.

Packaging Materials

External:	PAPER/Corrugated	295g
	PAPER/Molded pulp	170g
Internal:	PLASTIC/Polyethylene low density-LDPE	10g

The plastic packaging material contains at least 0.0% recycled content.

The corrugated paper packaging materials contains at least 58.8% recycled content.

RoHS Compliance

HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.

We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.

We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.

Technical Specifications – Environmental

To obtain a copy of the HP RoHS Compliance Statement, see [HP RoHS position statement](#).

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Bis(2-Ethylhexyl) phthalate (DEHP)
- Benzyl butyl phthalate (BBP)
- Dibutyl phthalate (DBP)
- Diisobutyl phthalate (DIBP)
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>.

Technical Specifications – Environmental

These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

HP Inc. Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www8.hp.com/us/en/hp-information/environment/ecolabels.html>

ISO 14001 certificates:

<http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842>

and

<http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf>

Footnotes

¹Percentage of ocean-bound plastic contained in each component varies by product

²Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.

³External power supplies, WWAN modules, power cords, cables and peripherals excluded.

⁴100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.

⁵Fiber cushions made from 100% recycled wood fiber and organic materials.

⁶Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams

Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part #
Cases	HP Prelude Pro Recycle Backpack	1X644AA
	HP Prelude Pro Recycle Top Load	1X645AA
	HP Prelude 15.6 Top Load	1E7D7AA
	HP Prelude 15.6 Top Load	2Z8P4AA
	HP Prelude 15.6 Top Load	50P31AA
	HP Prelude 15.6 Backpack	1E7D6AA
	HP Prelude 15.6 Backpack	2Z8P3AA
	HP Prelude 15.6 Backpack	50P32AA
	HP Renew Business 17.3 Laptop Backpack	3E2U5AA
	HP Renew Business 17.3 Laptop Bag	3E2U6AA
	HP Renew Business 15.6 Laptop Bag	3E5F8AA
	HP Renew Executive 16 Laptop Backpack	6B8Y1AA
	HP Renew Executive 16 Laptop Bag	6B8Y2AA
	HP Travel 25 Liter 15.6 Iron Gray Laptop Backpack	6B8U4AA
	HP Travel 25 Liter 15.6 Iron Gray Laptop Backpack	6H2D8AA
	HP Travel 18 Liter 15.6 Iron Gray Laptop Backpack	6B8U6AA
	HP Travel 18 Liter 15.6 Iron Gray Laptop Backpack	6H2D9AA
Docking Station	HP USB-C Dock G5	26D32AA
	HP USB-C Dock G5	5TW10AA
	HP USB-C/A Universal Dock G2	5TW13AA
	HP USB-C/A Universal Dock G2 TAA	7UP88AA
	HP Thunderbolt 120W G4 Dock	4J0A2AA
	HP Thunderbolt 280W G4 Dock w/Combo Cable	4J0G4AA
Adapter/Dongle	HP HDMI to VGA Adapter	H4F02AA
	HP USB-C to USB 3.0 Adapter	N2Z63AA
	HP USB-C to DisplayPort Adapter	N9K78AA
	HP USB-C to VGA Adapter	N9K76AA
	HP USB-C to VGA Adapter	P7Z54AA
	HP USB-C to HDMI 2.0 Adapter	1WC36AA
	HP USB-C to HDMI 2.0 Adapter	2PC54AA
	HP 7.4 mm to 4.5 DC dongle	K0Q39AA
	HP USB-C to RJ45 Adapter G2	4Z527AA
	HP USB-C to RJ45 Adapter G2	4Z534AA
	HP USB 3.0 to Gig RJ45 Adapter G2	4Z7Z7AA
HP USB-C to USB-C 100W Cable	5AR72AA	
Audio/Video	HP USB G2 Stereo Headset	428H5AA
	HP USB G2 Stereo Headset	428K6AA
	HP 3.5mm G2 Stereo Headset	428H6AA
	HP 3.5mm G2 Stereo Headset	428K7AA
	HP 365 BT Speaker	567D3AA

Options and Accessories (sold separately and availability may vary by country)

	HP 325 FHD USB-A Webcam	53X27AA
	HP 965 4K Streaming Webcam	695J5AA
	HP 620 FHD Webcam	6Y7L2AA
Hub	HP USB-C to USB-A Hub	Z6A00AA
Storage	HP 512GB PCIe-4x4 NVMe M.2 Solid State Drive	5R8X9AA
	HP 1TB PCIe-4x4 NVMe M.2 Solid State Drive	5R8Y0AA
	HP 2TB PCIe-4x4 NVMe TLC M.2 Solid State Drive	6D8L6AA
	HP USB External DVDRW Drive	F2B56AA,Y3T76AA
Keyboard/Combo	HP 320K Wired Keyboard	9SR37AA
	HP 125 Wired Keyboard	266C9AA
	HP 975 USB+BT Dual-Mode Wireless Keyboard	3Z726AA
	HP 455 Programmable Wireless Keyboard	4R177AA
	HP 355 Compact Multi-Device Keyboard	692S9AA
	HP Wireless Rechargeable 950MK Mouse and Keyboard	3M165AA
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA
	HP 235 Wireless Mouse and Keyboard Combo	1Y4D0AA
	HP 225 Wired Mouse and Keyboard Combo	286J4AA
	HP 225 Antimicrobial Wired Mouse and Keyboard Combo	286K3AA
	HP 655 Wireless Keyboard and Mouse Combo	4R009AA
	HP 155 Wired Mouse and Keyboard Combo	5B8C0AA
Display	HP Z24f G3 FHD Display	3G828AA
	HP Z27q G3 QHD Display	1C4Z7AA
	HP Z24n G3 WUXGA Display	1C4Z5AA
	HP Z34c G3 WQHD Curved Display	30A19AA
	HP Z24q G3 QHD Display	4Q8N4AA
	HP Z24m G3 QHD Conferencing Display	4Q8N9AA
	HP Z32k G3 4K USB-C Display	50U19AA
Mouse	HP Wired 320M Mouse	9VA80AA
	HP Travel USB Mouse	G1K28AA
	HP Premium Wireless Mouse	1JR31AA
	HP Travel Bluetooth Mouse	6SP30AA
	HP Multi-Device 635 Black Wireless Mouse	1D0K2AA
	HP Creator 935 Black Wireless Mouse	1D0K8AA
	HP 235 Slim Wireless Mouse	4E407AA
	HP 128 LSR Wired Mouse	265D9AA
	HP 125 Wired Mouse	265A9AA
	HP 435 Multi-Device Wireless Mouse	3B4Q5AA
	HP 155 Wired Mouse	5B8B7AA
	HP 715 Rechargeable Multi-Device Bluetooth Mouse	6E6F0AA

Options and Accessories (sold separately and availability may vary by country)

	HP 925 Ergonomic Vertical Wireless Mouse	6H1A5AA
Power Adapter	HP 150W Slim Smart 4.5mm AC Adapter	4SC18AA
	HP ZBook 200W Slim Smart 4.5mm AC Adapter	491C7AA
	HP ZBook 230W Slim Smart 4.5mm AC Adapter	6E6M1AA
Security	HP Nano Keyed Cable Lock	1AJ39AA
	HP Nano Master Keyed Cable Lock	1AJ40AA
	HP Sure Key Cable Lock	6UW42AA
	HP Nano Combination Cable Lock	63B28AA
	HP Essential Nano Combination Cable Lock	63B31AA

Copyright © 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core, and Celeron, Thunderbolt and vPro are registered trademarks or trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. Bluetooth is a registered trademark of its proprietor used by HP Inc. under license. AMD, FirePro, and Enduro are trademarks of Advanced Micro Devices, Inc. Adobe is a trademark of Adobe Systems Incorporated. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation in the United States and/or other countries. Qualcomm and Snapdragon are trademarks of Qualcomm, Inc. SD, SDHC, and SDXC are trademarks or registered trademarks of SD-3C in the United States, other countries or both. USB Type-C and USB-C are trademarks of USB Implementers Forum. ENERGY STAR® is a registered trademark mark of the U.S. Environmental Protection Agency.

Date of change:	Version History:		Description of change:
July 5, 2023	From v1 to v2	Changed	ENVIRONMENTAL DATA section
July 20, 2023	From v2 to v3	Changed	PROCESSOR section
July 25, 2023	From v3 to v4	Changed	GRAPHICS section
August 1, 2023	From v4 to v5	Changed	ENVIRONMENTAL DATA section