



Product Highlights:

- Quickly transfer high-res images and 8K RAW videos with transfer speeds up to 10Gbps¹
- Two slots—one for CFexpress™ Type B cards and one for SD cards—for simultaneous offloads
- Supports USB 3.2 Gen 2 speeds to dramatically accelerate your workflow
- Includes both a USB Type-C to Type-C cable and a USB Type-A to Type-C cable
- Compact and portable design for use on location and in the studio
- Two-year limited warranty



TYPE-C



Twice as Nice with Dual Slots

The Professional CFexpress™ Type B / SD™ USB 3.2 Gen 2 Reader lets you use one port to offload from two cards at once. And transfer speeds up to 10Gbps¹ and a design that leverages USB 3.2 Gen 2 speeds will fast-track your workflow too.

Offload with Ease. Transfer speeds up to 10Gbps¹ allow you to quickly offload high-res images and 8K RAW videos with ease.

One Port. Two Slots. On location, laptop ports are sometimes in short supply. Which is why we designed the Lexar Professional CFexpress™ Type B / SD™ USB 3.2 Gen 2 Reader to fit in one port, while offering two slots—one for CFexpress cards and one for SD cards.

Optimize Your Workflow. Along with exceptional transfer speeds, the reader also leverages USB 3.2 Gen 2 speeds to dramatically accelerate your workflow.

Designed for Convenience. With both a USB Type-C to Type-C cable and a USB Type-A to Type-C cable included, the reader is good to go right out of the box, without any extra peripherals.

Travel-Ready and Willing. With its compact and portable design, the Lexar Professional CFexpress™ Type B / SD™ USB 3.2 Gen 2 Reader is easy to take with you, no matter where you're going.

Peace of Mind Included. All Lexar products undergo rigorous testing to ensure they're reliable and this reader comes with a 2-year limited warranty so you can rest assured it's a good choice.

Rigorously Tested. All Lexar products undergo extensive testing in the Lexar Quality Labs, facilities with thousands of different cameras and digital devices to ensure performance, quality, compatibility, and reliability.

For more than 27 years, Lexar has been trusted as a leading global brand of memory solutions. Our award-winning lineup includes memory cards, USB Flash Drives, card readers, solid-state drives, and DRAM. With so many options, it's easy to find the right Lexar solution to fit your needs. Lexar products are available worldwide at major retail and e-tail stores. For more information or support, visit www.lexar.com.

Lexar Retail Sku	Region	Single UPC Code	Inner Carton UPC Code	Inner Carton Qty
LRW520U-RNBNG	Global	843367130344	10843367130341	10

¹Results may vary based on system configuration and card speed.

Warning: Compatible only with CFexpress™ Type B memory cards, indicated by a boxed USB logo on the card label. Use with incompatible card may result in data loss. Contact your card manufacturer for details.

Lexar is not liable for any loss of data or images.

Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.

www.lexar.com

©2023 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.

Specifications

Performance	CFexpress™ Type B card: Sequential read up to 1050MB/s, sequential write up to 1000MB/s ¹ UHS-II SD™ card: Sequential read up to 312MB/s, sequential write up to 260MB/s ¹ UHS-I SD™ card: Sequential read up to 170MB/s ¹
Drivers	No driver required, plug-and-play, hot-plug support
Indicator Status	Insert memory card: white Data transfer: white flashing
Weight	128g / 0.28 lbs
Dimensions (L x W x H)	98mm x 60mm x 22mm / 3.85" x 2.36" x 0.86"
Supported Card Formats	CFexpress™ Type B memory card SD™, SDHC™, SDXC™, SD™ UHS-I and UHS-II memory card
Operating Temperature	0° to 40°C (32°F to 104°F)
Storage Temperature	-25°C to 85°C (-13°F to 185°F)
Systems Supported	Mac® OS 10.8+, Windows® 11/10/8/7/Vista/XP, USB 2.0+ port

www.lexar.com

©2023 All Rights Reserved. Information, products, specifications, and features are subject to change without notice. Neither Lexar nor Longsys is responsible for omissions or errors in typography or photography. Lexar, the Lexar logo, and all other Lexar trademarks are the property of Longsys Electronics (HK) Co., Ltd. or Shenzhen Longsys Electronics Co., Ltd. All other trademarks are property of their respective owners.