

# PRODUCT DATASHEET

## LED Office Line 1200 mm 48 W 4000 K

LED OFFICE LINE | Ceiling luminaire with a slim and modern design



---

### AREAS OF APPLICATION

- Indoor applications
- Home offices
- General indoor illumination
- Kitchens, workspaces

---

### PRODUCT BENEFITS

- Flexible mounting options
- Functional and minimalistic design

---

### PRODUCT FEATURES

- Replacement for traditional T8 luminaires
- Wall and ceiling batten luminaire
- Material: Aluminium (Housing), Polycarbonate (Diffusor)
- Lifetime: up to 30,000 h
- Lengths available: 0.6 m, 1.2 m
- Color temperature: 4,000 K



## TECHNICAL DATA

### Electrical data

<b>Nominal wattage</b>	48.00 W
<b>Operating mode</b>	Mains voltage
<b>Nominal voltage</b>	220...240 V
<b>Mains frequency</b>	50/60 Hz

### Photometrical data

<b>Color temperature</b>	4000 K
<b>Color rendering index Ra</b>	≥80
<b>Light color (designation)</b>	Cool White
<b>Luminous flux</b>	4800 lm
<b>Luminous efficacy</b>	100 lm/W

### Light technical data

<b>Beam angle</b>	105.00 °
-------------------	----------

### Dimensions & weight



<b>Length</b>	1215 mm
<b>Width</b>	130.0 mm
<b>Height</b>	25.0 mm
<b>Product weight</b>	1171.00 g

### Colors & materials

<b>Body material</b>	Aluminum
<b>Product color</b>	White
<b>Housing color</b>	White

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Temperature range in operation	-20...+40 °C

### Lifespan

Number of switching cycles	25000
Lifespan	30000 h
Rated lamp life time	30000 h

### Additional product data

Mounting type	Surface
Mounting location	Ceiling
Mercury content	0.0 mg

### Capabilities

Dimmable	No
Type of connection	Screw terminal
LED module replaceable	Not replaceable

### Certificates & standards

Protection class	II
Type of protection	IP20
Standards	CE/EAC/REACH/RoHS
ErP For end-consumer	yes
EEL of included LED module	A++/A+/A

### Logistical data

ErP For end-consumer	yes
----------------------	-----

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075271487	Folding carton box 1	32 mm x 135 mm x 1245 mm	1276.00 g	5.38 dm <sup>3</sup>
4058075271494	Shipping carton box 8	1240 mm x 290 mm x 150 mm	10675.00 g	53.94 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.