# Product Data Sheet

## Melitta One

### Technical Data

| | | |
|---|---|---|
| Type | 1031-XX | |
| Power rating | 1395 - 1660 | [ W ] |
| Voltage | 220 - 240 | [ V ] |
| Frequency | 50 - 60 | [ Hz ] |
| Weight | 2,83 | [ kg ] |
| Weight with packaging | 3,57 | [ kg ] |
| Height x Width x Depth | 355 x 360 x 160 | [ mm x mm x mm ] |
| Height x Width x Depth packaging | 365 x 370 x 203 | [ mm x mm x mm ] |
| Water tank volume | 1.25 | [ l ] |
| Maximum amount of coffee | 10 | [ cups ] / [ l ] |
| Brewing time | 06:00 | [ mm:ss ]   (approx.) |
| Finish brew coffee | 85 | [ °C ]   (approx.) |
| Warmkeeping temperature | 85 | [ °C ]   (approx.) |
| Automatic shut-off time | 0/30/60 | [ min ] |
| Filter size | 1x4 | |

**Available colours:**

- 1031-01   Stainless Steel
- 1031-02   Pure Black
- 1031-03   Cream White

### Feature Details

**Glass jug**
- glass handle
- dishwasher safe
- removable lid
- printed water level indication

**Water tank**
- water level indication for 2 to 10 cups
- additional markings for 0.25l, 0.50l, 0.75l, 1.00l and 1.25l
- removable water tank lid
- illuminated waterlevel indication, switches on when filling the watertank, switches off at end of the brewing cycle

**Filter**
- removable filter with handle
- break-proof
- drip stop
- dishwasher safe
- filter size 1x4
- lock-in mechanism for fixing at the coffeemaker, to be opened by one hand operation at the handle
- removable filter lid for easy cleaning

**Housing**
- filter, filter lid, spout, water tank lid and jug lid as single removable parts for easy cleaning
- lacquered stainless steel inlay

**Brewing system**
- 1465W heating system for fast coffee preparation
- high brewing temperature for perfect coffee extraction (ECBC approval)
- two brewing modes: full power and reduced power, reduced power for 2-5 cup preparation
- glass raising tube for visualization of raising water during brewing or decalcification
- separate 60W heater for warm keeping

**Calcification indication**
- necessity to descale shown with red LED

**Descaling program**
- CALC button to start descaling program
- decalcification process works with reduced power, audio indication when finished

**Brewing end signal**
- programmable acustic brewing end signal loudness: on , off
- factory setting: on
- acoustic signals for brew end signal

**Automatic shut-off**
- programmable warm keeping time: 0, 30 or 60 minutes
- warm keeping time setting shown by flashing LED
- factory setting 30 minutes
- after warmkeeping time is finished
- manual switch-off possible

**ON-OFF-Switch**
- ON/OFF button

**Power cord**
- cord length 90 cm
- storage under bottom cover
- power cord outlet on the back or on the side

**Approvals**
- Safety approval (GS approval mark)
- Food law approval
- ECBC approval (European Coffee Brewing Centre)