

# Atos Unify OpenScape Desk Phone CP G2 device family

This next generation of OpenScape Desk Phone CP devices blend a modern and elegant design language with the latest technology upgrades to deliver an intuitive, class-leading experience.



OpenScape Desk Phone  
CP110



OpenScape Desk Phone  
CP210

## Easy to use

These design and technology enhancements in combination with their ease of provisioning, configuration and management serve to simplify operational activities and reduce the cost of ownership.

## Meeting the needs of modern organizations

Equipped with a wide range of capabilities, this family of devices deliver the functionality required to provide for the broadest range of organizational use cases, applications, and needs.

## Intuitive and economical with a small footprint

The ergonomic design and user-friendly familiarity of the OpenScape Desk Phone CP G2 family means they can be quickly and easily deployed and used with low friction adoption.

## Operational software

- SIP & HFA (Cornet-IP) software, SIP software is pre-installed
- Plug & Play / automatic software deployment via Atos Unify DLS

## Phone models

### OpenScope Desk Phone CP110

The ideal device for entry level workplace scenarios without compromise in quality.



#### Display

- Graphical three-line display (162 x 48 pixels), monochrome
- Signaling LED (red)

#### Keys

- 3 freely programmable function keys with Soft Label on LCD  
Pre-assignment: call log, forwarding, redialing
- 2 fixed function keys: settings, messages
- 3-way navigator plus OK key
- 3 audio function keys (mute/loudspeaker/headset)
- Volume +/-
- Open listening/hands free speaking (full duplex)

#### Connection options

- Headset interface (DHS/G/EHS)

#### Placement

- Base, two different placement angles
- Wall mountable

### OpenScope Desk Phone CP210

Outstanding quality, an extensive scope of features and a three-line display make this device the ideal choice for users with UC/CTI support.



#### Display

- Graphical three-line display (199 x 48 pixels), monochrome
- Signaling LED (red/green/amber)

#### Keys

- 4 freely programmable function keys with Soft Label on LCD and LED signaling on the key (red/green/amber)  
Pre-assignment: call log, directory, forwarding, redialing
- 5 fixed function keys, 3 with LED: hold, transfer, conference calling, settings, messages
- 4-way navigator plus OK key
- 3 audio function keys (mute/loudspeaker/headset)
- Volume +/-
- Open listening/hands free speaking (full duplex)

#### Connection options

- Headset interface (DHS/G/EHS)
- USB interface

#### Placement

- Base, two different placement angles
- Wall mountable

## Communications platforms

The OpenScope Desk Phone CP G2 supports the following communications platforms:

### SIP

- From Atos Unify OpenScope Voice V9

### HFA

- From Atos UNIFY OpenScope Business V3R2
- From Atos UNIFY OpenScope 4000 V8R2 (in preparation)
- From Atos UNIFY OpenScope 4000 V10R1

## Technical data

	Atos Unify OpenScape Desk Phone CP110	Atos Unify OpenScape Desk Phone CP210
Housing color		black
Placement angle		2
Handset embossed with Unify logo		Yes
<b>Display</b>		
Dimensions	2,8" FSTN display 162 x 48 pixels 3 Lines	3,4" FSTN display 199 x 48 pixels 3 Lines
Color	Monochrome	
Additional optical call alert	Yes (red)	Yes (red/green/amber)
<b>Keys/LEDs</b>		
Fixed function keys	2 (Settings/messages)	5 3 with LED (hold, transfer, conference calling, settings, messages)
Free-programmable keys	3 with LCD Label, call log, forwarding, redialing	4 with LCD Label and LED (red/green/orange) Pre-assignment: call log, directory, forwarding, redialing
Key labeling	Display	
Audio keys	3 (Mute/loudspeaker/headset) and Volume +/-	
Navigation	3-way navigator, plus OK key	4-way navigator, plus OK key
<b>Audio</b>		
G.711 (64 kbit/s a/μ-law)	Yes	
G.722 (64 kbit/s)	Yes	
G.729AB (8 kbit/s)	Yes	
OPUS	Yes	
Open listening	Yes	
Full duplex handsfree	Yes	
Echo canceling for local echo (AEC) full duplex	Yes	
<b>Interfaces</b>		
LAN connection (Ethernet with auto-sensing)	10/100/1000Mbit/s	
Integrated switch	Yes	
Energy Efficient Ethernet (IEEE 802.3az)	Yes	
Headset jack for cord-connected (121 TR9-5) and cordless headsets (121 TR9-5*)	Yes	
USB Interface	No	Yes
Passive RFID tag	Yes	
<b>VoIP protocol</b>		
SIP	Yes	
CorNet IP / HFA	Yes	
<b>Security features</b>		
Layer 2 authentication (IEEE 802.1x)	Yes	
Payload encryption via SRTP	Yes	

	Atos Unify OpenScape Desk Phone CP110	Atos Unify OpenScape Desk Phone CP210
Signaling via TLS encryption	Yes	
Support of digital certificates (X.509 V3)	Yes	
HTTPS	Yes	
<b>Network</b>		
LLDP-MED	Yes	
QoS (DiffServ and IEEE 802.1Q)	Yes	
IEEE 802.1Q	Yes	
<b>Power supply</b>		
Power over Ethernet (PoE, IEEE 802.3az)	Yes	
PoE class	1	2
External power supply (country-specific models available)	Optional	
<b>Ecolabel certifications</b>		
ENERGY STAR	Yes	
<b>Technical data</b>		
Dimensions (angle (°) x height [mm] x width [mm] x depth [mm])	22,5° x 215 x 187 x 201 45° x 183 x 187 x 168	22,5° x 125 x 228 x 206 45° x 183 x 228 x 168
Weight [kg]	0,75	0,88
Storage conditions	-25 °C to +70 °C	
Operating conditions	+5 °C to +40 °C	