


Project Name

Qty

Type


Catalog / Part Number



Certifications



Shafts



Description

The 1000 Dorado pole is constructed and shipped as 1 piece assembly to keep the base and shaft true and plumb for the life of the product. This highly decorative tall and slender base is a unique style that fits many applications.

Features

Base Model	10: 1000 Dorado Pole
Height (in feet)	8', 10', 11'9", 12', 13'9", 14', 15'9", 16', 18', 20', 22', 24', 26', 28'
Shafts	P6: 6" Round Straight Smooth FP6: 6" Round Straight Fluted T6: 6"-3" Tapered Smooth T64: 6"-4" Tapered Smooth TFP6: 6"-3" Cast Tapered Fluted ETFP6: 6" Extruded Tapered Fluted
Wall Thickness	.125: 1/8" Wall Thickness .188: 3/16" Wall Thickness .250: 1/4" Wall Thickness C: Cast Shaft, Varied Wall Thickness
Optional Post Center Cap	BCC: Ball Center Cap FCC: Finial Center Cap SCC: Spike Center Cap TFCC: Tall Finial Center Cap SSCC: Side Spike Center Cap RCC: Round Center Cap PCC: Plate Center Cap, Flat
Optional Burial	DB4: Direct Burial mounting style pole, with 4' direct burial section (or advise other length) HXB: HXB - Helix Base mounting style pole
Optional Vibration Damper	VD: Internal Vibration Damper

1" x 36" long anchor bolts



Finish



Optional Photocell	PCD: Electronic Button Photocontrol, mounted on an access door (120V-277V) PCD4: Electronic Button Photocontrol, mounted on an access door (480V)
Optional Receptacle	GFI LPIUC: 120V, 15 Amp Duplex GFCI receptacles with a low-profile in-use cover USB LPIUC: 120V, 15 Amp Duplex USB/ Receptacle combo with a low-profile in-use cover (NON-GFCI) GFI IUC: 120V, 15 Amp Duplex GFCI receptacles with a standard in-use cover GFI IB: 120V, 15 Amp duplex GFCI receptacle in pole base, includes mouse hole on door for wire access DPL-LPIUC-GFB: 120V duplex (NON-GFI) receptacle, low-profile in-use cover, Remote Ground Fault Breaker In pole base
Optional Flag Pole Holder	FH: Cast Aluminum flag holder mount, for use with 1" diameter flag pole
Optional Banner Arms	SBA: Single Banner Arm, PM style mount DBA: Double Banner Arms, PM style mount SBAR: Single Banner Arm and Ring, for triangle banners, PM style mount HSBA: Single Banner Arm, HUB mount style mount HDBA: Double Banner Arms, HUB mount style mount BDBA6: Double Banner Arms, Break-Away style, to break with 60MPH wind gust BDBA9: Double Banner Arms, Break-Away style, to break with 90MPH wind gust
Banner Width (If Applicable)	18W: 20" Long Banner arm 24W: 26" Long Banner arm 30W: 32" Long Banner arm 36W: 38" Long Banner arm CSTM: Custom Sized Banner setup
Break-Away Banner Size (If Applicable)	18x36: 20" Long Banner arm, 36" tall center to center 18x72: 20" Long Banner arm, 72" tall center to center 24x48: 26" Long Banner arm, 48" tall center to center 30x36: 32" Long Banner arm, 36" tall center to center 24x60: 26" Long Banner arm, 60" tall center to center CSTM: Custom Sized Banner setup
Optional Planter Arms	DHPA: Double Hooked Planter Arm SHPA: Single Hooked Planter Arm DSPA: Double Stepped Planter Arm SSPA: Single Stepped Planter Arm PA478: Cast aluminum decorative planter arm
Optional Drip Irrigation	DIS: Drip Irrigation System
Optional Sign Arms	SA78: Small cast aluminum decorative sign arm, with 24" long channel for blade sign by others SA478: Large cast aluminum decorative sign arm, with 24" long channel for blade sign by others SABA: Banner arm style sign arm, with 24" long channel for blade sign by others

Optional Speaker Hub	SH0.5: Speaker Hub Coupling, 1/2"-14 NPS SH0.75: Speaker Hub Coupling, 3/4"-14 NPS SH1.0: Speaker Hub Coupling, 1"-11.5 NPS SH1.5: Speaker Hub Coupling, 1-1/2"-11.5 NPS SH2.0: Speaker Hub Coupling, 2"-11.5 NPS
Optional Sign Bracket	SB: Sign Bracket, vertically mounted on pole shaft
Optional Steel Wreath Hook	WHK: Steel Wreath Hook
Finish	BKT: Black Textured WHT: White Textured PGT: Park Green Textured ABZT: Arch Med Bronze Tex DBT: Dark Bronze Textured VG: Verde Green SI: Swedish Iron OWGT: Old World Gray Tex OI: Old Iron RT: Rust WBR: Weathered Brown CD: Cedar WBK: Weathered Black TT: Two Tone CM: Custom Match

Electrical and control

Optional Motion Sensor In Arm	MSA-RND-L3: Motion Sensor, For Round shaft, L3 Sensor Lens (40' diameter coverage at 20' Mounting Height) MSA-RND-L7: Motion Sensor, For Round shaft, L7 Sensor Lens (50' diameter coverage at 20' Mounting Height)
-------------------------------	--

Important

Virtual Patent Marking Notice

This website (<https://www.lmpg.com/patents-trademarks>) is provided to satisfy the virtual patent marking provisions of applicable jurisdictions. Some products listed may be covered by additional patents not referenced here.

How to Order

Base Model	Height (in feet)	Shafts	Wall Thickness	Optional Post Center Cap	Optional Burial	Optional Vibration Damper ⁽⁸⁾	Optional Photocell	Optional Receptacle	Optional Motion Sensor In Arm	Optional Flag Pole Holder
10 1000 Dorado Pole	08FT 8'	P6 6" Round Straight Smooth ⁽¹⁾	.125 1/8" Wall Thickness	BCC Ball Center Cap	DB4 Direct Burial mounting style pole, with 4' direct burial section (or advise other length) ⁽⁷⁾	VD Internal Vibration Damper	PCD Electronic Button Photocontrol, mounted on an access door (120V-277V)	GFI LPIUC Duplex GFCI , low-profile in- use cover	MSA-RND-L3 Motion Sensor, For Round shaft, L3 Sensor Lens	FH Cast Aluminum flag holder mount, for use with 1" diameter flag pole
	10FT 10'	FP6 6" Round Straight Fluted ⁽²⁾	.188 3/16" Wall Thickness	FCC Finial Center Cap						
	11.75FT 11'9"	T6 6"-3" Tapered Smooth	.250 1/4" Wall Thickness	SCC Spike Center Cap						
	12FT 12'	T64 6"-4" Tapered Smooth	C Cast Shaft, Varied Wall Thickness ⁽⁶⁾	TFCC Tall Finial Center Cap	HXB HXB - Helix Base mounting style pole		PCD4 Electronic Button Photocontrol, mounted on an access door (480V)	USB LPIUC Duplex Combo Receptacle, low-profile in- use cover	MSA-RND-L7 Motion Sensor, For Round shaft, L7 Sensor Lens	
	13.75FT 13'9"	T64 6"-4" Tapered Smooth		SSCC Side Spike Center Cap						
	14FT 14'	TFP6 6"-3" Cast Tapered Fluted ⁽³⁾		RCC Round Center Cap						
	15.75FT 15'9"	ETFP6 6" Extruded Tapered Fluted ^{(4) (5)}		PCC Plate Center Cap, Flat				GFI IUC Duplex GFCI , standard in-use cover		
	16FT 16'							GFI IB Duplex GFCI , In pole base		
	18FT 18'							DPL-LPIUC-GFB Duplex Combo Receptacle, low-profile in- use cover , Remote breaker in pole base		
	20FT 20'									
	22FT 22'									
	24FT 24'									
	26FT 26'									
	28FT 28'									

Notes:

1. Not available in .125 wall.

2. Only available in .250 wall.

3. Heights limited to 11'9", 13'9" & 15'9" for TFP shaft

4. 20' Max Height.
5. Not available in .125 wall.

6. For cast "TFP" shafts only.

7. 24' Max Height

8. Required on pole heights 26' and taller.

How to Order

Optional Banner Arms	Banner Width (If Applicable) ⁽⁹⁾ ⁽¹⁰⁾ ⁽¹¹⁾	Break-Away Banner Size (If Applicable) ⁽¹¹⁾ ⁽¹²⁾	Optional Planter Arms	Optional Drip Irrigation ⁽¹³⁾	Optional Sign Arms	Optional Speaker Hub	Optional Sign Bracket ⁽¹⁴⁾	Optional Sign Bracket (Length in inches) ⁽¹⁵⁾	Optional Steel Wreath Hook	Finish
SBA Single Arm, PM mount	18W 20" Long Banner arm	18x36 20" Long Banner arm, 36" tall center to center	DHPA Double Hooked Planter Arm	DIS Drip Irrigation System	SA78 Small cast aluminum decorative sign arm, with 24" long channel for blade sign by others	SH0.5 Speaker Hub Coupling, 1/2"-14 NPS	SB Sign Bracket, vertically mounted on pole shaft		WHK Steel Wreath Hook	BKT Black Textured ⁽¹⁶⁾
DBA Double Arms, PM mount	24W 26" Long Banner arm	18x72 20" Long Banner arm, 72" tall center to center	SHPA Single Hooked Planter Arm			SH0.75 Speaker Hub Coupling, 3/4"-14 NPS				WHT White Textured ⁽¹⁶⁾
SBAR Single Arm W/ Ring, PM mount	30W 32" Long Banner arm	24x48 26" Long Banner arm, 48" tall center to center	DSPA Double Stepped Planter Arm		SA478 Large cast aluminum decorative sign arm, with 24" long channel for blade sign by others	SH1.0 Speaker Hub Coupling, 1"-11.5 NPS				PGT Park Green Textured ⁽¹⁶⁾
HSBA Single Arm, HUB mount	36W 38" Long Banner arm	30x36 32" Long Banner arm, 36" tall center to center	SSPA Single Stepped Planter Arm			SH1.5 Speaker Hub Coupling, 1-1/2"-11.5 NPS				ABZT Arch Med Bronze Tex ⁽¹⁶⁾
HDBA Double Arm, HUB mount	CSTM Custom Sized Banner setup	24x60 26" Long Banner arm, 60" tall center to center	PA478 Cast aluminum decorative planter arm		SABA Banner arm style sign arm, with 24" long channel for blade sign by others	SH2.0 Speaker Hub Coupling, 2"-11.5 NPS				DBT Dark Bronze Textured ⁽¹⁶⁾
BDBA6 Double Arms, BREAK-AWAY, 60MPH										VG Verde Green
BDBA9 Double Arms, BREAK-AWAY, 90MPH										SI Swedish Iron
										OWGT Old World Gray Tex
										OI Old Iron ⁽¹⁷⁾
										RT Rust ⁽¹⁷⁾
										WBR Weathered Brown ⁽¹⁷⁾
										CD Cedar ⁽¹⁷⁾
										WBK Weathered Black ⁽¹⁷⁾
										TT Two Tone ⁽¹⁷⁾
										CM Custom Match ⁽¹⁷⁾

Notes:

9. Only required if a NON-Break Away style banner arm is selected

10. Height to be advised (CONSULT EPA CHART)

11. Banner width should be 2" smaller than the banner arm, so an 18" wide banner is assumed to be used with a 20" long arm. Banners by Others.

12. Only required if a Break-Away style banner arm is selected
13. Requires planter arm

14. Advise Length in next field.

15. Bracket should be 2 inches shorter than the sign/frame.

16. Smooth finishes are available upon request.

17. Custom colors require upcharge.

Specifications

Construction	The base shall be made of heavy wall, 356 alloy cast aluminum. It shall have a 7/8" thick floor cast as an integral part of the one piece base. The high tensile aluminum shaft shall be double circumferentially welded internally and externally to the base for added strength.
Access Door	Cast aluminum access door integral to base. Includes stainless steel allen head hardware for attachment to base.
Tenon	Standard tenon size to be 3" OD x 3" tall. Consult the Sales Department for additional sizes.
Straight Smooth Shaft - Round	The straight round shaft shall be made of ASTM 6061 extruded aluminum and tempered to a T6 condition.
Straight Fluted Shaft	The straight fluted shaft will have a 12 Flat Flute profile and shall be made of ASTM 6061 extruded aluminum and tempered to a T6 condition.
Tapered Smooth Shaft	The tapered smooth shaft shall be made of ASTM 6063 extruded aluminum and tempered to a T6 condition.
Tapered Fluted Shaft	The tapered fluted shaft will have a 16 Flat Flute profile and shall be made of heavy wall 356 alloy cast aluminum.
Extruded Tapered Fluted Shaft	The extruded tapered fluted shaft will have a 16 Flat Flute profile shall be made of ASTM 6063 extruded aluminum that is tapered into shape and tempered to a T4 condition. Shaft tapers at .14" per linear foot.
Installation	Four 1" diameter by 36" long, hot-dipped galvanized "L" type anchor bolts shall be provided with the post for anchorage, they shall be mounted in a 16" bolt circle, Diamond pattern. Post will be provided with a grounding stud mounted on the base floor opposite the access door. CONCRETE FOOTING DESIGN BY OTHERS (OPTIONAL): 4' direct burial portion of pole shaft extending below pole base. Includes "Slipping" base style which has set screws at the neck to tighten the base down to the pole shaft. Includes anti-rotational rod and (2) wireway holes on direct burial portion.
Hardware	Includes Stainless steel hardware. Most finishes will include hardware with a Black Oxide conversion coating. Light finishes will get non-color coated hardware (Whites and Silvers)
Receptacle	Optional 120V duplex 15A GFI (GFI LPIUC) or NON-GFI/5A USB combo duplex receptacle (USB LPIUC) installed in proprietary "Low-Profile" box with a lockable In-Use cover (lock not included). Optional 120V duplex 15A GFI duplex receptacle (GFI IB) is installed in the decorative pole base with no cover. The access door includes a mouse hole for wire access. Optional 120V duplex (NON-GFI) receptacle (DPL) is installed in proprietary "Low-Profile" box (LPIUC) with a lockable In-Use cover (lock not included). A Ground Fault Breaker (GFB) is installed in the decorative pole base for easy reset access. Optional 120V duplex 15A GFI duplex receptacle installed in standard J-box with a lockable In-Use cover (lock not included).
Photocontrols	Button Photocell (On Plate): Optional photocontrol shall be mounted on a plate and installed on the pole shaft. The electronic button type photocontrol is instant on with a 5-10 second turn off, and shall turn on at 1.5 footcandles with a turn-off at 2-3 footcandles.
Wreath Hook	A steel wreath hook is offered to support a variety of decorations. The removable hook attaches to a cast aluminum mount via 2 stainless steel hex head bolts . Not for use to support catenary applications - 40 LB max weight
Drip Irrigation System	Optional concealed irrigation system efficiently waters flora in hanging baskets. The system includes 1" PVC pipe, 1/4" OD clear flexible tubing and a cord grip. The PVC acts as a conduit to separate the water from the power. The 1/4" tubing carries water from the supply line to the flora. The cord grip seals the system, stopping rainwater and debris from entering the pole. This low-maintenance feature can help reduce upkeep costs and conserve water. Plants, planter baskets and water supply system are by others.

Motion Sensor	The optional passive infra-red (PIR) sensor allows for autonomous management of each luminaire's light levels based on activity within the coverage area. Fully programmable for the specific needs of the site, including an integral photocell for dusk to dawn on/off control. Sensor mounted in 10" long rectangular aluminum arm, available for square and round poles shafts. Offered with 2 optional FSP-Lx lenses. L3 – 40' diameter coverage at 20' MH L2 – 50' diameter coverage at 20' MH Lenses include a WHITE frame with USLT, USL, UWHT, UWH finishes. All other finishes include BLACK frame on lens. Enables compliance with Title 24 for luminaires without integral dimming control.
Banner Arm(s)	"PM" style banner arms use a cast aluminum mount welded to the pole shaft. The removable banner arm includes a flange that attaches to cast mount via 2 stainless steel hex head bolts and a removable cast aluminum ball cap. 1/2" pipe (.84" OD) is used for banner arm lengths up to and including 20" long. 3/4" pipe (1.05" OD) is used for banner arm lengths 21" to 30" •The actual banner width should be 2" smaller than the attachment arm , so an 18" wide banner is assumed to be used with a 20" long arm. All Banners by Others (SBA) - Single Banner Arm (DBA) - Double Banner Arm (SBAR) - Single Banner Arm and Ring "HUB" style banner arms use an aluminum female coupling welded to the pole shaft. The removable banner arm includes a nut and bolt for a "cotter pin" style attachment to hub and a removable cast aluminum ball cap. 3/4" pipe (1.05" OD) is used for banner arm lengths up to and including 30" long. 1" pipe (1.315" OD) is used for banner arm lengths 31" to 38" •The actual banner width should be 2" smaller than the attachment arm , so an 18" wide banner is assumed to be used with a 20" long arm. All Banners by Others (HSBA) - Hub Style Single Banner Arm (HDBA) - Hub Style Double Banner Arm "BREAK-AWAY" style banner arms use an aluminum female coupling welded to the pole shaft. The removable banner arm includes a nut and bolt for a "cotter pin" style attachment to hub and a removable cast aluminum ball cap. Engineered with a 60MPH maintained break speed (BDBA6), or a 90MPH maintained break speed (BDBA9). Includes an air-craft cable to hold broken section after incident. 3/4" pipe (1.05" OD) is used for 60 MPH break speed (BDBA6). 1" pipe (1.315" OD) is used for 90 MPH break speed (BDBA9) •The actual banner width should be 2" smaller than the attachment arm , so an 18" wide banner is assumed to be used with a 20" long arm. All Banners by Others •This style is offered in standard sized, consult factory for custom sizes •Standard sizes include: 20"x36", 20"x72", 26"x48", 32"x36", 26"x60" (BDBA6) - Break-Away Style Double Banner Arm, 60MPH break speed (BDBA9) - Break-Away Style Double Banner Arm, 90MPH break speed
Vibration Damper	OPTIONAL Internal canister style vibration damper comes pre-installed from the factory and can help limit pole vibrations. REQUIRED on pole heights 26' and taller.
Finish	Our 6 Stage Polyester Powder coat paint system offers a beautiful high-end finish that holds up to even the most extreme environments. Each part is inspected for quality and consistency before being released for shipment. Our system exceeds AAMA 2604, AAMA 2605, ASTM D523 and ASTM D4214 requirements.
Traditional Finish	Traditional paint finishes are available in Sternberg Lighting's Traditional product line. A range of colors help accent the decorative elements on the product. Finishes are available in textured or smooth. Available finishes include: Black, White, Park Green, Architectural Medium Bronze and Dark Bronze
Sternberg Select Finish	The Sternberg Select antique-inspired palette adds a touch of vintage elegance to modern applications. Old World Gray Textured is a 1 part powder coat with metallic flakes. Verde Green and Swedish Iron is a 2 part finish that includes a powder coat base coat with a hand applied antique top coat. The top coat is unique to each application and changes over time.

Custom Finish	Custom finishes are offered to adapt to any application. Rust, Weathered Brown and Cedar are special 1 part powder coat finishes with a distinctive look. Old Iron and Weathered Black are 2 part finishes that includes a powder coat base coat with a hand applied antique top coat. The top coat is unique to each application and changes over time. Two-Tone and Custom Match options are available to blend Sternberg product with the site, consult factory for more information.
UL Listing	UL listed per UL1598 for the US and Canada.
Warranty	5-year limited warranty (See Website for Terms and Conditions)

Post Caps



Flower Center Cap (FCC)



Ball Center Cap (BCC)



Spike Center Cap (SCC)



Side Spiked Center Cap (SSCC)



Tall Finial Center Cap (TFCC)



Plate Center Cap, Round Flat (PCC)



Round Center Cap (RCC)


Options



Button Photocell On Door (PCD)



Double Banner Arms (DBA)




Single Banner Arm and Ring (SBAR)



Hub Style Banner Arm, Single Arm (HSBA)




Break-Away Banner Arm Detail (BDBA6 & BDBA9)



Drip Irrigation System (DIS)



Double Hooked Planter Arm (DHPA)



Single Hooked Planter Arm (SHPA)



Double Stepped Planter Arm (DSPA)



Single Stepped Planter Arm (SSPA)



Speaker Hub (**SH_**)



Sign Bracket (**SB**)



Wreath Hook (**WHK**)



Low-Profile In-Use Cover
(**GFI LPIUC/USB LPIUC**)



Standard In-Use Cover (**GFI IUC**)



Flag Holder (**FH**)
(For 1" diameter poles)



Sign Arm Banner Arm (**SABA**) (24" Channel)



Sign Arm, "78" style (**SA78**) (24" Channel)



Decorative Planter Arm, "478" style (**PA478**)



Motion Sensor in Arm (MSA)



15A Ground Fault Interrupter, in base (GFI IB)



15A Ground Fault Breaker, in base (GFB)

EPA Chart(s)

EPA Chart Based on AASHTO 2009 - EPA values expressed in square feet - Consult factory for other heights

Pole Height	90 MPH	100 MPH	110 MPH	120 MPH	130 MPH	140 MPH	150 MPH
(P6) - Straight Smooth Shaft, 6" - .188 Wall Thickness							
10	31.54	25.48	21.00	17.60	14.94	12.78	11.04
12	24.20	19.51	16.05	13.43	11.38	9.68	8.32
14	19.37	15.58	12.79	10.68	9.02	7.63	6.51
16	15.92	12.77	10.46	8.71	7.32	6.14	5.19
18	13.30	10.64	8.68	7.20	6.03	5.00	4.17
(P6) - Straight Smooth Shaft, 6" - .250 Wall Thickness							
20	15.20	12.16	9.92	8.24	6.90	5.73	4.78
22	13.09	10.43	8.48	7.02	5.84	4.80	3.95
24	11.33	8.99	7.28	5.99	4.96	4.01	3.24
26	9.83	7.75	6.24	5.11	4.20	3.33	2.63
28	8.52	6.68	5.34	4.34	3.53	2.73	2.09
(FP6) - Straight Fluted Shaft, 6" - .250 Wall Thickness							
20	13.47	10.10	7.61	5.72	4.25	3.08	2.13
22	11.17	8.16	5.93	4.23	2.91	1.86	1.02
24	9.23	6.50	4.48	2.94	1.74	0.79	
26	7.54	5.04	3.19	1.79	0.70		
28	6.04	3.75	2.05	0.75			
(T6) - Tapered Smooth Shaft, 6"-3" - .125 Wall Thickness							
10	12.04	9.68	7.94	6.62	5.60	4.79	4.14
12	8.87	7.09	5.78	4.79	4.03	3.43	2.95
14	6.72	5.33	4.31	3.55	2.96	2.50	2.13
16	5.13	4.02	3.22	2.62	2.16	1.80	1.51
18	3.88	2.99	2.35	1.88	1.52	1.24	1.02
(T6) - Tapered Smooth Shaft, 6"-3" - .188 Wall Thickness							
14	10.63	8.50	6.93	5.75	4.84	4.12	3.54
16	8.45	6.71	5.44	4.49	3.75	3.17	2.71
18	6.77	5.33	4.29	3.50	2.90	2.43	2.06
20	5.41	4.21	3.35	2.70	2.21	1.83	1.52
22	4.27	3.27	2.55	2.02	1.62	1.31	1.07
(T6) - Tapered Smooth Shaft, 6"-3" - .250 Wall Thickness							
20	7.76	6.12	4.92	4.02	3.33	2.80	2.37
22	6.38	4.98	3.96	3.21	2.63	2.18	1.83
24	5.20	4.01	3.15	2.51	2.03	1.65	1.36
26	4.18	3.16	2.43	1.90	1.49	1.19	0.95
28	3.27	2.41	1.79	1.35	1.02	0.77	0.57