

Project Name

Qty

Type

Catalog / Part Number



CCT - Color Temp (K)

2,700K

3,000K

3,500K

4,000K

5,000K

7 Year Warranty

7

Certifications

UL

US

LISTED

Description

The versatile VCOB-MS605 conversion kit transforms existing Sternberg MS605 Main Street II luminaires into energy-efficient luminaires at significantly reduced maintenance costs. The wide variety of options makes this the industry's choice when converting from conventional lamp sources to energy-efficient lighting; made by Sternberg Lighting for Sternberg Lighting.

Physical

Series

VCOB-MS605: Main Street II, LED Conversion Kit

Light Source

LED

4L: 4 LEDs

CCT - Color Temp (K)

27: 2,700K

30: 3,000K

35: 3,500K

40: 4,000K

50: 5,000K

Distribution Type

TS: Type Symmetric

TA: Type Asymmetric

Electrical and control

Driver

MDL02: 120V-277V, 250mA

MDH02: 347V-480V, 250mA

MDL03: 120V-277V, 350mA

MDH03: 347V-480V, 350mA

MDL05: 120V-277V, 500mA

MDH05: 347V-480V, 500mA

Features

Optional Fixed Dimming Resistor Board

FDRB: Fixed Dimming Resistor Board

Sternberg

555 Lawrence Ave, Roselle, IL, 60172, US | T 847-588-3400 | contactus@sternberglighting.com

www.sternberglighting.com www.sternberglighting.com/products/581

Sternberg reserves the right to make changes to this product at any time without prior notice and such modification shall be effective immediately.

2024.03.12 Copyright © 2024 Sternberg

1 / 4

Specifications

LEDs	The luminaire shall use high output, high brightness LED's, consisting of a two piece assembly complete with Chip on Board (COB) LED component and COB holder frame. The LEDs shall be 100% recyclable; not contain lead, mercury or any other hazardous substances and shall be RoHS compliant. Lumen maintenance shall be determined in accordance with IESNA TM-21, based on LED manufacturer LM-80 test data of no less than 6,000 hours and in-situ testing of the luminaire by an NVLAP accredited Energy Efficient Lighting Products lab. The high-performance white LEDs will have a predicted lumen depreciation of approximately 100,000 hours with greater than 70% of initial output at 25°C. The High Brightness, High Output LED's shall be 4000K (2700K, 3000K, 3500K or 5000K option) correlated color temperature (CCT) with a 70 (minimum) color rendering index (CRI). Consult factory for custom color CCT. The luminaire shall have a minimum _____ (see table) delivered initial lumen rating when operated at steady state with an average ambient temperature of 25°C (77°F). CCT Lumen Derate Values from 4,000K 2,700K (80+ CRI)=.89 3,000K (70+ CRI)=.97 3,500K (80+ CRI)=.93 5,000K (70+ CRI)=1.01
Optics	The luminaire shall be provided with individual, refractor type optics applied to each LED. The luminaire shall provide Type ____ (Symmetric or Asymmetric) light distribution. Testing shall be done in accordance with IESNA LM-79.
UL Listing	UL listed per UL1598 and CSA 22.2 No. 250.0 for the United States and Canada. Suitable for Wet Locations.
Electronic Driver	The LED driver is UL recognized and will be securely mounted inside the fixture, for optimized performance and longevity. It will be supplied with a quick-disconnect electrical connector on the power supply, providing easy power connections for fixture installation and maintenance. It will have DC voltage output and be a constant current design. It runs at 50/60HZ and will have overload, overheat, and short circuit protection. It will be supplied with a supplemental line-ground, line-neutral and neutral-ground electrical surge protection in accordance with IEEE/ANSI C62.41.2 guidelines. It will be a high efficiency driver with a THD less than 20% and a high-power factor greater than .9. It will be dimming capable using a 0-10V signal, consult factory for more information.
Fixed Dimming Resistor Board (FDRB)	Optional numbered 10-step selector switch allows for fine adjustment of the light levels in the field, repeatable from location to location. Offers dimming from 25% to 100% of the original output. Enclosure is composite material, sealed to protect components for the life of the product.
Warranty	7-year limited warranty. See Website for Terms and Conditions.

Lumen Chart(s)

Model #	TA DELIVERED LUMENS	BUG	EFFICACY (LPW)	TS DELIVERED LUMENS	BUG	EFFICACY (LPW)	WATTAGE
4L40T_-MDL05	6670	B2U3G3	85.5	6800	B3U3G3	87.2	78
4L30T_-MDL05	6500	B2U3G3	83.3	6625	B3U3G3	84.9	78
4L27T_-MDL05	5905	B2U3G3	75.7	6020	B3U3G3	77.2	78
4L40T_-MDL03	5015	B2U3G2	94.6	4990	B2U3G2	94.2	53
4L30T_-MDL03	4885	B2U3G2	92.2	4865	B2U3G2	91.8	53
4L27T_-MDL03	4440	B2U3G2	83.8	4420	B2U3G2	83.4	53
4L40T_-MDL02	3760	B1U3G2	96.4	3725	B2U3G2	95.5	39
4L30T_-MDL02	3665	B1U3G2	94.0	3630	B2U3G2	93.1	39
4L27T_-MDL02	3330	B1U3G2	85.4	3300	B2U3G2	84.6	39

Options



Fixed Dimming Resistor Board (**FDRB**)

How to Order

Series	LED	CCT - Color Temp (K)	Distribution Type	Driver	Optional Fixed Dimming Resistor Board
VCOB-MS605 Main Street II, LED Conversion Kit	4L 4 LEDs	27 2,700K 30 3,000K 35 3,500K 40 4,000K 50 5,000K	TS Type Symmetric TA Type Asymmetric	MDL02 120V-277V, 250mA MDH02 347V-480V, 250mA MDL03 120V-277V, 350mA MDH03 347V-480V, 350mA MDL05 120V-277V, 500mA MDH05 347V-480V, 500mA	FDRB Fixed Dimming Resistor Board