

Project Name

Qty

Type

Catalog / Part Number



CCT - Color Temp (K)		Description																			
2,700K 3,000K 3,500K 4,000K 5,000K		The versatile VCOB-9920 conversion kit transforms existing Sternberg 9920 Gettysburg luminaires into energy-efficient luminaires at significantly reduced maintenance costs. The wide variety of options makes this the industry's choice when converting from conventional lamp sources to energy-efficient lighting; made by Sternberg Lighting for Sternberg Lighting.																			
7 Year Warranty		Physical																			
7		<table><tr><td>Series</td><td colspan="3">VCOB-9920: Gettysburg, LED Conversion Kit</td></tr><tr><td>Optional Internal Diffusing Lens</td><td colspan="3">SV2: Cylindrical Soft Vue Medium Diffused Acrylic SV4: Cylindrical Soft Vue Maximum Diffused Acrylic</td></tr></table>		Series	VCOB-9920: Gettysburg, LED Conversion Kit			Optional Internal Diffusing Lens	SV2: Cylindrical Soft Vue Medium Diffused Acrylic SV4: Cylindrical Soft Vue Maximum Diffused Acrylic												
Series	VCOB-9920: Gettysburg, LED Conversion Kit																				
Optional Internal Diffusing Lens	SV2: Cylindrical Soft Vue Medium Diffused Acrylic SV4: Cylindrical Soft Vue Maximum Diffused Acrylic																				
Certifications		Light Source																			
UL US LISTED		<table><tr><td>LED</td><td colspan="3">4L: 4 LEDs</td></tr><tr><td rowspan="3">CCT - Color Temp (K)</td><td>27: 2,700K</td><td colspan="2">30: 3,000K</td></tr><tr><td>35: 3,500K</td><td colspan="2">40: 4,000K</td></tr><tr><td>50: 5,000K</td><td colspan="2"></td></tr><tr><td colspan="2">Distribution Type</td><td>TS: Type Symmetric</td><td>TA: Type Asymmetric</td></tr></table>		LED	4L: 4 LEDs			CCT - Color Temp (K)	27: 2,700K	30: 3,000K		35: 3,500K	40: 4,000K		50: 5,000K			Distribution Type		TS: Type Symmetric	TA: Type Asymmetric
LED	4L: 4 LEDs																				
CCT - Color Temp (K)	27: 2,700K	30: 3,000K																			
	35: 3,500K	40: 4,000K																			
	50: 5,000K																				
Distribution Type		TS: Type Symmetric	TA: Type Asymmetric																		
		Electrical and control																			
Driver		<table><tr><td>MDL02: 120V-277V, 250mA</td><td>MDH02: 347V-480V, 250mA</td></tr><tr><td>MDL03: 120V-277V, 350mA</td><td>MDH03: 347V-480V, 350mA</td></tr><tr><td>MDL05: 120V-277V, 500mA</td><td>MDH05: 347V-480V, 500mA</td></tr></table>		MDL02: 120V-277V, 250mA	MDH02: 347V-480V, 250mA	MDL03: 120V-277V, 350mA	MDH03: 347V-480V, 350mA	MDL05: 120V-277V, 500mA	MDH05: 347V-480V, 500mA												
MDL02: 120V-277V, 250mA	MDH02: 347V-480V, 250mA																				
MDL03: 120V-277V, 350mA	MDH03: 347V-480V, 350mA																				
MDL05: 120V-277V, 500mA	MDH05: 347V-480V, 500mA																				
		Features																			
Optional Fixed Dimming Resistor Board		FDRB: Fixed Dimming Resistor Board																			

Specifications

LEDs	The luminaire shall use high output, high brightness LED's, consisting of a two piece assembly complete with Chip on Board (COB) LED component and COB holder frame. The LEDs shall be 100% recyclable; not contain lead, mercury or any other hazardous substances and shall be RoHS compliant. Lumen maintenance shall be determined in accordance with IESNA TM-21, based on LED manufacturer LM-80 test data of no less than 6,000 hours and in-situ testing of the luminaire by an NVLAP accredited Energy Efficient Lighting Products lab. The high-performance white LEDs will have a predicted lumen depreciation of approximately 100,000 hours with greater than 70% of initial output at 25°C. The High Brightness, High Output LED's shall be 4000K (2700K, 3000K, 3500K or 5000K option) correlated color temperature (CCT) with a 70 (minimum) color rendering index (CRI). Consult factory for custom color CCT. The luminaire shall have a minimum _____ (see table) delivered initial lumen rating when operated at steady state with an average ambient temperature of 25°C (77°F). CCT Lumen Derate Values from 4,000K 2,700K (80+ CRI)=.89 3,000K (70+ CRI)=.97 3,500K (80+ CRI)=.93 5,000K (70+ CRI)=1.01
Optics	The luminaire shall be provided with individual, refractor type optics applied to each LED. The luminaire shall provide Type ____ (Symmetric or Asymmetric) light distribution. Testing shall be done in accordance with IESNA LM-79.
UL Listing	UL listed per UL1598 and CSA 22.2 No. 250.0 for the United States and Canada. Suitable for Wet Locations.
Electronic Driver	The LED driver is UL recognized and will be securely mounted inside the fixture, for optimized performance and longevity. It will be supplied with a quick-disconnect electrical connector on the power supply, providing easy power connections for fixture installation and maintenance. It will have DC voltage output and be a constant current design. It runs at 50/60HZ and will have overload, overheat, and short circuit protection. It will be supplied with a supplemental line-ground, line-neutral and neutral-ground electrical surge protection in accordance with IEEE/ANSI C62.41.2 guidelines. It will be a high efficiency driver with a THD less than 20% and a high-power factor greater than .9. It will be dimming capable using a 0-10V signal, consult factory for more information.
Fixed Dimming Resistor Board (FDRB)	Optional numbered 10-step selector switch allows for fine adjustment of the light levels in the field, repeatable from location to location. Offers dimming from 25% to 100% of the original output. Enclosure is composite material, sealed to protect components for the life of the product.
Warranty	7-year limited warranty. See Website for Terms and Conditions.

Lumen Chart(s)

Model #	TA DELIVERED LUMENS	BUG	EFFICACY (LPW)	TS DELIVERED LUMENS	BUG	EFFICACY (LPW)	WATTAGE
4L40__-MDL05	6955	B2U3G3	89.2	7195	B3U3G3	92.2	78
4L30__-MDL05	6735	B2U3G3	86.3	6970	B3U3G3	89.4	78
4L27__-MDL05	6125	B2U3G3	78.5	6335	B3U3G3	81.2	78
4L40__-MDL03	5125	B2U3G3	94.9	5270	B3U3G2	97.6	54
4L30__-MDL03	4965	B2U3G3	91.9	5105	B3U3G2	94.5	54
4L27__-MDL03	4515	B2U3G3	83.6	4640	B3U3G2	85.9	54
4L40__-MDL02	3765	B1U3G2	99.1	3850	B2U3G2	101.3	38
4L30__-MDL02	3645	B1U3G2	95.9	3730	B2U3G2	98.2	38
4L27__-MDL02	3315	B1U3G2	87.2	3390	B2U3G2	89.2	38

Options



Fixed Dimming Resistor Board (**FDRB**)



Internal Cylindrical Soft View Lens (**SVx**)

How to Order

Series	LED	CCT - Color Temp (K)	Distribution Type	Driver	Optional Internal Diffusing Lens ⁽¹⁾	Optional Fixed Dimming Resistor Board
VCOB-9920 Gettysburg, LED Conversion Kit	4L 4 LEDs	27 2,700K 30 3,000K 35 3,500K 40 4,000K 50 5,000K	TS Type Symmetric TA Type Asymmetric	MDL02 120V-277V, 250mA MDH02 347V-480V, 250mA MDL03 120V-277V, 350mA MDH03 347V-480V, 350mA MDL05 120V-277V, 500mA MDH05 347V-480V, 500mA	SV2 Cylindrical Soft Vue Medium Diffused Acrylic ⁽²⁾ SV4 Cylindrical Soft Vue Maximum Diffused Acrylic ⁽³⁾	FDRB Fixed Dimming Resistor Board

Notes:

1. Not for use with TA optic.

2. Custom colors require upcharge.

3. Smooth finishes are available upon request.