



Project Name

Qty

Type

Catalog / Part Number



Certifications



Finish



Description


The A78LED Cambridge and A78BLED Frisco series are stylized Victorian acorn fixtures which consist of a decorative cast aluminum fitter, cage, hinged roof and high efficiency prismatic acrylic acorn. The cage includes four cast aluminum medallions finished in gold. The acorn will include a cast aluminum decorative urn finial.

EPA: 2.03 (ft²) | WEIGHT: 22 LBS

Features

Mounting Configuration	1W: Wall Mount	PT: Post Top
	1A: 1 Arm Mount	1APT: 1 Arm & Post Top
	2A: 2 Arm Mount @ 180°	2A90: 2 Arm Mount @ 90°
	2APT: 2Arm @180 & Post Top	3A: 3 Arms @ 120°
	3A90: 3 Arms @ 90°	3APT: 3Arm @120 & Post Top
	4A: 4 Arms @ 90°	4APT: 4Arm @90 & Post Top
	1AM: 1Arm MidMount	2AM: 2Arm MidMount @180
	450PB: Pier Base	
Fixture	A78LED: Cambridge A78BLED: Frisco	
Fitter	5P: Slip fit 3" OD x 3" tall tenon/pole 990: Utility-Fitter, Slip fit 3" OD x 3" tall tenon/pole 991: Utility-Fitter, Slip fit 3" OD x 3" tall tenon/pole 992: Utility-Fitter, Slip fit 3" OD x 3" tall tenon/pole 993: Utility-Fitter, Slip fit 3" OD x 3" tall tenon/pole 994: Utility-Fitter, Slip fit 4" OD x 3" tall tenon/pole 995: Utility-Fitter, Slip fit 4" OD x 3" tall tenon/pole BD4: Slip fit 4" OD x 5" tall tenon/pole BD5: Slip fit 5" OD x 6" tall tenon/pole BD7: Slip fit 7" OD x 1" tall tenon/pole OL3: Oak-Leaf, Slip fit 3" OD x 3" tall tenon/pole OL4: Oak-Leaf, Slip fit 4" OD x 3" tall tenon/pole C2097: Low-Profile, Slip fit 7" OD x 1" tall tenon/pole	
Lens	A: Prismatic Acrylic Acorn	


Mounting Configuration



CCT - Color Temp (K)



Distribution Type



Optional Control Receptacle	R7: 7-Pin control receptacle only	
Optional Control	PE: Twist-Lock Photocontrol (120V-277V) PE4: Twist-Lock Photocontrol (347V-480V) SC: Shorting Cap PEC: Electronic Button Photocontrol (120V-277V) PEC4: Electronic Button Photocontrol (480V)	
Optional Fuse	FHD: Double Fuse and Holder	
Optional Ring	MP: Medallions Painted to Match fixture finish CL: Custom Logo on Decorative Ring	
Optional Terminal Block	TB: Terminal Block	
Optional Receptacle	GFI: 120V, 15A Duplex GFI for Utility Fitter	
Optional House Side Shield	HSS: 120° House Side Shield	
Optional Fixed Dimming Resistor Board	FDRB: Fixed Dimming Resistor Board	
Finish	BKT: Black Textured WHT: White Textured PGT: Park Green Textured ABZT: Arch Med Bronze Tex DBT: Dark Bronze Textured VG: Verde Green SI: Swedish Iron OWGT: Old World Gray Tex OI: Old Iron RT: Rust WBR: Weathered Brown CD: Cedar WBK: Weathered Black TT: Two Tone CM: Custom Match	
Light Source		
LED	4L: 4 LEDs	
CCT - Color Temp (K)	27: 2,700K 30: 3,000K 35: 3,500K 40: 4,000K 50: 5,000K	
Distribution Type	T3: Type 3 T4: Type 4 T5: Type 5	
Driver	MDL02: 120V-277V, 250mA MDL03: 120V-277V, 350mA MDL05: 120V-277V, 500mA MDL06: 120V-277V, 630mA	MDH02: 347V-480V, 250mA MDH03: 347V-480V, 350mA MDH05: 347V-480V, 500mA MDH06: 347V-480V, 630mA

Important

Virtual Patent Marking Notice

This website (<https://www.lmpg.com/patents-trademarks>) is provided to satisfy the virtual patent marking provisions of applicable jurisdictions. Some products listed may be covered by additional patents not referenced here.

How to Order

Mounting Configuration	Fixture	Fitter ⁽²⁾	LED	CCT - Color Temp (K)	Distribution Type	Driver	Lens
1W Wall Mount	A78LED Cambridge	5P 3" OD x 3" tall tenon	4L 4 LEDs	27 2,700K	T3 Type 3	MDL02 120V-277V, 250mA	A Prismatic Acrylic Acorn
PT Post Top	A78BLED Frisco	990 Utility-Fitter, Slip fit 3" OD x 3" tall tenon/pole		30 3,000K	T4 Type 4	MDH02 347V-480V, 250mA	
1A 1 Arm Mount		991 Utility-Fitter, Slip fit 3" OD x 3" tall tenon/pole		35 3,500K	T5 Type 5	MDL03 120V-277V, 350mA	
1APT 1 Arm & Post Top		992 Utility-Fitter, Slip fit 3" OD x 3" tall tenon/pole		40 4,000K		MDH03 347V-480V, 350mA	
2A 2 Arm Mount @ 180°		992 Utility-Fitter, Slip fit 3" OD x 3" tall tenon/pole		50 5,000K		MDL05 120V-277V, 500mA	
2A90 2 Arm Mount @ 90°		993 Utility-Fitter, Slip fit 3" OD x 3" tall tenon/pole				MDH05 347V-480V, 500mA	
2APT 2Arm @180 & Post Top		993 Utility-Fitter, Slip fit 3" OD x 3" tall tenon/pole				MDL06 120V-277V, 630mA	
3A 3 Arms @ 120°		994 Utility-Fitter, Slip fit 4" OD x 3" tall tenon/pole				MDH06 347V-480V, 630mA	
3A90 3 Arms @ 90°		995 Utility-Fitter, Slip fit 4" OD x 3" tall tenon/pole					
3APT 3Arm @120 & Post Top		BD4 Slip fit 4" OD x 5" tall tenon/pole					
4A 4 Arms @ 90°		BD5 Slip fit 5" OD x 6" tall tenon/pole					
4APT 4Arm @90 & Post Top		BD7 Slip fit 7" OD x 1" tall tenon/pole					
1AM 1Arm MidMount		OL3 Oak-Leaf, Slip fit 3" OD x 3" tall tenon/pole					
2AM 2Arm MidMount @180		OL4 Oak-Leaf, Slip fit 4" OD x 3" tall tenon/pole					
450PB Pier Base ⁽¹⁾		C2097 Low-Profile, Slip fit 7" OD x 1" tall tenon/pole ^{(3) (4)}					

Notes:

- 1. For use with 3" fitters only
- 2. Use 3" fitter for arm applications.
- 3. Consult factory for use on concrete poles.
- 4. Not for use with button photocell

How to Order

Optional Control Receptacle ⁽⁵⁾ ⁽⁶⁾ ⁽⁷⁾	Optional Control	Optional Fuse ⁽¹⁰⁾	Optional Ring	Optional Terminal Block ⁽⁵⁾	Optional Receptacle ⁽⁵⁾ ⁽¹²⁾	Optional House Side Shield ⁽¹³⁾	Optional Fixed Dimming Resistor Board ⁽⁹⁾	Finish
R7 7-Pin control receptacle only	PE Twist-Lock Photocontrol (120V-277V) ⁽⁸⁾ PE4 Twist-Lock Photocontrol (347V-480V) ⁽⁸⁾ SC Shorting Cap ⁽⁸⁾ PEC Electronic Button Photocontrol (120V-277V) ⁽⁹⁾ PEC4 Electronic Button Photocontrol (480V) ⁽⁹⁾	FHD Double Fuse and Holder	MP Medallions Painted to Match fixture finish CL Custom Logo on Decorative Ring ⁽¹¹⁾	TB Terminal Block	GFI 120V, 15A Duplex GFI for Utility Fitter	HSS 120° House Side Shield	FDRB Fixed Dimming Resistor Board	BKT Black Textured ⁽¹⁴⁾ WHT White Textured ⁽¹⁴⁾ PGT Park Green Textured ⁽¹⁴⁾ ABZT Arch Med Bronze Tex ⁽¹⁴⁾ DBT Dark Bronze Textured ⁽¹⁴⁾ VG Verde Green SI Swedish Iron OWGT Old World Gray Tex OI Old Iron ⁽¹⁵⁾ RT Rust ⁽¹⁵⁾ WBR Weathered Brown ⁽¹⁵⁾ CD Cedar ⁽¹⁵⁾ WBK Weathered Black ⁽¹⁵⁾ TT Two Tone ⁽¹⁵⁾ CM Custom Match ⁽¹⁵⁾

Notes:

5. For 900 series utility fitter only.

6. Not for use with FDRB.

7. For use with standard 3-Pin photocells only, not for use with a wireless network controller.

8. Requires control receptacle.

9. Not for use with R7.

10. Ships loose for installation in base.
11. Consult factory for specification details.

12. For use with MDLxx driver only.

13. Not for use with TS optic.

14. Smooth finishes are available upon request.

15. Custom colors require upcharge.

Specifications

Available with Intellistreets® Technology	Intellistreets® is an integrated set of solutions offering the capability to see, hear, and record what's happening on your streets, through both cameras and audio sensors.
Fitter	The sand cast fitter is a heavy wall, low-copper aluminum 356 alloy for enhanced corrosion resistance and high tensile strength. It will have an 8-1/2" inside diameter opening to attach to the 8" neck of the lens. It includes 4 stainless steel Allen-head set screws for attachment. The fitter will include a one-piece ring bug gasket to resist insect penetration. Utility Fitter: The die-cast fitter shall be heavy wall, low-copper 360 aluminum alloy for enhanced corrosion resistance and high tensile strength. It shall have a hinged, tool-less entry door that provides open access to all components. The 900 series shall have an optional terminal block for ease of wiring, an optional Twist-Lock Photocontrol receptacle, an optional single GFCI outlet for auxiliary power needs. The top mounted driver mounting plate will provide tool-less removal from the housing using 2 finger latches. The fitter shall have a one-piece ring gasket to resist insect penetration into globe assembly. When supplied with GFCI receptacle a hole will be provided for cord and plug installation with the access door closed. When cord and plug is not in use a filler plug will be provided and shall be tethered to the fitter for easy recovery and installation.
Medallions	Includes Four cast aluminum 3" medallions in a GOLD finish. Mounted on a 2.75" tall horizontal band with vertical slots Optional version with medallions painted to match fitter. (MP) Consult factory for custom logos.
Hardware	Includes Stainless steel hardware. Most finishes will include hardware with a Black Oxide conversion coating. Light finishes will get non-color coated hardware (Whites and Silvers)
Serviceability	Easy access to service the lens in the field. Tool-less access to the driver compartment after the acorn is removed allows for trouble free servicing of the LED Driver and Surge Suppressor.
UL Listing	UL listed per UL1598 and CSA C22.2 No. 250.0 for the United States and Canada. Suitable for Wet Locations.
Electronic Driver	The LED driver is UL recognized and will be securely mounted inside the fixture, for optimized performance and longevity. It will be supplied with a quick-disconnect electrical connector on the power supply, providing easy power connections for fixture installation and maintenance. It will have DC voltage output and be a constant current design. It runs at 50/60HZ and will have overload, overheat, and short circuit protection. It will be supplied with a supplemental line-ground, line-neutral and neutral-ground electrical surge protection in accordance with IEEE/ANSI C62.41.2 guidelines. It will be a high efficiency driver with a THD less than 20% and a high-power factor greater than .9. It will be dimming capable using a 0-10V signal, consult factory for more information.
Finish	Our 6 Stage Polyester Powder coat paint system offers a beautiful high-end finish that holds up to even the most extreme environments. Each part is inspected for quality and consistency before being released for shipment. Our system exceeds AAMA 2604, AAMA 2605, ASTM D523 and ASTM D4214 requirements.
Traditional Finish	Traditional paint finishes are available in Sternberg Lighting's Traditional product line. A range of colors help accent the decorative elements on the product. Finishes are available in textured or smooth. Available finishes include: Black, White, Park Green, Architectural Medium Bronze and Dark Bronze
Sternberg Select Finish	The Sternberg Select antique-inspired palette adds a touch of vintage elegance to modern applications. Old World Gray Textured is a 1 part powder coat with metallic flakes. Verde Green and Swedish Iron is a 2 part finish that includes a powder coat base coat with a hand applied antique top coat. The top coat is unique to each application and changes over time.
Custom Finish	Custom finishes are offered to adapt to any application. Rust, Weathered Brown and Cedar are special 1 part powder coat finishes with a distinctive look. Old Iron and Weathered Black are 2 part finishes that includes a powder coat base coat with a hand applied antique top coat. The top coat is unique to each application and changes over time. Two-Tone and Custom Match options are available to blend Sternberg product with the site, consult factory for more information.
Warranty	7-year limited warranty. See Website for Terms and Conditions.

LEDs	The LEDs in this system will be mounted vertically. They fully illuminate the luminaire and allow some up-light for vertical illumination. The luminaire shall use high output, high brightness LEDs, consisting of a two piece assembly complete with Chip on Board (COB) LED component and COB holder frame. The LEDs shall be 100% recyclable; not contain lead, mercury or any other hazardous substances and shall be RoHS compliant. Lumen maintenance shall be determined in accordance with IESNA TM-21, based on LED manufacturer LM-80 test data of no less than 6,000 hours and in-situ testing of the luminaire by an NVLAP accredited Energy Efficient Lighting Products lab. The high performance white LED's will have a predicted lumen depreciation of approximately 100,000 hours with greater than 70% of initial output at 25°C. The High Brightness, High Output LEDs shall be 4000K (2700K, 3000K, 3500K or 5000K option) correlated color temperature (CCT) with a 70 (minimum) color rendering index (CRI). Consult factory for custom color CCT. The luminaire shall have a minimum _____ (see table) delivered initial lumen rating when operated at steady state with an average ambient temperature of 25°C (77°F). CCT Lumen Derate Values from 4,000K 2,700K (80+ CRI)=.88 3,000K (70+ CRI)=.97 3,500K (80+ CRI)=.93 5,000K (70+ CRI)=1.01
Optics	The luminaire shall be provided with refractor type optics from the external prismatic acorn lens. The luminaire shall provide Type ____ (3, 4 or 5) light distribution per the IESNA classifications. Testing shall be done in accordance with IESNA LM-79.
Backlight Optical Control	An optional INTERNAL 120° House Side Shield helps control backlight.
Fixed Dimming Resistor Board (FDRB)	Optional numbered 10-step selector switch allows for fine adjustment of the light levels in the field, repeatable from location to location. Offers dimming from 25% to 100% of the original output. Enclosure is composite material, sealed to protect components for the life of the product.
Photocontrols	Button Photocell: The photocontrol shall be mounted on the fixture and pre-wired to driver. The electronic button type photocontrol is instant on and will turn on at 1.5 footcandles and will turn off at 2-3 footcandles. See pole spec sheet for pole mounted version. Twist-Lock Style (Utility Fitter): The photocontrol shall be mounted in the utility fitter and prewired to driver. Utility fitter includes acrylic window to read ambient light levels. The twist lock type photocontrol is instant on with a 3-6 second turn off, and shall turn on at 1.5 footcandles with a turnoff at 2-3 footcandles. Photocontrol is 120-277 volt and warranted for 6 years. For use with standard photocells only, not for use with a wireless network controller.

Lumen Chart(s)

Model #	T3 DELIVERED LUMENS	BUG	EFFICACY (LPW)	T4 DELIVERED LUMENS	BUG	EFFICACY (LPW)	T5 DELIVERED LUMENS	BUG	EFFICACY (LPW)	WATTAGE
4L40T_-MDL06	5340	B1U3G3	54.5	5275	B3U3G3	53.8	5400	B3U3G3	55.1	98
4L30T_-MDL06	5170	B1U3G3	52.8	5110	B3U3G3	52.1	5230	B3U3G3	53.4	98
4L27T_-MDL06	4700	B1U3G3	48.0	4645	B3U3G3	47.4	4755	B3U3G3	48.5	98
4L40T_-MDL05	4395	B1U3G3	58.6	4355	B2U3G3	58.1	4405	B3U3G3	58.7	75
4L30T_-MDL05	4255	B1U3G3	56.7	4220	B2U3G3	56.3	4265	B3U3G3	56.9	75
4L27T_-MDL05	3870	B1U3G3	51.6	3835	B2U3G3	51.1	3880	B3U3G3	51.7	75
4L40T_-MDL03	3450	B1U3G3	62.7	3395	B2U3G2	61.7	3445	B3U3G2	62.6	55
4L30T_-MDL03	3340	B1U3G3	60.7	3290	B2U3G2	59.8	3335	B3U3G2	60.6	55
4L27T_-MDL03	3040	B1U3G3	55.3	2990	B2U3G2	54.4	3035	B3U3G2	55.2	55
4L40T_-MDL02	2540	B1U3G2	63.5	2510	B2U3G2	62.8	2530	B2U3G2	63.3	40
4L30T_-MDL02	2460	B1U3G2	61.5	2430	B2U3G2	60.8	2450	B2U3G2	61.3	40
4L27T_-MDL02	2235	B1U3G2	55.9	2210	B2U3G2	55.3	2230	B2U3G2	55.8	40

Fitters



5P Fitter

10-1/8" W x 10-3/8" H
Fits 3" OD x 3" tall tenon/pole



990 (or 994) Utility Fitter

10-1/2" W x 15-3/4" H
Fits 3" (or 4") OD x 3" tall tenon/pole



991 Utility Fitter

10-1/2" W x 13-1/8" H
Fits 3" OD x 3" tall tenon/pole



992 Utility Fitter

10-1/2" W x 13-1/8" H
Fits 3" OD x 3" tall tenon/pole



993 (or 995) Utility Fitter

10-1/2" W x 15-3/4" H
Fits 3" (or 4") OD x 3" tall tenon/pole



BD4 Fitter

10-1/8" W x 10-1/8" H
Fits 4" OD x 5" tall tenon/pole



BD5 Fitter

10-1/8" W x 10-1/4" H
Fits 5" OD x 6" tall tenon/pole



BD7 Fitter

10-1/8" W x 11-3/4" H
Fits 7" OD x 1" tall tenon/pole



OL3 (or OL4) Fitter

10-1/8" W x 10-3/8" H
Fits 3" (or 4") OD x 3" tall tenon/pole



C2097 Fitter

10" W x 3-1/4" H
Fits 7" OD x 1" tall tenon/pole

Options




Button Photocell **(PEC)**




Fixed Dimming Resistor Board
(FDRB)



Double Fuse Holder & (2) 3A Fuses **(FHD)**



House Side Shield **(HSS)**



Custom Logo *(Example)* **(CL)**

Utility Fitter Details

Optional Accessories

990 Utility Fitter

