



TZG3-XX-QU/S812, TZG3-XX-QU/S8, TZG3-XX-QU/S812, TZG13-XX-QU/S8

**SPECIFICATION**

- ALUMINUM SHOWER COLUMN CASING
- 6MM THICK TEMPERED GLASS FACING
- ½" THERMOSTATIC VALVE
- 3 FUNCTIONS DIVERTER VALVE WITH HALF ZONES
- ASSEMBLED WITH STAINLESS STEEL BRAIDED HOSES
- SUPPLIED WITH ½" HI-FLOW HOSES
- ANTI-LIMESCALE SILICONE NOZZLES
- PRESSURE : MINIMUM 35 PSI, MAXIMUM 80 PSI
- ½" CONNECTION

**AVAILABLE OPTION**

- AVAILABLE WITH OR WITHOUT BODY JETS
- CHOICE OF 2 SHOWER HEADS (8"x 8" AND 8"x 12")
- HAND SHOWER HOLDER SUPPORT REPLACED BY A SLIDING BAR

**AVAILABLE FINISH**

- TEMPERED GLASS: LAMINATED VINYL BACKING FINISHES  
REFER TO WEBSITE FOR CHOICE OF COLORS

**ACCESSORIES**

ACCESSORIES	TZG3-XX-QU/S812	TZG3-XX-QU/S8	TZG13-XX-QU/S812	TZG13-XX-QU/S8
SHOWER HEAD	SSTS-812-Q	PVTS-08-Q	SSTS-812-Q	PVTS-08-Q
HAND SHOWER	HS-212	HS-212	HS-212	HS-212
SUPPORT	HSH-302	HSH-302	HSHC-101-70	HSHC-101-70
HOSE	SSHE-175	SSHE-175	SSHE-150	SSHE-150
DIVERTER SPOUT	R-36	R-36	R-26	R-26


**FLOW RATE**

THERMOSTATIC VALVE	30 L/MIN [7.9 GPM] @ 60 PSI
SHOWER HEAD	9.5 L/MIN [2.5 GPM] @ 60 PSI
HAND SHOWER	9.5 L/MIN [2.5 GPM] @ 60 PSI
JETS (2)	9.7 L/MIN [2.6 GPM] @ 60 PSI
DIVERTER SPOUT	17 L/MIN [4.5 GPM] @ 60 PSI
SPOUT	19.7 L/MIN [5.2 GPM] @ 60 PSI

**WARRANTY**

PRODUCTS COVERED BY A FULL LIMITED LIFETIME WARRANTY AGAINST ALL MANUFACTURING DEFECTS.

FOR MORE INFORMATION ABOUT THE PRODUCT, OR BEFORE PROCEEDING TO ANY INSTALLATION PLEASE CONSULT THE INSTALLATION MANUAL.



ASME 112.118.1 / CSA B125.1.

THE PRODUCT MAY VARY SLIGHTLY FROM ITS DIMENSION AND APPEARANCE.

REV.: 02/2018