





TRT Crane Pads evenly distribute outrigger crane loads.

Quality engineering ensures all TRT Crane Pads adhere to the CICA industry standards.

PAD-031-T

PAD WEIGHT: 470kg

MINIMUM FOOT SIZE: Ø300mm

MAXIMUM SPAN: 1000mm

MAXIMUM LOAD: 100T

Ground Pressure Rating							
WIDTH (r	mm)	1480					
LENGTH (mm)	2100					
CONTACT AR	EA (m^2)	3.1					
GROUND PRESSURE	kg / m^2	kPa					
25 TONNE	8044	79					
50 TONNE	16088	158					
100 TONNE	32175	316					

	UNLESS OTHERWISE STATED				TED	WELL	DING: ALL INFOR	MATION SHALL COMPLY WITH NZ/AS 1554:2000 PT 1 CATEGORY SP UNLESS		
	GENERAL TOLERANCES		0.00 = ± 0.05 0.0 = ± 0.2 0 = ± 0.5 THIRD ANGLE PROJECTION		OTHERWISE STATED AND SHALL BE WELDED TO A QUALIFIED PROCEDURE, BY A WELDER QUALIFIED FOR THE APPOPRIATE POSITION AND SUPERVISED BY A WELDING SUPERVISOR					
	ANGLES	0	$= \pm 0.5^{\circ}$		SURFACE FINISH (µm)					
	THIS DRAWING IS © COPYRIGHT AND IS THE PROPERTY OF TIDD ROSS TODD LTD. IT IS FURNISHED TO YOU FOR CONFIDENTIAL INFORMATION PURPOSES ONLY AND IS NOT TO BE DISCLOSED TO ANYONE ELSE OR USED FOR MANUFACTURING PURPOSES WITHOUT				PROPERTY	E	23/11/22	UPDATED PAD TO REDUCE WEIGHT	DT	
					INFORMATION	D	25/08/2022	WEB END REVISED FOR MANUFACTURABILITY	MJ	
						С	07/03/22	ADDED CORNER RODS NOTE	DT	
						В	09/02/22	UPDATED LOGO AND TOLERANCES	DT	
	THE EXPRESS WRITTEN PERMISSION OF TIDD ROSS TODD LTD.					REV	DATE	COMMENT	NAME	



TIDD ROSS TODD LTD
48 Maui Street, Hamilton,
New Zealand
Phone: +64 7 849 4839
Email: trt@trt.co.nz
Website: trt.co.nz
ISO9001:2015

	NA	ME	DAI	Έ	TITLE:	D 0100 V 1 400	A CC\/	
DRAWN	JH		14/05	5/20	CRANE PAD 2100 X 1480 ASSY			
CHK'D	-		-					
APPV'D	-		-		SHEET 3 OF 3	DWG NO.	REVISION	
DO NOT SCALE DRAWINGS IN mm's		TUS -	М	SCALE:1:15	PAD-031	E		