





TRT Crane Pads evenly distribute outrigger crane loads. Quality engineering ensures all TRT Crane Pads adhere to the CICA industry standards.

PAD-050-T

PAD WEIGHT: 1141kg

MINIMUM FOOT SIZE: Ø300mm

MAXIMUM SPAN: 1000mm

MAXIMUM LOAD: 200T

Ground Pressure Rating									
WIDTH (r	mm)	2470							
LENGTH (mm)	2025							
CONTACT AR	EA (m^2)	5.0							
GROUND PRESSURE	kg / m^2	kPa							
25 TONNE	4998	49							
50 TONNE	9997	98							
100 TONNE	19993	196							
150 TONNE	29990	294							
200 TONNE	39986	392							

UNLESS OTHERWISE STATED	WELDING: ALL INFORMATION SHALL COMPLY WITH NZ/AS 1554:2000 PT 1 CATEGORY SP UNLESS				
GENERAL TOLERANCES 0.00 = ± 0.05 0.0 = ± 0.0	OTHERWISE STATED AND SHALL BE WELDED TO A QUALIFIED PROCEDURE, BY A WELDER QUALIFIED FOR THE APPOPRIATE POSITION AND SUPERVISED BY A WELDING SUPERVISOR				
ANGLES $0 = \pm 0.5^{\circ}$ SURFACE FINISH (μ m)					
THIS DRAWING IS © COPYRIGHT AND IS THE PROPERTY					
OF TIDD ROSS TODD LTD.					
IT IS FURNISHED TO YOU FOR CONFIDENTIAL INFORMATION					1
PURPOSES ONLY AND IS NOT TO BE DISCLOSED TO ANYONE	С	14/10/22	REMOVED DRAIN HOLES DT	DT	
ELSE OR USED FOR MANUFACTURING PURPOSES WITHOUT	В	07/09/2022	WEB END REVISED, LOGO UPDATED, CORNER RODS ADDED	MJ	
THE EXPRESS WRITTEN PERMISSION OF TIDD ROSS TODD LTD.	REV	DATE	COMMENT	NAME	



TIDD ROSS TODD LTD
48 Maui Street, Hamilton,
New Zealand
Phone: +64 7 849 4839
Email: trt@trt.co.nz
Website: trt.co.nz
ISO9001:2015

)		NAM	۱E	DATE	TITLE:			
	DRAWN	JH		29/05/20	CRANE PAD 2470 X 2025 ASSY			
	CHK'D	-		-				
	APPV'D	-		-	SHEET 3 OF 3	DWG NO.	REVISIO	
	DO NOT SCALE	- 1	STA	TUS - A	1 SCALE:1:20	PAD-050		