



SCALE 1:55

PAD-105L-T

PAD WEIGHT: 3065kg

MINIMUM FOOT SIZE: Ø600mm(NON PLASTIC)

MAXIMUM SPAN: 1000mm (Standard)

MAXIMUM LOAD: 250T

Ground Pressure Rating

WIDTH (mm)		2400
LENGTH (mm)		4380
CONTACT AREA (m ²)		10.5
GROUND PRESSURE	kg / m ²	kPa
25 TONNE	2378	23
50 TONNE	4756	47
100 TONNE	9513	93
150 TONNE	14269	140
200 TONNE	19026	187
250 TONNE	23782	233

TRT Crane Pads evenly distribute outrigger crane loads.
Quality engineering ensures all TRT Crane Pads adhere to the CICA industry standards.

UNLESS OTHERWISE STATED	
GENERAL TOLERANCES	0.00 = ± 0.05 0.0 = ± 0.2 0 = ± 0.5
ANGLES	0 = ± 0.5°
THIRD ANGLE PROJECTION	1.6
SURFACE FINISH (µm)	

THIS DRAWING IS © COPYRIGHT AND IS THE PROPERTY OF TIDD ROSS TODD LTD.
IT IS FURNISHED TO YOU FOR CONFIDENTIAL INFORMATION PURPOSES ONLY AND IS NOT TO BE DISCLOSED TO ANYONE ELSE OR USED FOR MANUFACTURING PURPOSES WITHOUT THE EXPRESS WRITTEN PERMISSION OF TIDD ROSS TODD LTD.

WELDING: ALL INFORMATION SHALL COMPLY WITH NZ/AS 1554:2000 PT 1 CATEGORY SP UNLESS OTHERWISE STATED AND SHALL BE WELDED TO A QUALIFIED PROCEDURE, BY A WELDER QUALIFIED FOR THE APPROPRIATE POSITION AND SUPERVISED BY A WELDING SUPERVISOR			
REV	DATE	COMMENT	NAME
B	20/07/2023	UPDATES FOR ROBOT WELDING	JC
A	16/11/20	FIRST ISSUE	JH



TIDD ROSS TODD LTD
48 Maui Street, Hamilton,
New Zealand
Phone: +64 7 849 4839
Email: trt@trt.co.nz
Website: trt.co.nz
ISO9001:2015

NAME	DATE	TITLE:	
DRAWN	JH	16/11/20	CRANE PAD 4380 X 2400
CHK'D	-	-	
APPV'D	-	-	
DO NOT SCALE DRAWINGS IN mm's	STATUS - M	SHEET 4 OF 5 SCALE:1:25	DWG NO. PAD-105L REVISION B