

ATM Paint Remover no. PR600

Bulletin no.

www.urpaints.com			
Description	An effective paint remover in solvent type which is designed to remove paint and		
	other finishes. It is ready to	use. Easy application.	
Application	Ideal to remove any type of old coating such as alkyd enamel, lacquer, varnish, epoxy, polyurethane, etc. It can be using to a wide range of surfaces, including		
			wood, concrete, stucco, plaster or steel.
	Technical Data	Product type	: Methylene Chloride
	Appearance	: Translucent liquid.	
	Density	: 1.1 – 1.2	
	Viscosity	: C – D by Gardner Bubble Viscometer	
		at 25 °C	
	Flash point	: 24 - 25 °C (ASTM 7094)	
	Application tools	: Brush	
Application Instruction	Apply ATM Paint Remover to the painted surface and allow it to remain on the		
	surface until the old coating is blistered or softened.		
	Using trowel or scrapper to scrape out the softened parts.		
	For the large surface, after the paint is softened, remove by stream or water in a		
	jet. • Make sure all residues are completely removed and clean the surface with		
			appropriated solvent or thinner.
	Coverage	No data.	
Storage & Shelf life	Maximum 6 months in sealed container. Keep container in a cool dry and well-		
	ventilated place. When not in use, keep container tightly closed and use again after		
	correct storage.		
Safety, Health and Environment Information	 Keep out of reach of c 	hildren.	
	Keep away from heat/ sparks/ open flames. No smoking.		
Information	 Keep away from heat/ 	sparks/ open flames. No smoking.	
Information		sparks/ open flames. No smoking. n a well-ventilated area.	
Information	Use only outdoors or i		
Information	Use only outdoors or iWear protective glove	n a well-ventilated area.	
Information	Use only outdoors or iWear protective gloveDo not breathe dust/ for	n a well-ventilated area. s, eye and face protection equipments.	
Information	 Use only outdoors or i Wear protective glove Do not breathe dust/ fi Do not eat, drink or sn 	n a well-ventilated area. s, eye and face protection equipments. ume/ gas/ mist/ vapours/ spray. noke when using this product.	
Information	 Use only outdoors or i Wear protective glove Do not breathe dust/ fi Do not eat, drink or sn Wash thoroughly after 	n a well-ventilated area. s, eye and face protection equipments. ume/ gas/ mist/ vapours/ spray. noke when using this product.	

Tel: +66 2 312 1049-50, +66 2 750 4808-9 Fax: +66 2 312 1163 www.urpaints.com



ATM Paint Remover no. PR600

Bulletin no.

	If inhaled, removes victim to fresh air and keep at rest in a position comfortable	
	of breathing.	
	Do not empty into drains.	
	Avoid release to the environment, some constituents of product is toxic to the	
	aquatic life.	
	Contents are under pressure. <u>Do not shake</u> .	
	Always by careful when unscrew the cap and cautiously open cap to avoid any	
	accident from the pressure inside.	
Packing	0.3 kg, 1 kg, 4 kg	

Tel: +66 2 312 1049-50, +66 2 750 4808-9 Fax: +66 2 312 1163 www.urpaints.com