

ATM ROOF PAINT

Bulletin no.

Description	A premium blend of high quality light fastness pigments in pure acrylic binder,
	specialized formulated for long lasting protection on roof surfaces under tropical
	climate. It provides smooth and durable finishes, retention colour in long life. Good
	protection against algae and fungus. Free from lead and mercury.
Application	An idealized to use as roof finish for variety of roof tiles, flat sheet and fibre cement
	board.
Technical Data	Product type : Acrylic Emulsion
	Appearance : Colour viscous liquid regarding to catalog.
	Film type : Semi-gloss
	Specific Gravity (water = 1) : 1.3 – 1.4
	Viscosity : 100 - 105 KU at 25 °C
	Application tools : Brush – Roller – Conventional spray
	Drying time at 25 °C
	- Dry to touch : 30 - 60 minutes.
	- Dry to recoat : 3 – 4 hours.
Painting System	Surface preparation : Clean the surface to be free from dust, dirt, grease
	or any loose particles.
	Priming : Not required.
	Top coating : Apply ATM Roof Paint at least 2 coats.
Coverage	35 – 40 sq.m/ gallon. /coat
Storage & Shelf life	Maximum 2 years in sealed container. Keep container in a cool dry and well-ventilated
	place. Protect from direct sunlight. When not in use, keep container tightly closed and
	use again after correct storage.
Safety, Health and Environment	Keep out of reach of children. Use in a well-ventilated area. Avoid contact with skin or
Information	eyes. Wash thoroughly after handling. If on skin, wash with plenty of soap and rinse
	skin with clean water. If in eyes, rinse cautiously with water for several minutes. Do not
	use empty container for food stuff. Do not empty into drains.
Packing	0.946 Litres, 3.785 Litres and 18.925 Litres

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.