



URAI PAINTS
www.urpaints.com

GALANT Pigment Emulsion Special Colour

Bulletin no.

Description	A water-borne acrylic emulsion special colour which developed from high quality of acrylic and pigments. More colours to be provided. Good adhesion and good colour retention. Easy to use. Suitable for both of exterior and interior application.																				
Application	It is widely used for art and decoration, both of full shade and tinting with white base of emulsion paint to apply on many surfaces such as cement, concrete, billboards, plaster, clothes, etc.																				
Technical Data	<table><tr><td>Product type</td><td>: Acrylic Co-polymer</td></tr><tr><td>Appearance</td><td>: Refer to Catalogue of Galant Acrylic Emulsion Paint</td></tr><tr><td>Film type</td><td>: Matt</td></tr><tr><td>Specific Gravity (water = 1)</td><td>: 1.4 – 1.5</td></tr><tr><td>Viscosity</td><td>: 112 – 117 KU at 25 °C</td></tr><tr><td>pH</td><td>: 8.5 – 9.5</td></tr><tr><td>Application tools</td><td>: Brush – Roller – Conventional spray</td></tr><tr><td>Drying time at 25 °C</td><td></td></tr><tr><td>- Dry to touch</td><td>: 30 - 60 minutes.</td></tr><tr><td>- Dry to recoat</td><td>: 1 – 2 hours.</td></tr></table>	Product type	: Acrylic Co-polymer	Appearance	: Refer to Catalogue of Galant Acrylic Emulsion Paint	Film type	: Matt	Specific Gravity (water = 1)	: 1.4 – 1.5	Viscosity	: 112 – 117 KU at 25 °C	pH	: 8.5 – 9.5	Application tools	: Brush – Roller – Conventional spray	Drying time at 25 °C		- Dry to touch	: 30 - 60 minutes.	- Dry to recoat	: 1 – 2 hours.
Product type	: Acrylic Co-polymer																				
Appearance	: Refer to Catalogue of Galant Acrylic Emulsion Paint																				
Film type	: Matt																				
Specific Gravity (water = 1)	: 1.4 – 1.5																				
Viscosity	: 112 – 117 KU at 25 °C																				
pH	: 8.5 – 9.5																				
Application tools	: Brush – Roller – Conventional spray																				
Drying time at 25 °C																					
- Dry to touch	: 30 - 60 minutes.																				
- Dry to recoat	: 1 – 2 hours.																				
Painting System	<ul style="list-style-type: none">- New surfaces should be fully cured at least 1 month to avoid any damaging from efflorescence. For old painted surface, all dirty stains should be removed and clean.- Make sure the surface to be free from dust, dirt, grease or any loose particles.- Stir thoroughly before use. In case of tinting with white base of emulsion paint, the Special Colours can be added as much as to meet the desirable colour shade. Water is allowed to be added if viscosity of mixed content is too thick.																				
Coverage	8 - 10 sq.m/ litres /coat																				
Storage & Shelf life	Maximum 5 years in sealed container. Keep container in a cool dry and well-ventilated place. Protect from direct sunlight. When not in use, keep container tightly closed and use again after correct storage.																				
Safety, Health and Environment Information	Keep out of reach of children. Use in a well-ventilated area. Avoid contact with skin or eyes. Wash thoroughly after handling. If on skin, wash with plenty of soap and rinse skin with clean water. If in eyes, rinse cautiously with water for several minutes. Do not use empty container for food stuff. Do not empty into drains.																				
Packing	0.236 L/ 0.9 L/ 3.6 L/ 10 L and 18 L																				

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.