



URAI PAINTS
www.urpaints.com

Lion Brand Wood Shellac Polish

Bulletin no.

Description	A special formula of rosin and translucent pigments in desirable solvent. An ideal to bring out wood grains and textures to be colourful with semi-gloss and transparent film																														
Application	For decoration to wood furniture or other wood works e.g. door, window or panels. The colour shades after application may vary from actual colour from a different type of wood. Suitable for Exterior and Interior.																														
Technical Data	<table><tr><td>Product type</td><td>:</td><td>Wood Shellac Polish.</td></tr><tr><td>Appearance</td><td>:</td><td>Colour liquid according to product catalogue.</td></tr><tr><td>Finish</td><td>:</td><td>Semi-gloss</td></tr><tr><td>Specific Gravity (water = 1)</td><td>:</td><td>0.8 – 0.9</td></tr><tr><td>Viscosity (Ford cup # 4)</td><td>:</td><td>10 – 14 sec at 25 °C</td></tr><tr><td>Application tools</td><td>:</td><td>Brush for shellac (Soft brush)</td></tr><tr><td>Diluent</td><td>:</td><td>This product is ready to use. In case of dilution is required, recommended to use Lion brand Methyl Alcohol no. T31 as diluent only.</td></tr><tr><td colspan="3">Drying time at 25 °C</td></tr><tr><td>- Dry to touch</td><td>:</td><td>5 – 7 minutes</td></tr><tr><td>- Dry to recoat</td><td>:</td><td>1 - 2 hour.</td></tr></table>	Product type	:	Wood Shellac Polish.	Appearance	:	Colour liquid according to product catalogue.	Finish	:	Semi-gloss	Specific Gravity (water = 1)	:	0.8 – 0.9	Viscosity (Ford cup # 4)	:	10 – 14 sec at 25 °C	Application tools	:	Brush for shellac (Soft brush)	Diluent	:	This product is ready to use. In case of dilution is required, recommended to use Lion brand Methyl Alcohol no. T31 as diluent only.	Drying time at 25 °C			- Dry to touch	:	5 – 7 minutes	- Dry to recoat	:	1 - 2 hour.
Product type	:	Wood Shellac Polish.																													
Appearance	:	Colour liquid according to product catalogue.																													
Finish	:	Semi-gloss																													
Specific Gravity (water = 1)	:	0.8 – 0.9																													
Viscosity (Ford cup # 4)	:	10 – 14 sec at 25 °C																													
Application tools	:	Brush for shellac (Soft brush)																													
Diluent	:	This product is ready to use. In case of dilution is required, recommended to use Lion brand Methyl Alcohol no. T31 as diluent only.																													
Drying time at 25 °C																															
- Dry to touch	:	5 – 7 minutes																													
- Dry to recoat	:	1 - 2 hour.																													
Painting System	<p>Surface preparation :</p> <p>Smooth the substrate with sandpaper. Clean surface to be free from dirt, dust and any contaminants.</p> <p>Coating System :</p> <p>Apply by brush on prepared substrate 1-2 coats by keep an interval to recoat 1 - 2 hours. If dilution is needed or clean up tools after application. Using Lion brand methyl alcohol no. T31 only.</p>																														
Coverage	40 - 50 sq.m/ gallon /coat																														
Storage & Shelf life	Maximum 5 years in sealed container. Keep away from heat/ sparks/ open flames. No smoking. Keep container in a cool dry and well-ventilated place. Protect from direct sunlight. When not in use, keep container tightly closed and use again after correct storage.																														
Safety, Health and Environment Information	Keep out of reach of children. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye and face protection. Do no breathe vapours/ mist/ spray/ fume. Avoid contact with skin or eyes. Wash thoroughly after handling. IF ON SKIN; Wash with plenty of soap and rinse skin with clean water. IF IN EYES, Rinse cautiously with water for several minutes. Do not empty into drains. Avoid release to the environment.																														
Packing	0.48 Litres / 2 kg/ 12 kg																														

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.