



BEAUTY Shield 100% Pure Acrylic Emulsion Paint

Bulletin no.

Description	BEAUTY Shield 100% pure acrylic emulsion paint is based on formulation of high quality acrylic resin, pigments and more additives. It provides good adhesion and flexibility finish with odorless. Easy cleaning. Long-lasting protection against extreme weather condition in tropical zone. No lead and mercury compound is added.																								
Application	It is an ideal for exterior and interior walls decoration e.g. concrete, brick or gypsum board.																								
Technical Data	<table border="1"><tr><td>Product type</td><td>:</td><td>100% Pure acrylic emulsion paint.</td></tr><tr><td>Appearance</td><td>:</td><td>Color viscous liquid regarding to catalog.</td></tr><tr><td>Film type</td><td>:</td><td>Semi-gloss</td></tr><tr><td>pH</td><td>:</td><td>8-10</td></tr><tr><td>Density</td><td>:</td><td>1.100 – 1.400</td></tr><tr><td>Solid content</td><td>:</td><td>45 – 55 %</td></tr><tr><td>Viscosity</td><td>:</td><td>98 - 106</td></tr><tr><td>Drying time</td><td>:</td><td>- Dry to touch 30 minutes - Dry to recoat 2 hours</td></tr></table>	Product type	:	100% Pure acrylic emulsion paint.	Appearance	:	Color viscous liquid regarding to catalog.	Film type	:	Semi-gloss	pH	:	8-10	Density	:	1.100 – 1.400	Solid content	:	45 – 55 %	Viscosity	:	98 - 106	Drying time	:	- Dry to touch 30 minutes - Dry to recoat 2 hours
Product type	:	100% Pure acrylic emulsion paint.																							
Appearance	:	Color viscous liquid regarding to catalog.																							
Film type	:	Semi-gloss																							
pH	:	8-10																							
Density	:	1.100 – 1.400																							
Solid content	:	45 – 55 %																							
Viscosity	:	98 - 106																							
Drying time	:	- Dry to touch 30 minutes - Dry to recoat 2 hours																							
Application Instruction	<ul style="list-style-type: none">● Surface Preparation New surface: Leave the surface at least 1 month to completely cured and dried. Substrate must be free from dust, dirt, grease or loose particles. Old surface: the surface should be clean and dry. If fungus or mildew growth must be cleaned off before coating.● Primer New surface: Priming by BEAUTY Shield Acrylic Alkali-Resisting Primer S-1000 1 coat. Old surface: Priming by BEAUTY Shield Contact Primer S-1100 1 coat.● Coating System Apply BEAUTY Shield to top coat 2-3 coats by brush or roller. Drying time to recoat is 2-3 hours by approximately.																								
Coverage	35 – 40 sq.m / gallon /coat																								



URAI PAINTS
www.urapaints.com

BEAUTY Shield 100% Pure Acrylic Emulsion Paint

Bulletin no.

Storage & Shelf life	Maximum 5 years in sealed container. Protect from sunlight. Keep container tightly closed when not in use and use again after correct storage. Keep it in well-ventilated place.
Safety, Health and Environment Information	<ul style="list-style-type: none">● Keep out of reach of children.● Use in a well-ventilated area.● Avoid contact with skin or eyes.● If on skin, wash with plenty of soap and rinse skin with clean water.● If in eyes, rinse cautiously with water for several minutes.● Do not use empty container for food stuff.● Avoid release to the environment.
Packing	3.785 Litres / 10 Litres / 18.925 Litres

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3)
South Sathorn rd., Yannawaa, Sathorn,
Bangkok 10120.
Tel: +66 2 312 1049-50, +66 2 750 4808-9
Fax: +66 2 312 1163
www.urpaints.com