



LOBSTER 4 IN 1

Version 1.0

Date of issue 13.03.2021

Description	A special multi-purpose in paint system by top coat and primer can be in one application for all surfaces. Quick drying. Excellent adhesion. Anti-rust coating. Good covering with high hiding power. Heat resistant up to 160 °C. Good protection against corrosion and abrasive in aggressive environment.																																	
Application	Suitable to apply to all surfaces. Most effective on steel and metals such as galvanized steel, aluminium, stainless steel, brass, copper, etc. Including to the other substrates e.g. cement, wood, fibre cement, etc.																																	
Technical Data	<table><tr><td>Product type</td><td>:</td><td>Acrylic solvent based</td></tr><tr><td>Appearance</td><td>:</td><td>Viscous liquid in various colour by follow to LOBSTER 4 IN 1 Catalog.</td></tr><tr><td>Texture</td><td>:</td><td>Semi-gloss</td></tr><tr><td>Specific gravity (water = 1)</td><td>:</td><td>1.0 – 1.2</td></tr><tr><td>Viscosity</td><td>:</td><td>80 – 90 KU at temp 25 °C</td></tr><tr><td>Application</td><td>:</td><td>Brush, roller or spray gun.</td></tr><tr><td>Diluent</td><td>:</td><td>LION brand thinner AAA No. T72 or ATM Acrylic thinner No. T74</td></tr><tr><td colspan="3">Drying time at 25 °C</td></tr><tr><td>- Dry to touch</td><td>:</td><td>5 – 15 minutes</td></tr><tr><td>- Dry to recoat</td><td>:</td><td>30 -60 minutes</td></tr><tr><td>- Dry to recoat</td><td>:</td><td>4 – 8 hours</td></tr></table>	Product type	:	Acrylic solvent based	Appearance	:	Viscous liquid in various colour by follow to LOBSTER 4 IN 1 Catalog.	Texture	:	Semi-gloss	Specific gravity (water = 1)	:	1.0 – 1.2	Viscosity	:	80 – 90 KU at temp 25 °C	Application	:	Brush, roller or spray gun.	Diluent	:	LION brand thinner AAA No. T72 or ATM Acrylic thinner No. T74	Drying time at 25 °C			- Dry to touch	:	5 – 15 minutes	- Dry to recoat	:	30 -60 minutes	- Dry to recoat	:	4 – 8 hours
Product type	:	Acrylic solvent based																																
Appearance	:	Viscous liquid in various colour by follow to LOBSTER 4 IN 1 Catalog.																																
Texture	:	Semi-gloss																																
Specific gravity (water = 1)	:	1.0 – 1.2																																
Viscosity	:	80 – 90 KU at temp 25 °C																																
Application	:	Brush, roller or spray gun.																																
Diluent	:	LION brand thinner AAA No. T72 or ATM Acrylic thinner No. T74																																
Drying time at 25 °C																																		
- Dry to touch	:	5 – 15 minutes																																
- Dry to recoat	:	30 -60 minutes																																
- Dry to recoat	:	4 – 8 hours																																
Painting System	<div>Surface preparation:</div> <div><div>- Old surfaces: Remove old coating and clean the surface to be free from dust and dirt, oil, wax and any contaminants.</div><div><div>● Steel and metal: Remove rust from the surface and wipe off.</div><div>● Concrete: Fungus and mold should be clean thoroughly.</div><div>● Wood: Smooth with sandpaper.</div></div><div>- New surfaces: Clean the surface to be free from dust, dirt, oil, wax and any contaminants.</div><div><div>● Steel and metal: Verify the surface to be free from rust.</div><div>● Concrete: Surface should be fully cured at least 1 month.</div><div>● Wood: Smooth with sandpaper.</div></div></div>																																	

การปฏิเสธสิทธิ: ข้อมูลดังกล่าวข้างต้นได้มาจากความรู้ที่มีอยู่ในปัจจุบัน และประสบการณ์ที่ผ่านมา การที่ผลิตภัณฑ์ถูกนำไปใช้ในสภาวะที่แตกต่างกัน เราจึงไม่สามารถรับประกันในสิ่งอื่นใด นอกจากคุณภาพของสีเท่านั้น บริษัทขอสงวนสิทธิ์ในการเปลี่ยนแปลงข้อมูล โดยมีต้องแจ้งให้ทราบล่วงหน้า



URAI PAINTS
www.urpaints.com

LOBSTER 4 IN 1

Version 1.0

Date of issue 13.03.2021

	Coating System: <ul style="list-style-type: none">- Primer coating : No need for primer.- Top coating : Apply LOBSTER 4 IN 1 for 1-2 coats.- Dilution or cleaning : Strongly recommend to use LION Brand thinner No. T72 or ATM Acrylic Thinner No. T74. Other diluents or thinner is not recommended to avoid any damage in paint system.
Coverage	40 – 45 sq.m / gallon / coat
Storage and shelf life	Maximum 4 years in sealed container. Keep away from heat/ sparks/ open flames. No smoking. Keep container in a cool dry and well-ventilated place. Protect from direct sunlight. When not in use, keep container tightly closed and use again after correct storage.
Safety, Health and Environment Information	Keep out of reach of children. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye and face protection. DO Not breathe vapour/ mist/ spray or fume. Avoid contact with skin or eyes. Prolonged or repeated exposure may cause skin dryness or dermatitis. IF ON SKIN; Wash with plenty of soap and rinse skin with clean water. IF IN EYES, Rinse cautiously with water for several minutes. Avoid release to the environment
Packing	0.85 Litres/ 3.4 Litres

การปฏิเสธสิทธิ: ข้อมูลดังกล่าวข้างต้นได้มาจากความรู้ที่มีอยู่ในปัจจุบัน และประสบการณ์ที่ผ่านมา การที่ผลิตภัณฑ์ถูกนำไปใช้ในสภาวะที่แตกต่างกัน เราจึงไม่สามารถรับประกันในสิ่งอื่นใด นอกจากคุณภาพของสีเท่านั้น บริษัทขอสงวนสิทธิในการเปลี่ยนแปลงข้อมูล โดยไม่ต้องแจ้งให้ทราบล่วงหน้า

สำนักงานขาย: 52, 54 ซอยสาทร 11 (แยก 3) ถนน สาทรใต้, ยานนาวา, เขตสาทร} กรุงเทพฯ, 10120. โทร: +66 2 312 1049-50, +66 2 750 4808-9 แฟกซ์: +66 2 312 1163