

ATM Gypsum Jointing No. G120

www.urapaints.com

Version 1.0

Date of issue 26/02/2021

Description	ATM gypsum jointing no. G120 is a ready-mixed joint compound in white powder to mix with water before use. It gives creamy texture, spread easily and provide excellent bonding. High performance creates a seamless base for ceiling or interior walls.		
Application	Using for taping, finishing joint, corner bead, spotting fasteners or repairing cracks in gypsum walls.		
Technical Data	Product type	:	Mixed-cement
	Appearance	:	Powder in white colour
	Mixing ratio	:	Product: water = 2:1
	Pot life	:	60 minutes
	Appliances	:	Brush/ trowel
	Drying time at 25 °C	:	30-60 minutes
Application Instruction	<p>Surface Preparation</p> <p>The surface should be clean and dry. If there are oil or waxy contaminate must be cleaned off.</p> <p>Mixing</p> <p>Mix ATM gypsum jointing no. G120 with water in the ratio 2:1 (by weight) and stir well until it is homogeneous.</p> <p>Application</p> <ul style="list-style-type: none">● Apply the mixture with trowel or brush on seam of gypsum board.● After that, use a fabric to plastering on seam for 2 layers, leave 1st layer to dry 30-60 minutes before apply the other layer.● Sealing on seam of gypsum board again and leave it dry.● Sand the surface with sandpaper for more smoothness. <p>Recommendation</p> <ul style="list-style-type: none">● Interior use only.● Do not apply to an immersion area or high humidity condition.● Prepare with a moderate amount by according to pot life is about 60 minutes (depends on weather conditions) to avoid mixture is dry up.● Do not combine new mixture with the remains to avoid rapid drying out.		

ATM Gypsum Jointing No. G120

www.urapaints.com

Version 1.0

Date of issue 26/02/2021

Coverage	3 sq.m / 1 kg / coat
Storage & Shelf life	Maximum 2 years in sealed container. Store in room temperature. Avoid UV exposure. Keep container tightly closed and keep it in a well-ventilated place.
Safety, Health and Environment Information	<ul style="list-style-type: none"> • Keep out of reach of children. • Use personal protective equipment as required. • Use in a well-ventilated area. • If on skin, wash with plenty of soap and rinse skin with clean water. • If in eyes, rinse cautiously with water for several minutes. • Avoid release to the environment.
Packing	1 kg

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice.

Sales office: 52, 54 Soi Sathorn 11 (Sect. 3)
South Sathorn rd., Yannawaa, Sathorn,
Bangkok 10120.
Tel: +66 2 312 1049-50, +66 2 750 4808-9
Fax: +66 2 312 1163
www.urpaints.com