

Lion Brand Turpentine Grade AAA No. T21

Version 1.0 Date of issue 02.03.2022

Description	It is extensively used as a diluent for alkyd enamel paint (gloss or matt finish), varnish, undercoat white, primer for metal or steel and aluminum paint.	
Application	Used to dissolve alkyd enamel paint, varnish, undercoat white, primer for metal or steel and aluminum paint.	
Technical Data	Product Type	: Turpentine Substitute
	Appearance	: Colourless liquid.
	Density	: 0.778 – 0.783 g/cm ³ at 15 °C
	Flash Point	: 41 - 42 °C (closed cup)
	Dilution	: By brush: 5 – 10% by volume
		By spray gun: 10 – 15% by volume
	tightly closed and use again a	after correct storage.
Safety, Health and Environment	 Keep out of reach of chil 	dren
Information	 Keep away from heat/ sparks/ open flames. No smoking. 	
	Use only outdoors or in a well-ventilated area.	
	Wear protective gloves, eye and face protection equipments.	
	Wash thoroughly after handling.	
	• If on skin, wash with plenty of soap and rinse skin with clean water.	
	• If in eyes, rinse cautiously with water for several minutes.	
	If swallowed, Do NOT induced vomiting. Immediately call a POISON CENTER or	
	doctor/ physician.	
	 If inhaled, removes victim to fresh air and keep at rest in a position comfortable of breathing. 	
	• Do not empty into drains.	
	• Avoid release to the envi	ironment, some constituents of product is toxic to the aquatic
	life.	

DISCLAIMER: The above information provided herein is based on the present state of our knowledge and practical experience. Since the product is often used under different conditions beyond our control. We cannot guarantee anything but the quality of the product itself. All the rights are reserved to change the data without any notice. Sales office: 16/8 Soi Sathom 11 (Sect. 3) South Sathom rd., Yannawa, Sathom, Bangkok 10120. Tel: +66 2 312 1050 Fax: +66 2 312 1163 www.uraipaints.com