

LOBSTER 4IN1 Multi-purpose Paint & Primer in 1 for all surfaces (Gloss)

Version 1.0

Date of issue 01.01.2022

Description	A special multi-purpose in paint system by top coat and primer can be in one application for all surfaces. Quick drying. Excellent adhesion. Anti-rust coating. Good covering with high hiding power. Heat resistant up to 160 °C. Good protection against corrosion and abrasive in aggressive environment.																																		
Application	Suitable to apply to all surfaces. Most effective on steel and metals such as galvanized steel, aluminium, stainless steel, brass, copper, etc. Including to the other substrates e.g. cement, wood, fiber cement, etc.																																		
Technical Data	<table> <tr> <td>Product type</td><td>:</td><td>Acrylic solvent based</td></tr> <tr> <td>Appearance</td><td>:</td><td>Viscous liquid in various colour by follow to LOBSTER 4 IN 1 Catalog.</td></tr> <tr> <td>Texture</td><td>:</td><td>Gloss</td></tr> <tr> <td>Specific gravity (water = 1)</td><td>:</td><td>0.900 – 1.300 at temp 25 °C</td></tr> <tr> <td>Viscosity</td><td>:</td><td>80 – 90 KU at temp 25 °C</td></tr> <tr> <td>Application</td><td>:</td><td>Brush, roller or spray gun.</td></tr> <tr> <td>Diluent</td><td>:</td><td> <ul style="list-style-type: none"> - LION brand thinner AAA No. T72 - ATM Acrylic thinner No. T74 </td></tr> <tr> <td colspan="3">Drying time at 25 °C</td></tr> <tr> <td>- Dry to touch</td><td>:</td><td>15-20 minutes</td></tr> <tr> <td>- Dry to recoat</td><td>:</td><td>30 -60 minutes</td></tr> <tr> <td>- Dry to recoat</td><td>:</td><td>4 – 8 hours</td></tr> </table>		Product type	:	Acrylic solvent based	Appearance	:	Viscous liquid in various colour by follow to LOBSTER 4 IN 1 Catalog.	Texture	:	Gloss	Specific gravity (water = 1)	:	0.900 – 1.300 at temp 25 °C	Viscosity	:	80 – 90 KU at temp 25 °C	Application	:	Brush, roller or spray gun.	Diluent	:	<ul style="list-style-type: none"> - LION brand thinner AAA No. T72 - ATM Acrylic thinner No. T74 	Drying time at 25 °C			- Dry to touch	:	15-20 minutes	- Dry to recoat	:	30 -60 minutes	- Dry to recoat	:	4 – 8 hours
Product type	:	Acrylic solvent based																																	
Appearance	:	Viscous liquid in various colour by follow to LOBSTER 4 IN 1 Catalog.																																	
Texture	:	Gloss																																	
Specific gravity (water = 1)	:	0.900 – 1.300 at temp 25 °C																																	
Viscosity	:	80 – 90 KU at temp 25 °C																																	
Application	:	Brush, roller or spray gun.																																	
Diluent	:	<ul style="list-style-type: none"> - LION brand thinner AAA No. T72 - ATM Acrylic thinner No. T74 																																	
Drying time at 25 °C																																			
- Dry to touch	:	15-20 minutes																																	
- Dry to recoat	:	30 -60 minutes																																	
- Dry to recoat	:	4 – 8 hours																																	
Painting System	<p>Surface Preparation</p> <table> <tr> <td rowspan="4">Old Surfaces</td><td colspan="2">Old surfaces: Remove old coating and clean the surface to be free from dust and dirt, oil, wax and any contaminants.</td></tr> <tr> <td>Steel and Metal</td><td>Remove rust from the surface and wipe off.</td></tr> <tr> <td>Concrete</td><td>Fungus and mold should be clean thoroughly.</td></tr> <tr> <td>Wood</td><td>Smooth with sandpaper.</td></tr> <tr> <td rowspan="4">New Surfaces</td><td colspan="2">Clean the surface to be free from dust, dirt, oil, wax and any contaminants.</td></tr> <tr> <td>Steel and Metal</td><td>Verify the surface to be free from rust.</td></tr> <tr> <td>Concrete</td><td>Surface should be fully cured at least 1 month.</td></tr> <tr> <td>Wood</td><td>Smooth with sandpaper.</td></tr> </table>		Old Surfaces	Old surfaces: Remove old coating and clean the surface to be free from dust and dirt, oil, wax and any contaminants.		Steel and Metal	Remove rust from the surface and wipe off.	Concrete	Fungus and mold should be clean thoroughly.	Wood	Smooth with sandpaper.	New Surfaces	Clean the surface to be free from dust, dirt, oil, wax and any contaminants.		Steel and Metal	Verify the surface to be free from rust.	Concrete	Surface should be fully cured at least 1 month.	Wood	Smooth with sandpaper.															
Old Surfaces	Old surfaces: Remove old coating and clean the surface to be free from dust and dirt, oil, wax and any contaminants.																																		
	Steel and Metal	Remove rust from the surface and wipe off.																																	
	Concrete	Fungus and mold should be clean thoroughly.																																	
	Wood	Smooth with sandpaper.																																	
New Surfaces	Clean the surface to be free from dust, dirt, oil, wax and any contaminants.																																		
	Steel and Metal	Verify the surface to be free from rust.																																	
	Concrete	Surface should be fully cured at least 1 month.																																	
	Wood	Smooth with sandpaper.																																	

การปฏิเสธสิทธิ: ข้อมูลดังกล่าวข้างต้นได้มาจากความรู้ที่มีอยู่ในปัจจุบัน และประสบการณ์ที่ผ่านมา การที่ผลิตภัณฑ์ถูกนำไปใช้ในสภาวะที่แตกต่างกัน เราจึงไม่สามารถรับประกันในสิ่งอื่นใด นอกจากคุณภาพของสีเท่านั้น บริษัทขอสงวนสิทธิในการเปลี่ยนแปลงข้อมูล โดยไม่ต้องแจ้งให้ทราบล่วงหน้า

สำนักงานขาย: 16/8 ซอยสาทร 11 (แยก 3) ถนน สาทรใต้, ย่านนาว่า, เขตสาทร} กรุงเทพฯ, 10120. โทร: +66 2 312 1050, +66 2 750 4808-9 แฟกซ์: +66 2 312 1163

LOBSTER 4IN1 Multi-purpose Paint & Primer in 1 for all surfaces (Gloss)

Version 1.0

Date of issue 01.01.2022

Painting System (Continue)	<p>Primer Coating</p> <p>No need for primer.</p> <p>Top Coating</p> <p>Apply LOBSTER 4 IN 1 for 1-2 coats.</p> <p>Remark</p> <p>Dilution or cleaning: Strongly recommend to use LION Brand thinner No. T72 or ATM Acrylic Thinner No. T74.</p> <p>Other diluents or thinner is not recommended to avoid any damage in paint system.</p>
Coverage	40 – 45 sq.m / gallon / coat
Storage and shelf life	<p>Maximum 4 years in sealed container. Keep away from heat/ sparks/ open flames. No smoking.</p> <p>Keep container in a cool dry and well-ventilated place. Protect from direct sunlight. When not in use, keep container tightly closed and use again after correct storage.</p>
Safety, Health and Environment Information	<ul style="list-style-type: none"> ● Keep out of reach of children. ● Use only outdoors or in a well-ventilated area. ● Wear protective gloves, eye and face protection. ● DO Not breathe vapour/ mist/ spray or fume. ● Avoid contact with skin or eyes. Prolonged or repeated exposure may cause skin dryness or dermatitis. ● IF ON SKIN; Wash with plenty of soap and rinse skin with clean water. ● IF IN EYES, Rinse cautiously with water for several minutes. ● Avoid release to the environment
Packing	0.85 Litres/ 3.4 Litres

การปฏิเสธสิทธิ: ข้อมูลดังกล่าวข้างต้นได้มาจากความรู้ที่มีอยู่ในปัจจุบัน และประสบการณ์ที่ผ่านมา การที่ผลิตภัณฑ์ถูกนำไปใช้ในสภาวะที่แตกต่างกัน เราจึงไม่สามารถรับประกันในสิ่งอื่นใด นอกจากคุณภาพของสีเท่านั้น บริษัทขอสงวนสิทธิในการเปลี่ยนแปลงข้อมูล โดยมีต้องแจ้งให้ทราบล่วงหน้า

สำนักงานขาย: 16/8 ขอยสาร 11 (แยก 3) ถนน สาทรใต้, ย่านนาว่า, เขตสาทร} กรุงเทพฯ, 10120. โทร: +66 2 312 1050, +66 2 750 4808-9 แฟกซ์: +66 2 312 1163