



Key Features

- Economical wine cooling solution
- Simple installation - between wall studs
- Condensate evaporator
- Liquid measuring thermostat
- Exhaust side ductable

1600 MSRP \$1,645

3000 MSRP \$1,859

4200 MSRP \$2,049

6000 MSRP \$2,649

8000 MSRP \$2,839

Features

The XLT series is an economical cooling solution, designed for cellar enthusiasts who are on a budget but want to experience WhisperKOOL quality and performance. Designed for simple through-the-wall installation, the unit fits between standard wall studs and the rear flange eliminates the need for a support shelf. All XLT models include a condensate evaporator standard; this dissipates excess moisture that collects during normal operation. As with all WhisperKOOL systems, the XLT is equipped with a liquid measuring thermostat to accurately maintain wine temperature. The XLT has a 30°F temperature differential. In order to keep your cellar at 55°F, the area the units is exhausting into should not exceed 85°F. This makes interior installation ideal for XLT units.

Specifications

Model	1600	3000	4200	6000	8000
Cellar Size (cu. ft.)	300	650	1000	1500	2000
Dimensions	14.25"W x 15.75"H x 17"D			14.25"W x 22.75"H x 21.5"D	
Weight (lbs)	65	66	67	100	104
AMPS (starting/running)	28/4.5	30/6	32/9	36/9.5	36/10
Installation	Through-the-Wall				
Thermostat	PDT Jr. standard, optional PDT with LED display				
Temp. Delta	30°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 85°F)				
Outside Venting	Not recommended unless exhaust environment will not exceed 85F				
Ducting Options	ONLY the exhaust side can be ducted using the optional ducting kit				
Warranty	2 year parts and labor / 5 year compressor				

Optional Accessories

PDT with LED Display, Exhaust Ducting Kit, Exterior Grille