

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC





EU Type Examination Certificate

Date: 2021/05/24 n. 860212108/TE Validity: 2026/05/23

This Certificate is a translation in English of the original Certificate issued in Italian.

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health <mark>req</mark>uirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: **U-GROUP SRL** (Responsible of the Via Borgomanero, 50 – 28040 Paruzzaro (NO) – Italia PPE) Type of PPE: Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)

Category of PPE: II: "medium" risks.

This certificate is based on reference standards listed below: its validity is no longer

ensured should new version of the standards come into force.

Model: "SABER ESD" code **RS20046**

Description:

model: A (low footwear);

fastening system: by means of grey laces;

processing: direct injection;

outsole: grey compact PU "7466 360" marked "ANTISTATIC OIL RESISTANT" (CH00116);

midsole: black foam PU (CH00117) with white polystyrene inserts in the rear area;

(AT01766); the collar has been shaped to create a loop to ease the donning;

upper: lead-grey split suede leather declared thickness 1.8/2.0 mm (PL00039) and black 10 fishnet knitting VERTEX (\$100723); with a black polymeric insert in the heel area, marked "BREATHABLE", with lateral holes closed by means of a fabric/membrane; rear collar: dark grey Lycra MOREA (S100751) padded with a black folded Lycra edge

tongue: black fishnet knitting AIRNET (SI00151), lined and padded;

bellows: black coated synthetic fabric SPICE (\$100002);

vamp lining: grey three-dimensional fishnet knitting IMOLA coupled with a black canvas

quarter and tongue lining: grey 599 perforated three-dimensional fishnet knitting SURF

(SI00468);

rear collar lining: grey 599 perforated three-dimensional fishnet knitting SURF, reversed

heel-grip lining: anthracite grey non-woven fabric THORIN (\$100283);

insole: white multilayered fabric with a black print declared conductive art. WB FLEX (SP00007), which also serves as penetration resistant insert;

removable insock: grey perforated foam material coupled with a black knitting with "WOW!" stamp in contact with the user, with zig-zag stitching with conductive thread in the forepart (TL00161);

toecap: alluminum, art. A522 MARTEK (PU00041).

Optional interchangeable orthopedic insocks (DGUV 112-191) described by the Customer as follows (see also page 3): SECOSOL® by Matthias Hartmann Orthopädie + Sport GmbH (max thickness in the toetip area: 2,9 mm):

SECOSOL® COMPLETE – article number 951622012451XX

SECOSOL® LAMINATO CON TESSUTO – article number 9516101XXX7XXX





Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC





EU Type Examination Certificate

Date: 2021/05/24 n. 860212108/TE Validity: 2026/05/23

Technical Standard: EN ISO 20344:2011 Personal protective equipment – Test methods for footwear (UNI EN ISO 20344:2012) EN ISO 20345:2011 Personal protective equipment – Safety footwear (UNI EN ISO 20345:2012) Intended use: general industry, engineering industry, construction industry, agriculture, warehouses, works on trucks, cranes. Size range: from 35 to 48 Technical File: DC-13534/E RCT n°4031841/E Test report: Functions and basic requirements for safety footwear (SB) (see Table 2 and 3 of EN ISO 20345:2011); all performance levels: mandatory ones, among which: **SRC = Slip resistance** – meets the following requirement: - surface: ceramic / <u>lubricant</u>: detergent solution; - <u>surface</u>: steel / <u>lubricant</u>: glycerol. Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011): \$1 = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil; **P** = penetration resistance of the sole. Note 1: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption). Note 2: the footwear also meets the requirement in accordance with IEC 61340-5-1:2016 (IEC 61340-4-3:2017) for the electrical resistance **ESD** (electric dissipative footwear). Marking: on a stitched label and displaying the following information: - CE Marking; - registered trademark, name and complete address of the Manufacturer; designation of the footwear (= article name and alphanumeric code); nr. and year of the Standard of reference + safety symbols;

- size of the footwear (printed on the outsole);
- production date (month + year);
- additional information: website, category of the PPE, "Made in ...".





PRD Nº 0230 B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2021/05/24 n. **860212108/TE** Validity: 2026/05/23



www.u-power.it

RS20046 UGROUP

04/2021 SABER ESD

EN ISO 20345:2011 S1P SRC

MADE IN TUNISIA

UGROUP SRL Via Borgomanero,50 Paruzzaro (NO)-Italy

DPI II



SECOSOL® COMPLETE 951622012451XX



SECOSOL® LAMINATO CON TESSUTO 9516101XXX7XXX



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements.

The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

