



## EU Type Examination Certificate

Date: 2023/06/05

n. **860232324/OE**

Validity: 2028/06/04

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

|   |   |  |
|---|---|--|
| Manufacturer:<br>(Responsible of the PPE) | <b>U-GROUP SRL</b><br>Via Borgomanero, 50 – 28040 Paruzzaro (NO) – Italia   |  |
| Type of PPE:                              | <b>Safety footwear</b> in conformity with <b>EN ISO 20345:2022 class I</b> (= footwear made from leather and other materials)   |  |
| Category of PPE:                          | <b>II</b> : "medium" risks.<br>This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.  |  |
| Model                                     | <b>"RUSH s ESD"</b><br>code <b>RS20164</b>  |  |
| Description:                              | <p><u>model</u>: A (low- footwear);<br/> <u>fastening system</u>: by means of laces;<br/> <u>processing</u>: direct injection;<br/> <u>outsole</u>: grey 63354 compact PU "7466 360" marked "antistatic oil resistant" (CH00116);<br/> <u>midsole</u>: black foam PU (CH00117) with white polystyrene inserts in the rear area;<br/> <u>upper</u>: black Nabuk Bottalato leather declared thickness 1,8/2,0 mm (PL00066), with black polymeric insert in the heel area, marked "BREATHABLE", with lateral holes closed by means of fabric/membrane;<br/> <u>rear collar</u>: black grey Lycra MOREA (SI00753) padded with black folded Lycra edge (AT01766); the collar has been shaped to create a loop to ease the donning;<br/> <u>tongue</u>: black fabric ALBANY semplice (SI00046), lined and padded;<br/> <u>bellows</u>: black coated synthetic fabric SPICE (SI00002);<br/> <u>vamp lining</u>: grey three-dimensional fishnet knitting coupled with black canvas (SI00743);<br/> <u>quarter lining</u>: grey 599 three-dimensional perforated fishnet knitting SURF (SI00468);<br/> <u>tongue lining</u>: black three-dimensional perforated fishnet knitting SURF (SI00466);<br/> <u>rear collar lining</u>: black three-dimensional perforated fishnet knitting SURF, reversed (SI00466);<br/> <u>heel-grip lining</u>: anthracite grey non-woven fabric THORIN (SI00283);<br/> <u>insole</u>: white multi-layered fabric declared conductive, art. PREMIUM X MXC by LENZI (SP00037) <u>or in alternative</u> white multi-layered fabric declared conductive, art. IBISAFE 37RK36KG2 by BIAGIOLI (SP00038), <u>which also serve as perforation resistant inserts</u>;<br/> <u>removable insock</u>: grey perforated foam material, coupled with black knitting with "U-POWER ORIGINAL" stamp in contact with the user, with double zig-zag stitching with conductive thread in the forepart (TL00190);<br/> <u>toecap</u>: aluminium, art. A522 MARTEK (PU00041).</p> <p>Provided also with optional and interchangeable orthopaedic insocks SECOSOL®, see "Annex 827211301/E".</p> |  |
| Technical Standard:                       | <b>EN ISO 20344:2021</b><br><b>EN ISO 20345:2022</b>  | Personal protective equipment – Test methods for footwear<br>Personal protective equipment – Safety footwear |
| Intended use:                             | general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.   |  |
| Size range:                               | from 35 to 48   |  |





# EU Type Examination Certificate

Date: 2023/06/05

n. **860232324/OE**

Validity: 2028/06/04

Technical File: **DC-16254**

Test report: **RCT n°4251404.01/E**

Functions and performance levels: **basic requirements for safety footwear (SB)** (see Table 2 and 3 of EN ISO 20345:2022): all mandatory ones, among which:

**Slip resistance** = slip resistance on ceramic tile floor with NaLS.

**Additional requirements** (Tab. 16 and 20 of EN ISO 20345:2022):

**S3S** = closed heel area, energy absorption of seat region, antistatic properties, water penetration and absorption, perforation resistance: Type PS, cleated outsole; **CI** = cold insulation of outsole complex; **FO** = resistance to fuel oil; **SR** = slip resistance on ceramic tile floor with glycerine.

Note: the footwear also meets the requirement in accordance with IEC 61340-5-1:2016 (IEC 61340-4-3:2017) for the electrical resistance **ESD** (electric dissipative footwear).

Marking:

on a stitched label and displaying the following information:

- **CE Marking;**
- registered trademark, name and complete address of the Manufacturer;
- designation of the footwear (= article name and alphanumeric code);
- nr. and year of the Standard of reference + safety symbols;
- size of the footwear (printed on the outsole);
- production date (month + year);
- additional information: website, category of the PPE, "Made in ...".

**CE**

**U:Power**  
*Don't worry... be happy!*  
www.u-power.it

**UGROUP**  
**RS20164**

**12/2022**  
**RUSH s ESD**

**EN ISO 20345:2022**  
**S3S CI FO SR**

**MADE IN TUNISIA**

UGROUP SRL  
Via Borgomanero,50  
Paruzzaro (NO)-Italy

**DPI II**

**UK**  
**CA**



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements.

The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

