



WCP365 INSTALLATION INSTRUCTIONS

- UNLOAD AND CLEAR YOUR PISTOL
- REMOVE THE SLIDE ASSEMBLY AND SET IT ASIDE. KEEP YOUR TAKEDOWN LEVER IN THE DOWN POSITION.
- REMOVE THE REAR FRAME PIN FROM LEFT TO RIGHT WITH A SMALL PUNCH.
- LIFT THE CHASSIS STRAIGHT UP FROM THE REAR AT A FORWARD ANGLE OUT OF THE STOCK FRAME.
- INSTALL THE SUPPLIED MAGAZINE CATCH, SPRING, AND LOCK INTO THE WCP365 GRIP MODULE.
- REVERSE THE PROCESS TO INSTALL THE CHASSIS IN TO THE NEW GRIP FRAME.
- AFTER INSTALLATION, ENSURE THAT THE TAKEDOWN LEVER IS UNDER SPRING TENSION AND THE SLIDE SAFETY LEVER ISN'T BLOCKING THE SLIDE, REINSTALL THE SLIDE ASSEMBLY AND MOVE THE TAKEDOWN LEVER INTO THE LOCKED POSITION. ENSURE THAT THE SLIDE LOCK AND TAKEDOWN LEVER HAVE SPRING TENSION.
- ENSURE THAT YOUR PISTOL FUNCTIONS PROPERLY AND YOUR MAGAZINE DROPS CLEANLY AFTER INSTALLATION OF THE NEW GRIP FRAME PRIOR TO USE.