

TECHNICAL DATASHEET

APPLICATIONS	
	U UPHOLSTERY & SHOPFITTING
SURFACE	PVC-compound
BASE	Cotton knitted fabric
DECORATION BY	Foil stamping, blind embossing. Subject to test before using. Please consult us.
TESTS	Fire classification: NF P 92503-7 M1 DIN EN ISO 5470-2: ≥ 300'000 Martindale invers Lightfastness: 7
MIN. QUANTITY SPECIALS	1000 m
PRODUCTION TIME	8-10 weeks
ROLL WIDTH	~137 cm
ROLL LENGTH	~30 m
SHEETS	Not available
NET WEIGHT	~800 gsm
THICKNESS	~1.1 mm
TYPE OF PACKAGING	Pallets: goods horizontal in IPPC wooden frames Single rolls shrink-wrapped
SIZES OF PACKAGING	<30 kg brutto: Individual packages >30 kg brutto: Pallet 160×80 cm
INNER CORE Ø	5.2 mm
GROSS WEIGHT	~34 kg
NET WEIGHT	~33 kg
CUSTOMS DECLARATION	Plates, sheets, film, foil and strip, of cellular polymers of vinyl chloride, unworked or merely surface-worked or merely cut into squares or rectangles (excl. self-adhesive products, floor, wall and ceiling coverings of heading 3918 and sterile surgical or dental adhesion barriers of subheading 3006.10.30)
TARIFF NUMBER	3921.1200 (Switzerland) / 39211200 (EU)
ENVIRONMENTAL DATA	REACH SAME AND A STATE OF THE S

