Toile du Marais

TECHNICAL DATASHEET

APPLICATIONS	BINDING & PREMIUM SHOPPING BAGS STATIONERY PUBLISHING PACKAGING
SURFACE	Dyed woven cloth (Viscose)
BASE	Lining paper (acid free)
DECORATION BY	Foil and blind stamping, silk screen, offset and digital printing. Subject to test before using. Please consult us.
TESTS	Lightfastness: ISO 105-B02 = please consult us for test results Colourfastness to rubbing: ISO 105-X12: dry 4, wet 2 -3 (grey scale) Tensile strength: ISO 13934-1: Warp 380 N, Weft 305 N Elongation: ISO 13934-1: Warp 15.2 %, Weft 8.6 % Tear strength: ISO 13937-2: Warp = 6.3 mN, Weft = 8.8 mN Folding endurance: ISO 5626: > 10'000
MIN. QUANTITY SPECIALS	1500 m
PRODUCTION TIME	3-4 weeks
ROLL WIDTH	~137 cm
ROLL LENGTH	~100 m
SHEETS	On request
NET WEIGHT	~162 gsm, Neige: ~215 gsm
THICKNESS	~0.31 mm, Neige ~0.35 mm
TYPE OF PACKAGING	In plastic sleeves
SIZES OF PACKAGING	~140 × 20 × 20 cm
INNER CORE Ø	5 cm
GROSS WEIGHT	~24 kg
NET WEIGHT	~22 kg
CUSTOMS DECLARATION	Woven textile laminated to paper
TARIFF NUMBER	5901.1000 (Switzerland) / 59011000000 (European Community)
ENVIRONMENTAL DATA	REACH REACH ONLY THE CONTROL OF TH

