



LVT PRODUCT SPECIFICATION

PRODUCT DIMENSIONS	PLANK	HERRINGBONE
Width	192mm	106.7mm
Length	1230mm	553.5mm
Number of panels per pack	12	40
m ² per pack	2.834m ²	2.277m ²
Weight per pack	15.8kg	12.4kg
PRODUCT INFORMATION	PRODUCT SPECIFICATION	EN/ISO REFERENCE
Construction	PVC	ISO 10582
Thickness	3mm	EN ISO 24346
Wear Layer	0.7mm	EN ISO 24340
Wear Layer Treatment	PU	Manufacturer Spec
Thermal Resistance/Tog Rating	0.01m ² K/W / 0.1 TOG	EN 12667
Suitability	Class 23 - Heavy Domestic / Class 33 - Heavy Commercial	EN ISO 10874
Inflammability	Bfl-S1	EN 13501-1
Scratch Resistance	MSR-A1, MSR-B1	EN ISO 16094
Squareness & Straightness	≤ 0.25mm; ≤ 0.50mm	EN ISO 24342
Slip Resistance	DS/R11	EN 13893
Furniture Leg Resistance	No visible damage	EN ISO 16581
Curling	Norm ≤ 2mm, OK	EN 434
Dimensional stability	≤ 0.25%	EN ISO 23999
Formaldehyde Group	E1	EN 717-1
Acoustic Insulation	3dB	EN ISO 717-2
Castor Chair Resistance	No damage to wear layer	ISO 4918
Stain Resistance	OK	EN 423
Light Fastness	Class ≥ 6	EN ISO 105-B02
Underfloor Heating	Suitable, max 27 ° C	EN 1264
Warranty	Lifetime Residential / 20 Year Commercial	Manufacturer Spec