

Mira Select Single Outlet

Mixers Product Category



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

Inclusively designed. Intelligently engineered. Mira Select thermostatic mixer showers feature an ultra-ergonomic and RNIB certified visually optimised design for ultimate accessibility.

Product Information

Description	Colour	Product No.
Mira Select Single Outlet	High Contrast	31998W

Features & Benefits

Temperature control
TMV3 approved product
Thermostatic temperature stability
Maximum temperature setting for increased safety
Easy to fit
Quickly and easily fits onto reversed inlet supplies
Multi-Fit fits over 110-155 mm pipe centres
Suitable for replacement of a previous mixer valve using existing olives, compression nuts and pipe concealing plates
Suitable for rear fed 15 mm compression connections (not suitable for 3/4" Bar valve replacement)
Valve shroud design covers all previous fixing holes and water entry points
Easy to service
Long-life filters and replaceable cartridge
For your customer
Designed in conjunction with the RNIB
Separate flow and temperature control levers for ease of use
Push button on/off
Audible click in response to temperature adjustment
Mira Cool Shield™ technology prevents heat transferring to exposed surface of the shower, meaning Select is always safe to touch



Product Specification

Tech Details

Temperature Control
Control type: Thermostatic
Installation
Water entry points: Rear only
Inlet connections: 15 mm compression
Outlet connections: 1/2" BSP male flat face
Reversed inlets supported. Remove valve body from manifold, rotate then refit.
Supply Conditions (hot and cold)
Cold water range: 5 - 25°C
Hot water range: 55 - 85°C (operating; 60 - 65°C recommended)
Minimum maintained pressure: 0.1 bar (1 metre head)
Maximum maintained pressure: 5 bar (50 metre head)
Maximum static pressure: 10 bar (100 metre head)

Performance
Flow rate at handset: 7.1 L /min at 0.5 bar
Fitted with an 11 L/min flow regulator
Temperature stability: +/- 2°C
Safety Features
Automatic shutdown: Within 2 seconds
Factory set to safe max temp of 41°C
Adjustable maximum temperature for on site conditions

Dimensions

