

Mira Vie

Electric Shower

Consistent, all-year round performance and suitable for any system, it's the ultimate in reliability.



Product Information

Description	Colour	Product No.
Mira Vie 8.5 kW	White/Chrome	1.1788.004
Mira Vie 9.5 kW	White/Chrome	1.1788.005
Mira Vie 10.8 kW	White/Chrome	1.1788.006
Mira Vie 8.5 kW	Chrome	1.1788.512
Mira Vie 9.5 kW	Chrome	1.1788.513
Mira Vie 10.8 kW	Chrome	1.1788.514

Features & Benefits

Temperature control

Pressure stabilised temperature control

Easy to fit

Retrofits onto inlets of most Mira electric showers

Left-hand water and cable entry points

Adjustable slide bar fits over holes left by previous shower kit

Easy to service

Easy filter access

For your customer

Separate power and temperature controls

Push button on/off

Eco setting saves water and energy

Mira Clearscale™ reduces limescale by up to 50%

Single spray showerhead with rub-clean nozzles

Modern aesthetics with chrome detailing



Product Specification

Tech Details

Temperature Control

Control type: Pressure stabilised

Installation

Power options: 8.5 kW 240V AC (7.8 kW 230V AC)

- 9.5 kW 240V AC (8.7 kW 230V AC)
- 10.8 kW 240V AC (9.9 kW 230V AC)

Supply voltage: 230v ± 10%

Supply rating: 40 amp (8.5 & 9.5 kW); 45 amp (10.8 kW)

Terminal Block connections: Maximum 16 mm²

Water entry points: Left (rising, falling & rear)

Cable entry points: Left (rising, falling & rear)

Inlet connections: 15 mm plastic stub, compression or push-fit fittings

Outlet connections: ½" BSP Male

Supply Conditions (hot and cold)

Minimum maintained pressure: 8.5 & 9.5 kW: 0.7 bar (7 metre head);
10.8 kW: 1 bar (10 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Temperature stability: ± 6°C

Safety Features

Phased shutdown: No

Factory set to safe max temp: No

Mira Sensi-flo™: No

Accessories

Wide range of accessories available at www.mirashowers.co.uk

Approvals

Energy Efficiency: Class A

Kiwa certified

WRAS approved (Water Regulations Advisory Scheme)



Dimensions

