



Geberit Duofix element for wall-hung WC, 112 cm, without cistern



CHARACTERISTICS

- 2025 range
- Statically self-supporting frame, protected against corrosion with powder coating
- Frame for wall-hung WCs with connection dimensions as per EN 33 and projection up to 70 cm
- With pull-out plate for lateral fastening above the element on metal or wood profiles or on Geberit Duofix system studs
- Alternative fastening point for wall anchors
- Rotating foot plates, suitable for installation in U profiles UW 50 and UW 75
- Foot plates that can be mounted in Geberit Duofix system rail without tools, without additional components
- Galvanised non-slip leg supports protected against corrosion

- Connection bend can be mounted without tools at different depths, adjustable range 45 mm
- Rotatable connection bend for connection piece for horizontal outlet to the rear
- Fastening for electrical connection and Power & Connect Box

TECHNICAL DATA

Product material	Steel
Height-adjustable	Yes

SCOPE OF DELIVERY

- 2 wall anchors
- Connection set for WC, $\varnothing$ 90 mm
- Connection bend 90° made of PVC, $\varnothing$ 90 / 100 mm

- Fastening and protection material

ACCESSORIES

- Geberit sound insulation set for wall-hung WC
- Geberit Duofix system fastening bracket
- Geberit Duofix fastening material for stud clearance 50–57.5 cm
- Geberit set of support brackets for WC ceramic appliances with small contact surfaces
- Geberit Duofix set of wall anchors for single installation, corner construction
- Geberit Duofix set of wall anchor extensions
- Geberit Duofix set of foot fastener on rear wall
- Geberit drilling template for wall-hung WC and Geberit AquaClean
- Geberit Duofix set of foot extensions 20 cm length

Art. no.	B cm	H cm	T cm
111.321.00.2	50	112	4