

Mira Galena

Electric Shower



Stylish, contemporary designs with the reassurance of thermostatic technology.



Product Information

Description	Colour	Product No.
Mira Galena 9.8kW	Silver Glass	1.1634.082
Mira Galena 9.8kW	Black Flock	1.1634.083
Mira Galena 9.8kW	Light Stone	1.1634.084
Mira Galena 9.8kW	Slate Effect	1.1634.117

Features & Benefits

Temperature control

Thermostatic temperature control

Easy to fit

Retrofits onto inlets of most Mira electric showers

Easy to service

Easy filter access

For your customer

Separate power and temperature controls

Push button on/off, with choice of 3 flow settings

Mira Sensi-flo™ technology helps prevent scalding

Mira Clearscale™ and Dual Element™ technology reduces limescale by up to 50%

Phased shutdown flushes hot water from the tank making it safe for the next user

Includes easily adjustable clamp bracket and handy soap dish

5 spray 11cm showerhead with rub-clean nozzles

Product Specification

Tech Details

Temperature control

Control type: Thermostatic SMA

Installation

Power options: 9.8kW 240V AC (9.0kW 230V AC)

Supply voltage: 230v \pm 10%

Supply rating: 45 amp (9.8kW)

Terminal Block connections: Maximum 16mm²

Water entry points: Left (rising, falling & rear)

Cable entry points: Left (rising, falling & rear)

Inlet connections: Brass inlet connector. 15mm compression fitting

Outlet connections: 1/2" BSP Male

Supply Conditions

Minimum maintained pressure: 0.7 bar (7 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Temperature stability: \pm 2°C

Safety Features

Phased shutdown: Yes

Factory set to safe max temp: Factory set at 48°C

Mira Sensi-flo™: Yes

Accessories

Includes easily adjustable clamp bracket and handy soap dish

Wide range of accessories available at www.mirashowers.co.uk

Approvals

Energy Efficiency: Class A



Dimensions

