






Example image



CHARACTERISTICS

- Water heating via continuous flow heater
- Anal shower with WhirlSpray shower technology
- Separate Lady shower nozzle in protected resting position
- Continuous flow heater can be deactivated
- Spray arm with nozzle can be extended for anal and vaginal area
- Spray intensity can be set to five different levels
- Spray arm can be set to five different positions
- Adjustable oscillating spray (automatic forward and reverse motion of the spray arm)
- Floor-standing
- Automatic pre- and postrinsing of the spray nozzle with fresh water
- Descaling programme
- Rimless WC ceramic appliance featuring Rimfree flush technology
- Washdown WC with special glaze KeraTect
- User detection
- Odour extraction with ceramic honey comb filter can be activated
- Odour extraction unit with run-on function
- Dryer can be activated
- WC seat ring with rapid heating function
- WC seat ring and WC lid with soft-closing mechanism
- WC lid with SoftOpening
- WC lid with quick release

- Functions and settings via remote control
- Three user profiles can be programmed
- Water supply connection on the left, hidden behind the WC ceramic
- Mains connection with flexible three-core sheathed cable, on the right side, hidden behind the WC ceramic
- Floor inlets of 6–28 cm from wall in combination with Geberit Monolith sanitary modules for floor-standing WC possible
- Approval in accordance with (DIN) EN 1717 / (DIN) EN 13077
- Compatible with Geberit Home App
- Shower water temperature can be adjusted via Geberit Home App
- Dryer temperature can be adjusted via Geberit Home App
- Temperature of the WC seat heating can be adjusted via Geberit Home App
- Can be combined with Geberit Monolith sanitary module for floor-standing WC

TECHNICAL DATA

Degree of protection	IPX4
Nominal voltage	230 V AC
Mains frequency	50 Hz
Power consumption in standby mode max.	0.5 W
Flow pressure	0.5–10 bar
Operating temperature	5–40 °C

Water temperature, adjustment range	34–40 °C
Water temperature, factory setting	37 °C
Minimum flow pressure	0.5 bar
Calculated flow rate	0.02 l/s
Spray time	50 s
WC seat load max.	150 kg
Odour extraction unit	Yes
SoftOpening	Yes
With WC seat ring heating	Yes
With orientation light	No
With dryer functionality	Yes

SCOPE OF DELIVERY

- Water supply connection set
- Female socket for mains connection
- Sound insulation set
- Spray shield
- Compensation pad for WC seat / ceramic appliance
- Descaling agent, 125 ml
- Cleaning set
- Connection set for WC, ø 90 mm
- Remote control with wall-mounted holder and battery CR2032
- Fastening material

ACCESSORIES

- Wall-mounted control panel, touchless, for Geberit AquaClean

Art. no.	Colour / surface	B cm	B1 cm	H cm	T cm	Protection class	Power consumption W	QuickRelease-Funktion
146.310.11.1	WC ceramic appliance: white / KeraTect, Design cover: white / glossy	36	36	51.5	56	I	2000	Yes, WC lid only
146.310.FW.1	WC ceramic appliance: white / KeraTect, Design cover: brushed stainless steel	36	36	51.5	56	I	2000	Yes, WC lid only
146.310.SI.1	WC ceramic appliance: white / KeraTect, Design cover: white / glass	36	36	51.5	56	I	2000	Yes, WC lid only
146.310.SJ.1	WC ceramic appliance: white / KeraTect, Design cover: black / glass	36	36	51.5	56	I	2000	Yes, WC lid only

INFO

- This product is supplied with the Geberit AquaClean descaling agent. This consumable contains classified hazardous substances. Information, instructions and measures for handling hazardous substances safely can be found at www.geberit.com.