

# Mira Evoco

## Mixer Shower

Beauty, built-in.  
Contemporary mixer  
shower - designed  
for style, ease of use  
and reliability.



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

### Product Information

Description	Colour	Product No.
Mira Evoco Single Outlet Shower	Chrome	1.1967.051
Mira Evoco Single Outlet Valve Only	Chrome	1.1967.079

### Features & Benefits

#### Temperature control

Thermostatic temperature stability

#### Easy to fit

Mira's innovative installation system, providing a simple first fix solution

Flushing system provided to test connections prior to tiling

Suitable for rear wall installations

#### For your customer

Works on all systems, even at low pressure

Maximum temperature stop for increased safety (with override for a hotter shower)

Mira Cool Shield™ to ensure valve doesn't get hot during showering

One spray 11cm showerhead with rub-clean nozzles

1.25m flexible shower hose



# Product Specification

## Tech Details

### Temperature and flow control

Temperature control type: Thermostatic

Flow actuation: Single sequential cartridge

### Installation

Water entry points: Side only

Inlet connections: Compression fittings

Outlet connections: 15mm copper pipework

Reversed inlets supported: Yes

### Supply Conditions (hot and cold)

Cold water range: 1°C to 25°C

Hot water range: Min 55°C; 60°C - 65°C (recommended)

Minimum maintained pressure (gas water heater) : 1 bar (10 metre head)

Minimum maintained pressure (gravity system) : 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

### Performance

Flow rate (at handset): 9.75 l/min at 0.5 bar

Flow regulator: 6 l/min (supplied with product - x1)

Temperature stability:  $\pm 2^{\circ}\text{C}$

### Safety Features

Automatic shutdown: Shutdown within 2 secs

Factory set to safe maximum temperature

Adjustable maximum temperature for on-site conditions

### Approvals

KIWA UK approved product

WRAS approved (Water Regulations Advisory Scheme)

TMV2 approved product

CE approved product

UKCA approved product



## Dimensions

