

Mira Evoco

Mixer Shower



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

Beauty, built-in.
Contemporary mixer
shower - designed
for style, ease of use
and reliability.

Product Information

Description	Colour	Product No.
Mira Evoco Single Outlet Shower	Chrome	1.1967.051
Mira Evoco Single Outlet Valve Only	Chrome	1.1967.079

Features & Benefits

Temperature control

Thermostatic temperature stability

Easy to fit

Mira's innovative installation system, providing a simple first fix solution

Flushing system provided to test connections prior to tiling

Suitable for rear wall installations

For your customer

Works on all systems, even at low pressure

Maximum temperature stop for increased safety (with override for a hotter shower)

Mira Cool Shield™ to ensure valve doesn't get hot during showering

One spray 11cm showerhead with rub-clean nozzles

1.25m flexible shower hose



mira
SHOWERS

Product Specification

Tech Details

Temperature and flow control
Temperature control type: Thermostatic
Flow actuation: Single sequential cartridge
Installation
Water entry points: Side only
Inlet connections: Compression fittings
Outlet connections: 15mm copper pipework
Reversed inlets supported: Yes
Supply Conditions (hot and cold)
Cold water range: 1°C to 25°C
Hot water range: Min 55°C; 60°C - 65°C (recommended)
Minimum maintained pressure (gas water heater) : 1 bar (10 metre head)
Minimum maintained pressure (gravity system) : 0.1 bar (1 metre head)
Maximum maintained pressure: 5.0 bar (50 metre head)
Maximum static pressure: 10.0 bar (100 metre head)

Performance
Flow rate (at handset): 9.75 l/min at 0.5 bar
Flow regulator: 6 l/min (supplied with product - x1)
Temperature stability: ± 2°C
Safety Features
Automatic shutdown: Shutdown within 2 secs
Factory set to safe maximum temperature
Adjustable maximum temperature for on-site conditions
Approvals
KIWA UK approved product
WRAS approved (Water Regulations Advisory Scheme)
TMV2 approved product
CE approved product
UKCA approved product



Dimensions

