



US009709793B1

(12) **United States Patent**
Seltzer et al.

(10) **Patent No.:** **US 9,709,793 B1**

(45) **Date of Patent:** **Jul. 18, 2017**

(54) **DEPLOYABLE STRUCTURE**

USPC 359/399; 160/84.04
See application file for complete search history.

(71) Applicant: **Ball Aerospace & Technologies Corp.**,
Boulder, CO (US)

(56) **References Cited**

(72) Inventors: **Aaron J. Seltzer**, Boulder, CO (US);
David M Waller, Westminster, CO
(US); **Lawrence J. Campbell**,
Westminster, CO (US); **Ryan T.**
Thompson, Longmont, CO (US);
Dustin S. Putnam, Broomfield, CO
(US); **William D. Tandy**, Boulder, CO
(US)

U.S. PATENT DOCUMENTS

1,483,125 A *	2/1924	Singer	B65D 5/5206 206/45.22
3,397,399 A *	8/1968	Carman	F24J 2/125 135/33.2
4,550,973 A	11/1985	Hufnagel	
4,977,560 A	12/1990	Wantuck	
5,287,218 A	2/1994	Chen	

(Continued)

(73) Assignee: **Ball Aerospace & Technologies Corp.**,
Boulder, CO (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 85 days.

“First Folding Space Telescope Aims to “Break the Glass Ceiling”
of Traditional Designs”, DARPA News, Dec. 5, 2013, printed May
17, 2016 from <http://www.darpa.mil/news-events/2013-12-05>, 4
pages.*

(Continued)

(21) Appl. No.: **14/587,342**

Primary Examiner — Frank Font

(22) Filed: **Dec. 31, 2014**

(74) *Attorney, Agent, or Firm* — Sheridan Ross P.C.

Related U.S. Application Data

(57) **ABSTRACT**

(60) Provisional application No. 61/922,539, filed on Dec.
31, 2013.



A deployable structure having a plurality of panel elements
is provided. Adjacent panel elements are connected to one
another by hinges. The hinges allow the panel elements to be
placed in a stowed or folded configuration, in which adjacent
pairs of panel elements are folded against one another to
provide a relatively compact assembly. Biasing members
can be provided to transition the deployable structure from
the stowed configuration to a deployed configuration. When
in the deployed configuration, the relative positions of the
panel elements of the deployable structure are maintained,
at least in part, by locating interface assemblies. The deploy-
able structure may have a generally annular configuration
when deployed.

(51) **Int. Cl.**
G02B 23/20 (2006.01)
G02B 27/42 (2006.01)
G02B 5/18 (2006.01)

(52) **U.S. Cl.**
CPC **G02B 23/20** (2013.01); **G02B 5/18**
(2013.01); **G02B 27/4205** (2013.01); **G02B**
2005/1804 (2013.01)

(58) **Field of Classification Search**
CPC G02B 23/20; G02B 5/18; G02B 27/4205;
G02B 2005/1804; E06B 3/48; E06B
3/481; E06B 3/5009; E06B 3/5018

19 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,898,529 A * 4/1999 Meyer G02B 23/00
343/781 P
5,973,827 A 10/1999 Chipper
6,114,671 A 9/2000 Wehner et al.
6,134,366 A 10/2000 Loeb et al.
6,353,421 B1 * 3/2002 Lalezari H01Q 1/288
343/881
6,426,834 B1 7/2002 Braunecker et al.
6,487,342 B1 11/2002 Wu et al.
6,505,381 B1 * 1/2003 Thomson B64G 1/222
16/282
6,707,603 B2 3/2004 Ansley et al.
6,888,613 B2 5/2005 Robins et al.
7,557,995 B1 * 7/2009 Lloyd G02B 23/16
359/601
7,672,527 B2 * 3/2010 Arenberg G02B 3/08
359/742
7,730,925 B1 * 6/2010 Pereira E06B 9/262
160/348
8,664,570 B2 3/2014 Odeh
9,100,996 B2 8/2015 Lisinski et al.
2002/0071472 A1 6/2002 Dickson et al.
2002/0158131 A1 10/2002 Dickson et al.
2003/0206338 A1 11/2003 Cook
2004/0195233 A1 10/2004 Gerhardinger et al.

2006/0174930 A1 * 8/2006 Murphy B64G 1/443
136/246
2010/0200777 A1 8/2010 Hauf
2010/0319270 A1 * 12/2010 Slade B64G 1/222
52/71
2010/0321758 A1 12/2010 Bugno et al.
2011/0094093 A1 4/2011 Goldstein et al.
2011/0242663 A1 * 10/2011 Daily G02B 5/005
359/601
2012/0012154 A1 * 1/2012 Keller B64G 1/222
136/245
2013/0021789 A1 1/2013 Dahm
2015/0352881 A1 12/2015 Seils et al.

OTHER PUBLICATIONS

“DARPA developing giant folding space telescope”, Dec. 8, 2013, printed May 17, 2016 from <http://www.gizmag.com/darpa-folding-telescope/30039>, 6 pages.*
Anderson et al. “Photon Sieve Telescope,” Proceedings of SPIE, Jun. 2006, vol. 6265, 626523, 8 pages.
Hansen “Developing Lightweight Optics for Space,” Science & Technology Review, Jan./Feb. 2013, 4 pages.
Meinel et al. “Large membrane space optics: imagery and aberrations of diffractive and holographic achromatized optical elements of high diffraction order,” Optical Engineering, Aug. 2002, vol. 41, No. 8, pp. 1995-2007.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2A







FIG. 2B




STOWED GEOMETRY
FIG.3A




25% DEPLOYED
FIG.3B



50% DEPLOYED
FIG.3C



75% DEPLOYED
FIG.3D



FULLY DEPLOYED
FIG.3E




FIG. 4




FIG. 5




FIG.6




FIG.7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10

1

DEPLOYABLE STRUCTURE**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims the benefit of U.S. Provisional Patent Application Ser. No. 61/922,539, filed Dec. 31, 2013, the entire disclosure of which is hereby incorporated herein by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

This invention was made with Government support under agreement number HR 0011-10-C-0157 awarded by DARPA. The Government has certain rights in the invention.

FIELD

Methods and systems related to a space-based deployable structure are provided.

BACKGROUND

It is often desirable to deploy relatively large structures in space. For example, telescopes, antennas, and other instruments can benefit from including large optical elements. However, such structures must fit within the relatively restricted cargo volume of a launch vehicle.

In order to provide relatively large elements as part of space-based instruments, techniques and structures have been developed that allow such elements to be carried in the launch vehicle in a folded or otherwise compact form. The element is then unfolded or otherwise deployed after that element has been removed from the launch vehicle. With respect to such techniques and structures, it is important to provide an element that can be deployed reliably, and with high precision.

Deployable structures, such as the primary element of telescopes, have been developed that unfold like a Chinese fan. Other systems have been proposed that unfold linearly. Still other proposed designs utilize an origami or umbrella type structure. However, such designs can suffer from relatively imprecise forms and insufficient stability in a deployed state, and insufficient reliability with respect to successful deployment of the structure.

SUMMARY

In accordance with at least some embodiments, a deployable structure has a folded configuration that is relatively compact, for transport to a deployment location. For example, in the folded configuration, the deployable structure can be dimensioned to fit within a standard evolved expendable launch vehicle (EELV) fairing. In a deployed configuration, the deployable structure may comprise an annular structure. In at least some embodiments, the deployable structure is the primary element of a space-based telescope. More particularly, the deployable structure may provide a diffractive optical element. In other embodiments, the deployable structure may provide a refractive or reflective optical element. In accordance with still other embodiments, the deployable structure discussed herein can be utilized to provide a relatively compact structure that can be deployed into a relatively large planar structure with high reliability.

2

The deployable structure includes a number of rigid panel elements or petals. In accordance with embodiments of the present disclosure, any even number of rigid panel elements can be provided. Each of the rigid panel elements is joined to two adjacent rigid panel elements. In particular, at least one hinge interconnects an adjacent pair of panel elements to one another. The hinges allow adjacent panel elements to fold relative to one another in alternating directions to form folded pairs of panel elements when the deployable structure is in the folded configuration.

In the folded configuration, a first hinge interconnecting a first panel element to a second panel element adjacent the first panel element on a first side of the first panel element allows the second panel element to fold in a first direction relative to a plane of the first panel element. A second hinge interconnecting the first panel element to a third panel element adjacent the first panel element on a second side of the first panel element allows the third panel element to fold in a second direction relative to the plane of the first panel element. In accordance with embodiments of the present disclosure, there are at least three folded pairs of panel elements when the deployable structure is in the folded configuration. Accordingly, the deployable structure includes at least six panel elements. In accordance with at least some embodiments of the present disclosure, the number of panel elements is an even number of six or greater. In accordance with further embodiments, the number of pairs of panel elements is evenly divisible by three.

The hinges allow the panel elements to transition from the stowed configuration, in which pairs of panel elements are folded against one another, to the deployed configuration. Biasing members can be incorporated into the hinges and/or can be separately provided to transition the deployable structure to the deployed configuration when the deployable structure is released from the folded configuration. In the deployed configuration, the deployable structure may have an annular form. In addition, locating assemblies maintain the relative position of panel elements when the deployable structure is in the deployed configuration.

In plan view the shape of the individual panel elements can be trapezoidal or approximately trapezoidal. Accordingly, each panel element can have a relatively short side that faces a center point of the annular deployed structure and a relatively long side opposite the short side that defines a portion of the outer circumference of the annular deployed structure. The sides of each panel element are not parallel to another, and each side is joined by a hinge to a side of an adjacent panel element.

Each of the panel elements can include a perimeter frame with first and second side members, an inner end member, and an outer end member. The perimeter frame can function to support one or more optical elements, directly or in connection with a sled assembly or other support structure.

Additional features and advantages of embodiments of the present disclosure will become more readily apparent from the following description, particularly when taken together with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A depicts a deployable structure in accordance with embodiments of the present disclosure in a perspective view in a stowed configuration;

FIG. 1B depicts the deployable structure of FIG. 1A in a perspective view in a deployed configuration;

FIG. 2A depicts the deployable structure of FIG. 1A in plan view in the stowed configuration;

FIG. 2B depicts the deployable structure of FIG. 1A in plan view in the deployed configuration;

FIGS. 3A-3E depict a deployment sequence of the deployable structure of FIG. 1A;

FIG. 4 depicts a pair of panel elements in accordance with embodiments of the present disclosure;

FIG. 5 depicts a backing assembly of a panel element in accordance with embodiments of the present disclosure;

FIG. 6 depicts a sled assembly of a panel element in accordance with embodiments of the present disclosure;

FIG. 7 depicts a deployment hinge in accordance with embodiments of the present disclosure;

FIG. 8 depicts a locating interface in accordance with embodiments of the present disclosure in a closed configuration;

FIGS. 9A and 9B depict locating interfaces in accordance with embodiments of the present disclosure in an open configuration; and

FIG. 10 is a flowchart depicting aspects of a method for providing a deployable structure in accordance with embodiments of the present disclosure.

DETAILED DESCRIPTION

FIGS. 1A and 1B depict a deployable structure **104** in accordance with embodiments of the present disclosure in a perspective view. Specifically, FIG. 1A depicts the deployable structure **104** in a folded or stowed configuration (also referred to herein as folded or stowed structure **106**), and FIG. 1B shows the deployable structure **104** in a deployed configuration (also referred to herein as deployed structure **107**). The deployable structure **104** of FIGS. 1A and 1B is shown in plan view in FIG. 2A in the stowed configuration (i.e., the folded or stowed structure **106** is shown in plan view), and in FIG. 2B in the deployed configuration (i.e. the deployed structure **107** is shown in plan view). The deployable structure **104** includes an even number of petals or panel elements **108**. The panel elements **108** are joined to adjacent panel elements **108** by hinges **112**, such that the panel elements **108** fold relative to one another in alternating directions to form folded pairs **116** of panel elements **108** when the deployable structure **104** is in the folded configuration. More particularly, in the stowed configuration, a first surface **120** of each panel element **108** faces a first surface **120** of a paired panel element **108**, and a second surface **124** of each panel element **108** faces a second surface **124** of an adjacent panel element **108**. In accordance with embodiments of the present disclosure, the number of folded pairs **116** is equal to three or more. In accordance with further embodiments, the number of folded pairs **116** is equal to $3N$, where N is any integer number greater than or equal to one.

The folded structure **106** occupies a volume that generally has the form of a truncated cone. Moreover, in the stowed configuration, the deployable structure **104** features pairs **116** of panel elements **108** that lie in parallel or nearly parallel (i.e., at an angle of less than 10° with respect to one another). In addition, the folded pairs **116** of panel elements **108** can be arranged such that they are symmetric about radius lines that are evenly spaced about a center point of the folded structure **106**. As discussed in greater detail elsewhere herein, the deployable structure **104** can include biasing elements that provide the energy necessary to reliably move the deployable structure **104** from the stowed configuration to the deployed configuration. Accordingly, in order to maintain the deployable structure **104** in the stowed configuration, retention straps or bands **118** (see FIG. 1A) can be provided that connect the outer sides or edges of

adjacent folded pairs **116** of panel elements **108** together, and/or continuous bands that extend around the outer edges of the folded pairs **116** of panel elements **108**.

The deployed structure **107** can have a generally annular form in plan view. Accordingly, the sides of all the panel elements **108** and the hinges **112** generally lie along radii of the deployed structure **107**. In addition, the deployable structure **104** is relatively planar in the deployed configuration, at least as compared to the stowed configuration. In accordance with still other embodiments, the deployed structure **107** may approximate a concave surface when viewed from a first side, and may approximate a convex surface when viewed from a second side opposite the first side.

FIGS. 3A-3E depict a deployment sequence of the deployable structure **104** in a series of perspective views. In a first step (Step A), shown in FIG. 3A, the deployable structure **104** is shown as a folded structure **106**, completely folded. While in the stowed configuration, one or more retention straps or bands **118** can maintain the deployable structure **104** in the stowed configuration. At the moment of deployment, the retention straps or bands **118** can be released, to initiate the deployment sequence. In steps B, C, and D (FIGS. 3B, 3C and 3D), the deployable structure **104** is shown 25%, 50%, and 75% deployed respectively. Finally, in step E (FIG. 3E), the deployable structure **104** is shown as a deployed structure **107**, fully deployed. As can be appreciated from the present disclosure, folded pairs **116** of panel elements comprise two panel elements **108** that, in the folded configuration, are folded closely against (e.g. parallel or almost parallel) one another. Adjacent folded pairs **116** are separated from one another by an angle that is approximately equal to 360 degrees divided by the number of folded pairs **116** included in the deployable structure **104**. In the fully deployed configuration, the angle between panel elements **108** that form a folded pair **116** when in the folded configuration can be the same or close to (e.g. within 10 degrees of) adjacent panel elements belonging to other folded pairs **116**.

FIG. 4 depicts a pair of panel elements **108** in accordance with embodiments of the present disclosure. The panel elements **108** are joined to one another by hinges **112**. The panel elements **108** include a back assembly or perimeter frame **404**. In the illustrated embodiment, the perimeter frame **404** includes first **408** and second **412** side members or edges, an inner end member or edge **416**, and an outer end member or edge **420** (see also FIG. 5). In accordance with at least some embodiments, the first **408** and second **412** side members in each panel element **108** are of equal length. The inner end member **416** is shorter than the outer end member **420**. In the illustrated embodiment, the inner end member **416** and outer end member **420** are depicted as being linear elements that approximate a circular inner aperture and a circular outer diameter of the deployed structure **107**. However, the inner end member **416** can be curved, so as to comprise an arc of a circular inner aperture of the annular deployed structure **107**, and/or the outer end member **420** can be curved to comprise an arc of a circular outer diameter of the annular deployed structure **107**.

In addition, the panel elements **108** can include a sled assembly **424** that is supported by the perimeter frame **404** (see also FIG. 6). The sled assembly **424** includes first **428** and second **432** apertures for receiving first **436** and second **440** optical elements respectively. The optical elements **436**, **440** may, for example, comprise transmissive, diffractive optical elements. As further examples, the optical elements **436**, **440** may comprise refractive optical elements, reflect-

tive optical elements, solar panels, sail panels, an active radio frequency antenna or antennas, a passive radio frequency antenna or antennas, or the like. In addition, although illustrated as circular elements, the optical elements **436**, **440** may comprise trapezoidal elements, or any other shape. In addition, although two optical elements **436**, **440** are shown, a panel element **108** can include any number of such elements.

FIG. 7 illustrates an example hinge **112** in accordance with embodiments of the present disclosure. Adjacent panel elements **108** are connected by one or more hinges **112**, which allows the deployable structure **104** to transition from a folded configuration to a deployed configuration. In addition, some or all of the hinges **112** can incorporate or be associated with a spring or other biasing member **704** that is operative to bias the deployable structure **104** to the deployed configuration. Accordingly, the deployable structure **104** can be “self-powered” with respect to deployment of the structure **104**. In accordance with still further embodiments of the present disclosure, the hinges **112** can incorporate a damper mechanism **708** to control the rate at which the deployable structure **104** transitions from the folded configuration to the deployed configuration. Accordingly, when the deployable structure **104** has reached a deployment location, that structure can automatically place itself in the deployed configuration upon separation from the launch vehicle. Although a hinge **112** in the form of a pivoting mechanism is shown in FIG. 7, other embodiments of the present disclosure can incorporate other types of hinges. For example, a hinge **112** may be a flexure type hinge. As a further example, a hinge **112** may be a flexure type hinge that uses a portion of a flexible membrane provided as part of one or more panel elements **108** as the flexure of a flexure type hinge. In accordance with further embodiments, a hinge **112** in the form of a flexure type hinge can also provide a biasing force. A separate biasing member **704** can therefore be replaced or augmented by a flexure that operates as both a hinge **112** and a biasing member **704**. In accordance with still other embodiments, hinges **112** of different types can be included in the deployable structure **104**.

A locating interface assembly **804** is depicted in FIG. 8. In general, each panel element **108** includes a plurality of locating interface members or assemblies **804**. The locating interface assemblies **804** maintain the relative positions of the panel elements **108** of the deployable structure **104** in the deployed configuration, after the deployment sequence has been completed. More particularly, one or more locating interface assemblies **804** of any one panel element **108** cooperates with one or more locating interface assemblies of adjacent panel elements **108** to maintain a desired relative positioning of the panel elements **108** in the deployed structure **107**. Three or more locating interface assemblies **804** can be provided between adjacent panel elements **108**. In accordance with embodiments of the present disclosure, a locating interface assembly **804** can include at least one of a protruding element **808** and a receiving element **812**. In general, a protruding element **808** of a locating interface assembly **804** associated with a panel element **108** is received by a receiving element **812** of a locating interface **804** assembly of an adjacent panel element **108** when the deployable structure **104** is in the deployed configuration. As examples, a protruding element **808** may be in the form of a hemisphere, and the receiving element **812** can be in the form of a cone or a groove (e.g., a V-groove). In accordance with further embodiments, between any two adjacent panel elements **108**, at least a first one of the locating interface assemblies **804** features a hemispherical protruding element

808 in combination with a conical receiving element **812**, and at least a second one of the locating interface assemblies **804** features a hemispherical protruding element **808** in combination with a grooved receiving element **812**. In accordance with still further embodiments, between any two adjacent panel elements **108**, one locating interface assembly **804** features a hemispherical protruding element **808** in combination with a conical receiving element **812**, and two or more locating interface assemblies **804** feature hemispherical protruding elements **808** in combination with grooved receiving elements **812**.

FIGS. 9A and 9B depict elements **808**, **812** of locating interfaces **804**, and exemplary locations of those portions along a side **408** (or **412**) of a panel element **108**. In particular, the elements **808**, **812** of the locating interfaces **804** can be at or towards the ends **416**, **420** of the panel element **108**. Moreover, the elements **808**, **812** can be formed in the perimeter frame **404** itself, or as part of a plate or other assembly attached to the perimeter frame **404**. In FIG. 9A, a hemispherical protruding element **808** and a conical receiving element **812** are illustrated. In FIG. 9B, a hemispherical protruding element **808** and a grooved receiving element **812** are illustrated. As can be appreciated by one of skill in the art after consideration of the present disclosure, the protruding elements **808** shown in FIGS. 9A and 9B would be received by a receiving element **812** formed on or connected to an adjacent panel element **108**, while the receiving elements **812** would receive a protruding element **808** formed on or connected to the adjacent panel element **108** when the deployable structure **104** is in the deployed configuration.

In accordance with embodiments of the present disclosure, the deployable structure **104** may be biased towards the deployed configuration by a spring or other biasing member **704**. Accordingly, the deployable structure **104** may be configured to automatically transition itself to the deployed configuration when the deployable structure **104** is released from a launch vehicle or launch vehicle component. The energy required to transition deployable structure **104** to the deployed configuration can be provided by springs or other biasing members **704**, for example that are incorporated into the hinges **112**. The biasing members **704** can continue to provide a biasing force that, in combination with the locating members or interfaces **804**, maintains the deployable structure **104** in the deployed configuration. Moreover, the deployed configuration can be maintained with high precision by the biasing members **704**, the hinges **112**, and the cooperating locating members **804**. Alternatively or in addition, locating members **804** can be provided that lock the deployable structure **104** in the deployed configuration. The disclosed folded configuration, with at least three folded pairs of panel elements **108**, in combination with the biasing force and at least three locating members **804** between adjacent panel elements **108**, allows the deployable structure **104** to be deployed and maintained in the deployed configuration with high reliability.

With reference now to FIG. 10, aspects of a method for providing a deployable structure **104** in accordance with embodiments of the present disclosure are depicted. Initially, a plurality of panel elements **108** are provided (step **1004**). As discussed elsewhere herein, the panel elements **108** may be trapezoidal, with non-parallel side members or edges. Next, a plurality of pairs **116** of panel elements **108** are formed by hinging a first side edge **408** of a first panel element **108** to a second side edge **412** of a second panel element **108** (step **1008**). The hinges **112** allow the first and second panel elements **108** within each pair **116** to fold

relative to one another, such that a first surface **120** of each of the panel elements **108** within each pair **116** face one another. The panel elements **108** within each pair **116** can be biased towards the deployed position. At step **1012**, adjacent pairs **116** of panel elements **108** are connected to one another by hinges **112**. When this step is complete, the panel elements **108** will be connected in a continuous ring or annular structure. The hinges **112** connecting adjacent pairs **116** of panel elements **108** to one another operate so as to allow a second surface **124** of a first panel element **108** of a first pair **116** to face a second surface **124** of a second panel element **108** of a second pair **116**. Moreover, the panel elements **108** in adjacent pairs can be biased towards the deployed configuration by springs or other biasing members **704** provided as part of the hinges **112**, and/or as separate biasing members **704**.

At step **1016**, pairs **116** of panel elements **108** are folded flat, against the biasing force, such that the first surfaces **120** of the panel elements **108** within each pair **116** face one another. In accordance with at least some embodiments, the panel elements **104** within each pair **116** can be folded so that the first surfaces **120** are in parallel planes. In accordance with other embodiments, the panel elements **108** may be folded so that the first surfaces **120** are within nearly parallel planes (e.g., within about 10° of one another). As can be appreciated by one of skill in the art after consideration of the present disclosure, folding the panel elements **108** within each pair **116** against one another will have the effect of drawing up the deployable structure **104**, such that the maximum diameter of the deployable structure **104** is reduced as compared to the maximum diameter in the deployed configuration. Moreover, folding the deployable structure **104** will result in panel elements **108** in adjacent pairs **116** being folded towards one another. Thus folded, the deployable structure **104** is in a stowed configuration (i.e. is in the form of the folded structure **106**). In accordance with embodiments of the present disclosure, the second surfaces **124** of adjacent panel elements **108** of adjacent pairs **116** lie in planes that intersect one another at a first angle, where the first angle is greater than zero. In accordance with still further embodiments, the angle of intersection of planes corresponding to the second surfaces **124** of adjacent panel elements **108** of adjacent pairs **116** is 10° or greater. Thus configured, the deployable structure **104** is secured in the stowed configuration by one or more bands or restraints **118** (step **1020**).

The folded structure **106** can then be placed into the vehicle that will be used to transport the deployable structure **104** to a desired location (step **1024**). For example, the deployable structure **104** may be placed within the fairing of a launch or other transport vehicle. The deployable structure **104**, in the stowed configuration, can then be transported to the desired location (step **1028**).

After the deployable structure **104** has been brought to the desired location, the deployable structure **104** can be removed from the vehicle (step **1032**). The restraints **118** can then be released, allowing the biasing member **704** to place the deployable structure **104** in the deployed configuration (step **1036**). In the deployed configuration, the locating interface assemblies **804** in cooperation with the biasing members **704**, maintain adjacent panel elements **108** in a desired location relative to one another. The deployable structure **104** is then operational, and thus the telescope or other assembly or instrument of which the deployable structure **104** is a part can be operated (step **1040**).

In an exemplary embodiment, the deployable structure **104** comprises a diffractive primary optical element of a

space-deployed telescope. However, embodiments of the present disclosure are not so limited. In particular, a deployable structure **104** can be used to provide a precisely configured, planar or nearly planar component that can be transported to a deployment location in a relatively compact, folded configuration, and that can be deployed with high reliability, using a self-powered mechanism.

The foregoing discussion of the invention has been presented for purposes of illustration and description. Further, the description is not intended to limit the invention to the form disclosed herein. Consequently, variations and modifications commensurate with the above teachings, within the skill or knowledge of the relevant art, are within the scope of the present invention. The embodiments described hereinabove are further intended to explain the best mode presently known of practicing the invention and to enable others skilled in the art to utilize the invention in such or in other embodiments and with various modifications required by the particular application or use of the invention. It is intended that the appended claims be construed to include alternative embodiments to the extent permitted by the prior art.

What is claimed is:

1. A deployable structure, comprising:

- a plurality of panel elements, wherein each of the panel elements includes a perimeter having a first side edge and a second side edge, wherein the first side edge of a first panel element is not parallel to the second side edge of the first panel element, and wherein a total number of panel elements included in the plurality of panel elements is an even number; and
- a plurality of hinges, wherein at least a first hinge interconnects adjacent panel elements within a pair of panel elements of the plurality of panel elements to one another such that first surfaces of the panel elements within the pair can be folded towards one another, and wherein at least a second hinge interconnects adjacent panel elements in adjacent pairs of panel elements to one another such that second surfaces of the panel elements in the adjacent pairs can be folded towards one another; and
- a plurality of biasing members, wherein the biasing members bias the deployable structure towards a deployed configuration, and wherein the deployed configuration is planar.

2. The deployable structure of claim 1, wherein a number of pairs of panel elements included in the deployable structure is equal to a multiple of three.

3. The deployable structure of claim 1, wherein the biasing members are springs, and wherein at least some of the hinges are pivoting mechanisms.

4. The deployable structure of claim 1, wherein the deployed configuration of the deployable structure is approximately annular.

5. The deployable structure of claim 1, further comprising:

- a plurality of locating interface assemblies, wherein at least three locating interfaces are located between adjacent panel elements.

6. A deployable structure, comprising:

- a plurality of panel elements, wherein each of the panel elements includes a perimeter having a first side edge and a second side edge, wherein the first side edge of a first panel element is not parallel to the second side edge of the first panel element, and wherein a total number of panel elements included in the plurality of panel elements is an even number; and

a plurality of hinges, wherein at least a first hinge interconnects adjacent panel elements within a pair of panel elements of the plurality of panel elements to one another such that first surfaces of the panel elements within the pair can be folded towards one another, and wherein at least a second hinge interconnects adjacent panel elements in adjacent pairs of panel elements to one another such that second surfaces of the panel elements in the adjacent pairs can be folded towards one another;

a plurality of biasing members, wherein the biasing members bias the deployable structure towards a deployed configuration; and

a plurality of locating interface assemblies, wherein at least three locating interfaces are located between adjacent panel elements, each locating interface including at least one of:

- a protruding member; and
- a receiving member.

7. The deployable structure of claim 6, wherein a protruding member of a first locating interface assembly associated with a first panel element and a receiving member of a second locating interface assembly associated with a second panel element are in contact with one another when the deployable structure is in the deployed configuration.

8. A deployable structure, comprising:

- a plurality of panel elements, wherein each of the panel elements includes a perimeter having a first side edge and a second side edge, wherein the first side edge of a first panel element is not parallel to the second side edge of the first panel element, and wherein a total number of panel elements included in the plurality of panel elements is an even number; and
- a plurality of hinges, wherein at least a first hinge interconnects adjacent panel elements within a pair of panel elements of the plurality of panel elements to one another such that first surfaces of the panel elements within the pair can be folded towards one another, wherein at least a second hinge interconnects adjacent panel elements in adjacent pairs of panel elements to one another such that second surfaces of the panel elements in the adjacent pairs can be folded towards one another, wherein each of the panel elements includes at least one optical element, and wherein the at least one optical element is a transmissive diffractive optical element.

9. The deployable structure of claim 8, wherein the deployable structure is a primary optical element of a space-deployed telescope.

10. A deployable structure, comprising:

- a plurality of panel elements, wherein each panel element in the plurality of panel elements includes first and second side edges, an inner edge, an outer edge, and first and second surfaces, wherein each of the panel elements is planar, and wherein the plurality of panel elements includes an even number of panel elements;
- a plurality of hinges, wherein the first side edge of each panel element is interconnected by at least one of the hinges to the second side edge of an adjacent panel element, wherein for each of the panel elements the at least one hinge on the first side edge allows the adjacent panel element to pivot towards first surface of the panel

element, and wherein for each of the panel elements the at least one hinge on the second side edge allows the other adjacent panel element to pivot towards the second surface of the panel element.

11. The deployable structure of claim 10, wherein a deployed configuration of the deployable structure is approximately annular.

12. The deployable structure of claim 10, wherein the deployable structure is movable from a stowed configuration to a deployed configuration.

13. The deployable structure of claim 12, further comprising:

- a plurality of biasing members, wherein the deployable structure is biased towards the deployed configuration by the biasing members.

14. The deployable structure of claim 13, wherein the deployable structure has a form of a truncated cone in the stowed configuration, wherein the deployable structure has an annular form in the deployed configuration, and wherein each of the hinges is located along a radius of the truncated cone with the deployable structure in the stowed configuration and along a radius of the annular form in the deployed configuration.

15. A method for providing a deployable structure, comprising:

- joining side edges of a plurality of panel elements to one another by hinges, wherein each panel element includes a first side edge, a second side edge, an inner edge, and an outer edge, wherein the first side edge of each panel element is interconnected to the second side edge of an adjacent panel element by at least one of the hinges;
- biasing the panel elements towards a deployed configuration in which the deployable structure has an annular form, and in which the hinges lie along radii of the deployable structure in the deployed configuration, wherein the inner side edges of each of the panel elements define an aperture of the annular form, and wherein the outer side edges of each of the panel elements forms an outer perimeter of the annular form.

16. The method of claim 15, further comprising:

- folding the panel elements in pairs, such that a first surface of each panel element faces a first surface of a paired panel element, and such that a second surface of each panel element faces a second surface of a panel element in an adjacent pair of panel elements, whereby the deployable structure is placed in a stowed configuration;
- securing the deployable structure in the stowed configuration.

17. The method of claim 16, further comprising:

- transporting the deployable structure to a deployment location while the deployable structure is in the stowed configuration.

18. The method of claim 17, further comprising:

- releasing the deployable structure from the stowed configuration, wherein the panel elements are allowed to move into the deployed configuration.

19. The method of claim 16, wherein in the stored configuration the deployable structure has a form of a truncated cone.

* * * * *