

磁性鑽臺 (電鑽另購)

規格 Specifications

型式 Type	穿孔徑 Dia of drilling	電源 Power source Voltage(V) Power	最大深度 Max depth	回轉度 Turning angle	前後移動 Shift for ward & back ward	磁石寸法 Magnet	最大磁力 Magnet holding power	高度 Height	淨重 N.W.
TC-3	2-10 ϕ mm	110/220v 78w	90mm			100 \times 130mm	450	280mm	8kg
TC-6S	2-20 ϕ mm	110/220v 78w	200mm	330 $^{\circ}$	20mm	180 \times 105mm	1200	400mm	18.5kg
TC-6R	2-20 ϕ mm	110/220v 78w	200mm	330 $^{\circ}$	20mm	ϕ 150mm	1200	400mm	18.5kg
TC-10R	2-25 ϕ mm	110/220v 78w	220mm	330 $^{\circ}$	20mm	ϕ 160mm	2100	530mm	25kg
TC-10S	2-25 ϕ mm	110/220v 78w	220mm	330 $^{\circ}$	20mm	105 \times 220mm	2100	530mm	26kg
TC-12W	2-32 ϕ mm	110/220v 78w	280mm	50 $^{\circ}$	20mm	135 \times 260mm	2800	530mm	37kg
TC-12S	2-32 ϕ mm	110/220v 78w	280mm	330 $^{\circ}$	20mm	135 \times 260mm	2800	530mm	33kg



TC-3

可裝6010N 3/8" 電鑽



TC-6R

可裝TOSHIBA
DR-13B 1/2" 電鑽
DR-20S1 3/4" 電鑽
或TC-20 3/4" 電鑽



TC-6S

可裝TOSHIBA
DR-13B 1/2" 電鑽
DR-20S1 3/4" 電鑽
或TC-20 3/4" 電鑽



TC-10R

可裝TC-25 1" 電鑽
或TC-20 3/4" 電鑽



TC-12W

可裝TC-32 1 1/4" 電鑽
或TC-25 1" 電鑽



TC-12S

可裝TC-32 1 1/4" 電鑽
或TC-25 1" 電鑽



TC-10S

可裝TC-25 1" 電鑽
或TC-20 3/4" 電鑽