

Single Colour Flexible LED User Data



Product Code:

MF-SP-XX

(R,G,B,A,W)

1 Channel

4.8W/M

24V CV

SMD3528
60LED/M

IP20
Ingress Protection

5000 x 8 x 2.15mm
(L) x (W) x (D)

100mm
Cutting Points

-10°C / +40°C
Operating Temp

Cooling System:
Convection



Product Code:

MF-HP-XX

(R,G,B,A,W)

1 Channel

14.4W/M

24V CV

SMD5050
60LED/M

IP20
Ingress Protection

5000 x 12 x 2.15mm
(L) x (W) x (D)

100mm
Cutting Points

-10°C / +40°C
Operating Temp

Cooling System:
Convection



Single Colour Flexible LED User Data

More Options



IP67 Silicon Sleeve



Wider Range of LED Available To Order

Product Code Suffix:
XX-HP-XX-IP

5000 x 14 x 4mm
(L) x (W) x (D)

Compatible DMX Drivers



Product Code:
QD-75
SP/HP

Powers
15M / 5M

LED Outputs
2

Max per Output
-

DMX Channels
1 - 8



Product Code:
QD-150
SP/HP

Powers
30M / 10M

LED Outputs
2

Max per Output
15M / 5M

DMX Channels
1 - 8



Product Code:
QD-320
SP/HP

Powers
60M / 20M

LED Outputs
4

Max per Output
15M / 5M

DMX Channels
1 - 16



Product Code:
QD-640
SP/HP

Powers
120M / 40M

LED Outputs
8


Max per Output
15M / 5M

DMX Channels
1 - 32




Single Colour Flexible LED User Data


IP20 Dimensions



IP67 Dimensions



Single Colour Flexible LED User Data



WARNING! Example diagram only. Please read this section carefully before any installation work is carried out. All work should be carried out as per our instructions. Failure to do so may void any warranty. These instructions are to be used in addition to the Driver manuals.

IMPORTANT

All work involving electrical components should be carried out by a competent qualified electrical professional in accordance to IET BS 7671 and any local by-laws.

Installation instructions are for the installation of this product with the manufacturer's compatible recommended DMX drivers.

All mains power **MUST** be turned off before starting installation or maintenance; and **MUST** remain off for the duration of installation or maintenance.

Equipment may become hot to the touch when used for periods of time. Ensure equipment is off and cooled before carrying out maintenance.

The total combined wattage of any colour change flexible LED connected to any single 'LED' output of DMX driver **MUST NOT EXCEED 75W** or **MUST NOT EXCEED** the PSU's power rating.

Any continuous lengths of LED exceeding 5M **MUST** be powered from both ends, as per wiring diagram.

TESTING

You should test each length of LED in isolation before continuing installation.

1. Disconnect the Driver from mains power.
2. Connect length of LED to the 'LED' socket of the Driver or switchable PSU in isolation.
3. Power up the Driver.
4. DMX Drive: Press 'ENT' until you select channel that the length of LED is wired into.
5. Repeat steps 1 to 4, for each length of LED.

If each length lights up you can continue with your installation.

If a length does not light up please contact us for help. Do not continue your installation.

INSTALLATION

Ensure you have carried out the testing before installation.

1. Cut or solder LED to desired length using the designated cutting and soldering points.
2. Disconnect the Driver from mains power.
3. Connect LED to LED socket, ensuring that the colours are connected to the correct poles.
4. Additional lengths can be connected to the same LED output in parallel, ensuring you do not exceed the PSU's rated power.
5. Repeat steps 1 - 4 for each length of LED.

Wiring		
Pin	Function	Wire
1/2/3/4	GND -	Black
5	24V	Red



Tel: +44 (0) 116 278 8078
 Email: sales@abstractavr.com
 Website: www.abstractavr.com

User Data - Wiring
 Date: 01/11/2016
 Page 4/4