

## Specifications

### STANDARD CONSTRUCTION

- Bulkhead ..... 14 gauge galvanized
- Bumper..... 12 gauge galvanized
- Compartment Bottoms ..... 16 gauge galvanized
- Compartment Tops ..... 14 gauge galvanized
- Crossmember-front ..... 7 gauge formed
- Crossmember-intermediate 12 gauge formed
- Crossmember-rear..... 7 gauge formed
- Doors..... 20 gauge galvanized outer panel with 14 gauge galvanized inner panel
- End panels-front..... 16 gauge galvanized
- End panels-rear ..... 16 gauge galvanized with rivet-on thermo-plastic olefin end cap
- Fender panels ..... 16 gauge galvanized with rivet-on composite fender flare
- Floor ..... 12 gauge treadplate
- Intermediate panels ..... 16 gauge galvanized
- Loadspace inside centers ... 14 gauge galvanized (one piece with compartment tops)
- Longitudinals..... 11 gauge formed
- Shelving ..... 16 gauge high-spangle galvanized (250# capacity)
- Tailgate ..... 16 gauge galvanized (double panel, formed construction)
- A-40 galvanized construction. Two-sided zinc coated galvanized (.40 oz zinc coating per square foot of steel) provides maximum rust and corrosion resistance.
- Body construction is welded with front end panels and rear end panels welded at the top One-piece construction compartment tops and inside centers.
- Flush outside body surfaces with unexposed edges for rust resistance.



### STANDARD FEATURES / EQUIPMENT

- Body mounting kit (bodies have universal understructures).
- Contoured body sides complement the chassis styling.
- Galvanized bumper is recessed, features non-skid step and hitch plate, and houses clearance lights, ID lights, license plate and license plate light.
- Vinyl coated aircraft cables on horizontal doors.
- Door hinges are concealed to complement chassis styling and add security.
- Flush-mounted doors do not allow metal-to-metal contact when closed.
- Clip-on door seal (factory installed) allows easy removal for painting, replacement and quicker installation. Door seals against a flat surface for extra protection against water leakage.
- Drip rail runs the full length of the body and provides extra protection against water leakage.
- Fuel fill door is automotive style.
- Cutout in intermediate panel between horizontal and rear vertical compartments provides extended storage from the horizontal compartment in the rear vertical compartment.
- Lights include combination stop, tail and back up and complement the chassis styling.
- Lock cylinders are keyed alike with double-bitted keys.
- Primer is a high grade automotive type. Bodies are cleaned with a high-temperature, high-pressure chemical solution prior to prime painting.
- Rotary door latches with stainless steel paddle handles and galvanized steel pans. Latches are removable for ease of repair or replacement.
- Striker is adjustable, bolt-on.
- Tailgate (two point slam-locking) features locking rotary latch, anti-rack/rattle hardware, and vinyl coated cables to protect against paint damage.
- Spring loaded vertical door holders (double spring to hold door in open and closed positions).

- **STAHL**'s exclusive 5-year "No Rust, No Bust" warranty.

## STANDARD SHELVING PACKAGE

COMPARTMENT	BODY SIZE	COMPT. WIDTH	CURBSIDE	STREETSIDE
Front vertical	101" 112" 136"	29 13/16" 33 13/16" 33 13/16"	1 Adjustable material tray with adjustable dividers and 1 adjustable shelf	1 Adjustable material tray with adjustable dividers and 1 adjustable shelf
Second vertical	136"	23 15/16"	1 Adjustable material tray with adjustable dividers and 1 adjustable shelf	1 Adjustable material tray with adjustable dividers and 1 adjustable shelf
Horizontal	ALL	46 3/16"	1 Adjustable material tray with dividers	Open
Rear vertical	101" 112" 136"	20 15/16" 27 15/16" 27 15/16"	1 Adjustable material tray with adjustable dividers and shuttle cutout from horizontal to rear vertical	1 Adjustable material tray with adjustable dividers and shuttle cutout from horizontal to rear vertical

## DIMENSIONAL SPECIFICATIONS

### Standard Height Models

DESCRIPTION	G101	GD101	G112S	G112	G112	G136	G136
Floor width	48 1/2"	52 1/2"	48 1/2"	52 1/2"	48 1/2"	52 1/2"	48 1/2"
Cab-to-axle	56"	56"	60"	60"	60"	84"	84"
Body length (overall)	103 1/2"	103 1/2"	114 1/4"	114 1/4"	114 1/4"	138 1/4"	138 1/4"
Body length (inside bed)	101 1/2"	101 1/2"	112 1/2"	112 1/2"	112 1/2"	136 1/4"	136 1/4"
First vertical width	29 13/16"	29 13/16"	33 13/16"	33 13/16"	33 13/16"	33 13/16"	33 13/16"
Clear door opening	23 1/2"	23 1/2"	27 1/2"	27 1/2"	27 1/2"	27 1/2"	27 1/2"
Second vertical width	n/a	n/a	n/a	n/a	n/a	23 15/16"	23 15/16"
Clear door opening	n/a	n/a	n/a	n/a	n/a	18 7/8"	18 7/8"
Horizontal width	46 3/16"	46 3/16"	46 3/16"	46 3/16"	46 3/16"	46 3/16"	46 3/16"
Clear door opening	44"	44"	44"	44"	44"	44"	44"
Rear vertical width	20 15/16"	20 15/16"	27 15/16"	27 15/16"	27 15/16"	27 15/16"	27 15/16"
Clear door opening	16 1/2"	16 1/2"	23 1/2"	23 1/2"	23 1/2"	23 1/2"	23 1/2"
Overall body width	79 3/4"	95 3/4"	79 3/4"	95 3/4"	91 3/4"	95 3/4"	91 3/4"
Compartment depth	15 3/4"	21 3/4"	15 3/4"	21 3/4"	21 3/4"	21 3/4"	21 3/4"
Vertical compartment height	40"	40"	40"	40"	40"	40"	40"
Clear door opening	33"	33"	33"	33"	33"	33"	33"
Horizontal compartment height	19 3/16"	19 3/16"	19 3/16"	19 3/16"	19 3/16"	19 3/16"	19 3/16"
Clear door opening	12 1/2"	12 1/2"	12 1/2"	12 1/2"	12 1/2"	12 1/2"	12 1/2"
Floor-to-compartment top height	26"	26"	26"	26"	26"	26"	26"
Tailgate height above floor	13 3/4"	13 3/4"	13 3/4"	13 3/4"	13 3/4"	13 3/4"	13 3/4"

### OPTIONAL EQUIPMENT

- Bar Lock
- Bumper with Factory Installed Receiver Hitch
- Crane Reinforcement
- Compartment Lights
- Drawer Packages
- Hook
- Ladder Rack
- Light Kit
- Louver
- Low Sliding Roof
- Mounting Kit
- Off-Road Mounting Kit
- Paint and Installation
- Pull-Out Tray
- Rope Rail
- Shelf
- Thru Shelf
- Tie-Down Ring
- Tire Carrier
- Transverse Compartment
- Tray
- Treadplate Overlay



Due to constant product evaluations and improvements, specifications and options are subject to change without notice.