



# Insert Dump Bed



**Add productivity and profit to every load**



\*8' models only

The Payload™ Insert Dump Bed is the quickest and easiest way to improve your bottom line and hauling productivity for your ¾ ton+ pick-up truck. By adding a Meyer Payload, it quickly converts your standard pick-up bed into a high performance dump truck, making it easy to haul stone, mulch, dirt, firewood or any material that needs to be moved from place to place. It installs in minutes and features a double acting tailgate to make unloading a breeze. Dump beds are available in carbon steel or stainless steel and feature twin 3½" lifting cylinders\* to take on the heavy lifting. And when the work is done, you can easily remove the Payload from your vehicle and know it's there whenever you need it.



\*7500 lb units only

# Meyer® Insert Dump Bed



## Twin Lifting Cylinders\*

Provide maximum lift capability, while improved stability reduces the stress on the hoses and hydraulics. Competitive models typically feature one cylinder designs that twist and break during heavy usage.

\*7500 lb units only



## Single Piece Sides and Underbody Supports

Self locating underbody supports increase safety during maintenance and servicing operations.



## Monarch power unit with cabled control

Operated with a tethered controller.

## General Specifications

	<b>PART #</b> 63917 (carbon steel) 63918 (stainless steel)	<b>PART #</b> 63915 (carbon steel) 63916 (stainless steel) 63936 (stainless steel HD)
Pick-up Bed Size	short bed	long bed
Dump Bed Length	6' 6"	8' 0"
Capacity	1.5 cu yds	2.24 cu yds
Lifting Capacity	4000 lbs	7500 lbs
Cycle Time	40 seconds to dump at full capacity	45 seconds to dump at full capacity
Power	12V DC	12V DC
Floor Size (LxW)	75.5" x 48"	93.5" x 48"
Weight (empty)	650 lbs	750 lbs
Dump Angle	47 degrees	
Tailgate	Double Acting	
Material Construction	12 ga carbon / 14 ga SS	12 ga carbon / 14 ga SS / 12 ga SS
Cylinders	Single 3½" bore and 2500 psi working pressure	Twin 3½" bore and 2500 psi working pressure
Hoist	Scissor Lift	
Hydraulic Hoses	SAE 100 R2 3,500 PSI working pressure and 14,000 PSI burst pressure	
Pump	12 V Monarch® Electro Hydraulic	
Paint	Powder coated black**	

SS = Stainless Steel \*\* Carbon Steel Models Only

## Features & Benefits

### Performance Advantage

- Converts a standard ¾ ton+ pick-up truck to a dump body
- 4000 to 7500 lb lifting capacity\*
- Grease fittings for 13 pivot points
- Tethered control box (9' cord)
- Double acting tailgate for metered control of material
- Battery and pump shield for added protection
- Six stake pockets for added capacity
- Models available in carbon steel, stainless steel and heavy-duty stainless steel
- Standard bolt-on cab shield
- Standard vehicle harness kit

\* Weight limits not to exceed manufacturer's gross vehicle weight limits. Some photos shown with optional equipment.



### DOUBLE ACTING TAILGATE FOR ADDED VERSATILITY

Provides the needed flexibility for controlling material flow during dumping operations.



### BATTERY AND PUMP SHIELD FOR ADDED PROTECTION

**Meyer**  
Experience *The Difference!*

Meyer Products LLC reserves the right under its continuing product improvement program to change construction or design details and specifications without incurring any obligation.