



# RGL SERIES

## HEAVY DUTY RAIL GATE

2,000 lb., 3,000 lb., 4,000 lb.,  
5,000 lb., and 6,600 lb. Capacities

**Large, Level-Ride,  
Low-Profile Platforms**



### STANDARD RGL SERIES ADVANTAGES INCLUDE:

- Power up / gravity down hydraulic system
- Platform opens and closes hydraulically with no cam mechanisms to wear or become misaligned
- Frame rail constructed of rugged 3/8" steel
- Rigid steel linkage on sides of 2-piece platform provides greater load stability
- External slide bearing simplifies maintenance and eliminates hard to access internal rollers
- Coated galvanized cable assemblies
- All wiring and connections meet or exceed all TMC recommended practices

### OTHER STANDARD FEATURES:

- Weather-protective power unit enclosure
- Reduced Maintenance™ features including: self-lubricating, fiberglass-reinforced bearings at key pivot points
- Charge line circuit protection
- 12" Fixed Ramp standard on most 2-piece platform models
- Super Duty Motor
- Powder coat finish on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion

### SLIMLINE LEVEL RIDE (Standard)



**Platform remains level from vehicle bed to the ground.**

**Increase productivity with simplified handling of bulky, wheeled and palletized loads.**



**RGL Series Gate in stowed position**

Products shown may feature optional equipment.  
Content subject to change without notice.

# WALTCO



### SPECIFICATIONS

Bed Ht: 36"- 60" for (non-dock loading)  
Bed Ht: 46"- 60" for dock loading)

MODEL	CAPACITY	PLATFORM	RAMP
RGL-20	2,000 lbs.	36" x 90"	6"
RGL-20	2,000 lbs.	42" x 90"	6"
RGL-20	2,000 lbs.	48" x 90"	16"
RGL-30	3,000 lbs.	36" x 90"	6"
RGL-30	3,000 lbs.	42" x 90"	6"
RGL-30	3,000 lbs.	48" x 90"	16"
RGL-30	3,000 lbs.	60" x 90"	12"
RGL-30	3,000 lbs.	72" x 90"	12"
RGL-40	4,000 lbs.	42" x 90"	6"
RGL-40	4,000 lbs.	48" x 90"	16"
RGL-40	4,000 lbs.	60" x 90"	12"
RGL-40	4,000 lbs.	72" x 90"	12"
RGL-50 †	5,000 lbs.	60" x 90"	12"
RGL-50 †	5,000 lbs.	72" x 90"	12"
RGL-50 †	5,000 lbs.	84" x 90"	16"
RGL-60 †	6,000 lbs.	60" x 90"	12"
RGL-60 †	6,000 lbs.	72" x 90"	12"
RGL-60 †	6,000 lbs.	84" x 90"	16"

Note: 42"- 48" deep platforms require a minimum 52" bed height for dock loading

† Requires Rail Extension Kit

### OPTIONAL EQUIPMENT:

- 102" Wide Vehicle Option (increases steel platform widths to 96")
- Foot-Activated Cart Stops (available only on models with 12" fixed ramps)
- 16" Aluminum Retention Ramp with 90° lock reduces ground-to-platform incline and acts as a load retention device
- Auxiliary Pump & Motor Unit with Pendant Control: Industry's only backup power system complete with secondary control switches
- Bottom Stops allow operator to lower the folded platform into a pre-set dock loading position
- (†) Rail Extension Kit required for RGL-50, RGL-60 on bed heights greater than 53"
- Auxiliary Battery Power Kits for either straight truck or trailer applications
- Cycle Counter
- Customized Options – contact factory