



RBGL SERIES

BOTTLED GAS GATE

3,000 lb. and 4,000 lb. Capacities

**The Efficient, Affordable
Solution for Managing
Bottled Gas Deliveries**

Products shown may feature optional equipment.
Content subject to change without notice.



STANDARD RBGL SERIES ADVANTAGES INCLUDE:

- Thermally protected power unit safeguards liftgate motor from damage due to heat build-up
- Reduced maintenance features include:
 - Self-lubricating, fiberglass reinforced Teflon™ coated bearings in place of grease zerks
 - Hardened pins that reduce deflection and prolong bearing life
- Coated Valley® lift cables are tested and rated for exceptional performance and long service life
- Hydraulically powered open/close feature makes liftgate operation faster and easier by eliminating the need for manual folding

OTHER STANDARD FEATURES:

- Wide 90-inch liftgate platform for large loads
- Weather-resistant power unit enclosure protects liftgate power unit from corrosion and environmental damage
- Super Duty Motor
- Powder coat finish on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion

Efficient solution to managing oversized bottled gas loads, on or off dock with ease.



RBGL Series Gate in stowed position

RBGL SERIES

BOTTLED GAS GATE



SPECIFICATIONS

Bed Ht: 36"- 60" for (non-dock loading)
Bed Ht: 50"- 60" for (dock loading)

MODEL	CAPACITY	PLATFORM	FOLDING RAMP
RBGL-30	3,000 lbs.	36" x 90"	45" x 16"
RBGL-30	3,000 lbs.	42" x 90"	45" x 16"
RBGL-40	4,000 lbs.	36" x 90"	45" x 16"
RBGL-40	4,000 lbs.	42" x 90"	45" x 16"

Note: Minimum bed height is 36" when dock loading is not required. If dock loading, minimum bed height is 46" or greater based on platform size. Please refer specific questions about bed height and platform size to your Waltco representative.

OPTIONAL EQUIPMENT:

- Fold-Down Rear Retention Rails allow for faster, easier, unobstructed dock loading when the platform is lowered to below bed level while in the stored position
- Hand-held Pendant control allows driver to operate the liftgate from the truck bed or at ground level
- Dual Pump & Motor includes a backup power unit and switches
- Auxiliary Pump & Motor Unit with Pendant Control: Industry's only backup power system complete with secondary control switches
- Customized Options – contact factory

WALTCO

T: 800.211.3074
F: 800.211.3075
Email: sales@waltco.com
Web: www.waltcoliftgates.com

Waltco Lift Corp.
Corporate Office United States
285 Northeast Ave.
Tallmadge, OH 44278
P: 330.633.9191
F: 330.633.1418

Waltco Lift Corp.
United States
620 S Hambledon Ave.
City of Industry, CA 91744
P: 626.964.0990
F: 626.964.0149

Waltco Lift Inc.
Canada
90 North Queen St.
Etobicoke, ON M8Z 2C5