

STAHL<sup>®</sup>

3200LRX-15-EH

Crane Rating: 12,000 ft. lbs.

Maximum lifting capacity: 3,200 lbs.

Boom Length: 15'



### 15-FOOT TOTAL REACH

Hydraulic extension boom provides 11-ft. of reach with the manual boom adding an 4-ft. of reach

### SMOOTH OPERATION

Self-lubricating Nylatron™ bearing allows for smooth operation of inner and outer booms

### OPERATOR-FRIENDLY CONTROLS

Lightweight, multi-function remote control allows for single-handed operation of the crane

### SECURE FROM UNAUTHORIZED USE

Remote control unit can be quickly detached and locked away to prevent unauthorized use of the unit

Covered by a  
1-Year Limited Warranty



Get the complete  
Crane and Service Body package  
you need from STAHL

# LIFTING CAPACITIES\* - 3200 SERIES

REACH	RETRACTED BOOM	HYDRAULIC EXTENSION	MANUAL EXTENSION
3 ft.	3,200 lbs.		
4 ft.	3,000 lbs.		
5 ft.	2,400 lbs.		
6 ft.	2,000 lbs.		
7 ft.	1,710 lbs.		
8 ft.		1,500 lbs.	
9 ft.		1,330 lbs.	
10 ft.		1,200 lbs.	
11 ft.		1,090 lbs.	
12 ft.			1,000 lbs.
13 ft.			920 lbs.
14 ft.			855 lbs.
15 ft.			800 lbs.

\*Double Line is required for 1,600+ lb. loads

## SPECIFICATIONS

DESCRIPTION	SPECIFICATION
Total Boom Extension (Max.)	15 ft.
Hydraulic Extension	11 ft.
Manual Extension	4 ft.
Rotation System	360° continuous hydraulic on turntable bearing with worm drive and dynamic brake
Remote Control	Lightweight removable remote control unit with 25 ft. of cable
Winch Cable	62 ft. of 1/4" aircraft cable with latch hook, traveling block and down-haul weight
Winch	12V - DC electric motor - 1.8 hp. planetary gear with brake
Winch Line Speed	15 ft. per minute (single line)
Rotation Speed	1 RPM
Boom Elevation	-5° to +75°
Maximum Line Pull	1,600 lbs. single line / 3,200 lbs. double line
Weight	800 lbs.
Length	8 ft. - 11 in.
Width	20 in.
Height	28 in.
Minimum Chassis Requirements	10,000 GVW
Power Service Requirements	12V - DC chassis must have min. 60 amp alternator. Chassis battery must be HD maintenance type with min. 100 minute reserve and 500 cold cranking amps
Outrigger	Truck must be equipped with jackleg or outrigger

### Contact Us

3201 West Old Lincoln Way • Wooster, OH 44691  
 Phone: (800) 277-8245  
 Fax: (330) 264-0300  
 E-mail: info@stahl.cc  
 Web: www.stahltruckbodies.com

