

STAHL[®]



6000LRX-20-H

Crane Rating: 36,000 ft. lbs.

Maximum lifting capacity: 6,000 lbs.

Boom Length: 20 ft.

20-FOOT TOTAL REACH

Fully hydraulic extension boom provides 20-ft. of reach

SMOOTH OPERATION

Self-lubricating Nylatron™ bearing allows for smooth operation of inner and outer booms

OPERATOR-FRIENDLY CONTROLS

Lightweight, multi-function proportional radio remote control allows for single-handed operation of the crane

SECURE FROM UNAUTHORIZED USE

Remote control unit can be quickly detached and locked away to prevent unauthorized use of the unit

Covered by a
1-Year Limited Warranty



Get the complete Crane and Crane Body package you need from STAHL

LIFTING CAPACITIES* - 6000 SERIES

REACH	RETRACTED BOOM	FIRST HYDRAULIC EXTENSION	SECOND HYDRAULIC EXTENSION
3 - 5 ft.	6,000 lbs.		
6 ft.	6,000 lbs.		
7 ft.	5,140 lbs.		
8 ft.	4,500 lbs.		
9 ft.	4,000 lbs.		
10 ft.	3,600 lbs.		
11 ft.		3,270 lbs.	
12 ft.		3,000 lbs.	
13 ft.		2,770 lbs.	
14 ft.		2,570 lbs.	
15 ft.		2,400 lbs.	
16 ft.			2,250 lbs.
17 ft.			2,115 lbs.
18 ft.			2,000 lbs.
19 ft.			1,895 lbs.
20 ft.			1,800 lbs.

*Double Line is required for 2,500+ lb. loads

SPECIFICATIONS

DESCRIPTION	SPECIFICATION
Base Boom Length	10 ft.
First Hydraulic Extension	5 ft.
Second Hydraulic Extension	5 ft.
Rotation System	370° non-continuous hydraulic on turntable bearing with worm drive and dynamic brake
Remote Control	Proportional radio remote
Winch Cable	100 ft. of 5/16" aircraft cable with latch hook, traveling block and down-haul weight
Winch	Hydraulic planetary gear with brake
Winch Line Speed	60 ft. per minute (single line)
Rotation Speed	1 RPM
Boom Elevation	-5° to +75°
Maximum Line Pull	3,000 lb. single line / 6,000 lb. double line
Weight	950 lbs. (approx.)
Length	11 ft. - 6 in.
Width	20 in.
Height	30 in.
Minimum Chassis Requirements	14,500 GVW
Hydraulic Requirements	Pump output of 8 GPM @ 2750 PSI
Outrigger	Truck must be equipped with heavy-duty outrigger

Contact Us

3201 West Old Lincoln Way • Wooster, OH 44691

Phone: (800) 277-8245

Fax: (330) 264-0300

E-mail: info@stahl.cc

Web: www.stahltruckbodies.com

