

DOWNLIGHTS

TECHNICAL SPECIFICATION SHEET

DaxLite

Tel: 01252 311016
Email: sales@daxlite.com
Web: www.daxlite.com



Product: **Tilt GU10 Fire Rated Downlight**
Product Code: **DXGUFR7**
ISSUE A, 24.09.14

GENERAL DETAILS

Description	Tilt GU10 Shower Fire Rated Downlight. Die-cast bezel, steel can, with mechanical fire proof design. GU10 lampholder.
Overall Dimensions (mm)	Rim Dia: 96mm, 124mm Depth, 83mm Cut Out
Finishes Available	Bezel Finish: White, Satin Silver, Chrome, Polished Brass
Product Weight	0.4 kg
Ingress Protection	IP20

LIGHT SOURCE

Rated Wattage	Not Included
Lumens	
Lumens per Watt	
Recommended Product Location	Indoor
Light Source (brand) (type)	
Colour Temperature (K) Kelvin	
Light Source Life (Hrs)	
Photometric Data	

ELECTRICAL

Voltage (V)	220-240V. 50 Hz. AC
Running Current (I)	N/A
Total Running Wattage (W)	50W Max
Power Factor Correction (PFC)	N/A
Electrical Classification	Class I
Cabling (Electrical connections)	Screw fixed terminal

INSTALLATION

Distance from illuminated object	0.5m
Method of fix	Recessed in Ceiling
Recommended Working Temperature	Min -20°C to Max +40°C

MATERIALS

Main Housing (Material)	Steel
Front Shield (Material)	Die-cast Aluminium
Fixings (Main Housing)	2 pcs spring clips

APPROVALS

Guarantee	Lifetime* guarantee on fitting (from date of purchase)
Quality Assurance System	ISO9001:2008
Certification	CE, Darchem Flare,
Certificate of Conformity	Available on request
Manufactured in accordance to:	BS EN 60598-2-2, BS476 - part.20/21/23, BS EN ISO 140-3:1995, BS EN ISO 140-6:1998