

BULKHEADS

TECHNICAL SPECIFICATION SHEET

DaxLite

Tel: 01252 311016
Email: sales@daxlite.com
Web: www.daxlite.com



Product: 28W 2D Lunar Ceiling Light
Product Code: DX28WLUNAR
ISSUE A, 01.06.12

GENERAL DETAILS

Description	28W 2D Lunar Ceiling Light. Polycarbonate Body
Overall Dimensions (mm)	Dia: 330mm, 105mm Depth
Finishes Available	White Base. Opal Diffuser. Chrome Trim Available.
Product Weight	1.35 kg
Energy Rating	~
Ingress Protection	IP44

LIGHT SOURCE

Rated Wattage	28 Watts +/- 5%
Lumens	500 lumens (with diffuser)
Lumens per Watt	17.8 lumens per watt* (with diffuser)
Recommended Product Location	Indoor
Light Source (brand) (type)	2D Fluorescent Lamp
Colour Temperature (K) Kelvin	4000K / 6000K White
Colour Rendering Index CRI: Ra	CRI: Ra 87.1
Light Source Life (Hrs)	Average Life: 10,000 Hrs
Beam Angle	160°
Lamp working Temperature	<60°C

ELECTRICAL

Voltage (V)	240V +/- 10%. 50 Hz. AC
Running Current (I)	0.113 Amps
Total Running Wattage (W)	28.0W* (Includes light source and driver)
Power Factor Correction (PFC)	0.96
Electrical Classification	Class I
Cabling (Electrical connections)	0.5mm ² VDE Approved cable

INSTALLATION

Distance from illuminated object	0.5m
Method of fix	Surface Mount
Recommended Working Temperature	Min -10°C to Max +40°C

MATERIALS

Main Housing (Material)	Polycarbonate
Front Shield (Material)	Polycarbonate
Fixings (Main Housing)	Zinc Plated Screws

APPROVALS

Guarantee	2 Years (from date of purchase)
Quality Assurance System	ISO9001:2008
Certificate of Conformity	Available on request
Manufactured in accordance to:	BS EN 60598-2-1

DaxLite reserves the right to withdraw, improve or modify any design without prior notification. DaxLite cannot be held responsible for the incorrect application of any product.

Company Registration Number: 7955361 | VAT Number: 134182827