

ACCESSORIES

TECHNICAL SPECIFICATION SHEET

DaxLite

Tel: 01252 311016
Email: sales@daxlite.com
Web: www.daxlite.com



Product: **Photocell Kit**
Product Code: **DXCELLKIT**
ISSUE A, 23.03.12

GENERAL DETAILS

Description	Automatic Switch (On/Off) Dusk/Dawn
Overall Dimensions (mm)	125mm x 80mm x 85mm
Typical Load	2000W Tungsten or 2x400W HPS or 1800VA for use with standard Nema Socket
Product Weight	0.3 kg
Ingress Protection	IP65
Recommended Product Location	Outdoor
On/ Off Levels	20/80 Lux

ELECTRICAL

Voltage (V) (If applicable)	220-240V. 50Hz. AC
Time-delay	DC reply switch providing providing 15~20s
Electrical Classification (If applicable)	Class II

INSTALLATION

Method of Fix	Surface mount or recessed, 2 gang metal box
Recommended Working Temperature	Min -10°C to Max +30°C

MATERIALS

Main Materials	Polycarbonate Enclosure in Opal
Fixings	Brass

APPROVALS

Guarantee	2 Years (from date of purchase)
Symbols & Approval Marks	Easy-to-install Omni direction meeting BS 5972 with brackets
Quality Assurance System	QMS ISO9001:2008
Certificate of Conformity	Available on request
Manufactured in accordance to:	In compliance with BS EN60 598-1