

DOWNLIGHT TECHNICAL SPECIFICATION SHEET

DaxLite

Tel: 01252 311016
Email: sales@daxlite.com
Web: www.daxlite.com



Product: **DaxTILT 10W DOB LED IP40
TILT FIRE RATED DOWNLIGHT**
Product Code: **DXDT410 & DXDT310**
ISSUE A, 25.10.16

GENERAL DETAILS

Description	10 Watt DOB LED Tilt Fire Rated Downlight
Overall Dimensions (mm)	Depth: 83mm, Dia (Bezel edge to edge: 100mm)
Cut-out (mm)	Cut-out: 86mm
Finishes Available	Interchangeable bezels: Satin Silver/Chrome/White
Light Source Weight	0.29kg
Energy Rating	A
Ingress Protection	IP40
Fire Rating	30/60/90 Minutes

LIGHT SOURCE

Rated Wattage (Chip) & Brand	10 Watts (Epistar)
Lumens	700 lm (4000K), 650 lm (3000K)
Lumens per Watt	70 lm/W (4000K), 65 lm/W (3000K)
Recommended Product Location	Plasterboard ceilings
Beam Angle	60°
Colour Temperature (K) Kelvin	3000K/Warm White, 4000K/Cool White
Colour Rendering Index CRI: Ra	CRI: Ra 80
LED Life (Hrs)	Average Life: 50,000 Hrs
Photometric Data	Available on Request
Light Source Working Temperature	(LED Module) <55°C

ELECTRICAL

Voltage (V)	220V - 240V. 50 Hz. AC
Running Current (I)	0.05 Amps
Total Running Wattage (W)	10W +/- 5%
Dimmable	Yes. Suitable for use with selected dimmers
LED Driver	200 mA Constant Current AC
Electrical Classification	Class II

INSTALLATION

Distance from illuminated object	0.5m
Method of Fix	Spring Clip x2. 20A Fast Fix connector
Recommended Working Temperature	Min -10°C to Max +70°C

MATERIALS

Material Composition	Aluminium, Nylon, PMMA, Steel
----------------------	-------------------------------

APPROVALS

Guarantee	5 Years.
Building Compliance	Part B, Part E, Part C, Part L1 & Part L2
Marks & Symbols	CE. SELV
Manufactured in accordance to:	BS 476, BS EN 60 598

DaxLite reserves the right to withdraw, improve or modify any design without prior notification. DaxLite cannot be held responsible for the incorrect application of any product.

Company Registration Number: 7955361 | VAT Number: 134182827