## DOWNLIGHT TECHNICAL SPECIFICATION SHEET



Tel: 01252 311016 Email: sales@daxlite.com Web: www.daxlite.com



Product: DaxELITE10W DOB LED IP65
COLOUR SWITCHABLE FIRE RATED DOWNLIGHT
Product Code: DXEDF10

ISSUE A, 18.01.18

	1330L A, 16.01.16
GENERAL DETAILS	
Description	10 Watt COB LED Colour Switchable Fire Rated Downlight
Overall Dimensions (mm)	Depth: 74mm, Dia (Bezel edge to edge: 85mm)
Cut-out (mm)	Cut-out: 75mm
Finishes Available (die-cast aluminium)	Supplied With White, Brushed & Polished Chrome Bezels
Light Source Weight	0.44kg
Energy Rating	A
Ingress Protection	IP65
Fire Rating	30/60/90 Minutes
LIGHT SOURCE	
Rated Wattage (Chip) & Brand	10 Watts (Sharp)
Lumens	700 lm (6000K), 800 lm (4000K), 700 lm (3000K)
Lumens per Watt	70 lm/W (6000K), 80 lm/W (4000K), 70 lm/W (3000K)
Recommended Product Location	Plasterboard ceilings
Beam Angle	60°
Colour Temperature (K) Kelvin	6000K/Daylight, 4000K/Cool White, 3000K/Warm White
Colour Rendering Index CRI: Ra	CRI: Ra 80
LED Life (Hrs)	Average Life: 50,000 Hrs
Photometric Data	Available on Request
Light Source Working Temperature	(LED Module) <70°C
ELECTRICAL	
Voltage (V)	220V - 240V. 50 Hz. AC
Running Current (I)	0.05 Amps
Total Running Wattage (W)	10W +/- 5%
Dimmable	Yes. Suitable for use with selected dimmers
LED Driver	260 mA Constant Current AC
Electrical Classification	Class II
INSTALLATION	
Distance from illuminated object	0.5m
Method of Fix	Spring Clip x2. 20A Fast Fix connector
Recommended Working Temperature	Min -10°C to Max +70°C
MATERIALS	
Material Composition	Aluminium, Nylon, PMMA, Steel
APPROVALS	
Guarantee	7 Years.
Building Compliance	Part L1 & Part L2 (as of 2014)
Marks & Symbols	CE. SELV
Manufactured in accordance to:	BS 476, BS EN 60 598